

# Plastikman

Plastic repair putty



**PLASTIKMAN** can be used to rebuild rigid and semi-threadable plastics, repair automotive trim or plastic furniture, and to seal leaks in plastic plumbing pipes. **PLASTIKMAN** forms a durable bond to all major plastic types except ployoletim (polyethylene /phypropylene), and can be molded into any shape, drilled, sanded and painted. Great when fast repairs are needed for high use areas. Work life is 25 minutes and final cure is only 3 hours. **PLASTIKMAN** has a 300 volt di-electric strength. For other surface repairs please also try Omega's **STEELMAN**, **CONCRETEMAN**, and **WOODMAN** repair putty.

**Directions:** For best results, clean and roughen area to be repaired by sanding or filing. Twist off desired amount of **PLASTIKMAN** and knead into a uniform color. Apply at once as hardening begins immediately. For a smooth finish, hand rub with tap water or use damp cloth or tool prior to hardening. Wash hands and tools after use to remove any residue. Omega's **MUSCLEMAN** hand towels are a convenient way to clean hands and tools anywhere, anytime. No water needed.

**Areas of Use:**

- \*plumbing department
- \*HVAC
- \*water treatment
- \*sewer departments
- \*groundskeepers
- \*building maintenance
- \*schools
- \*apartment complexes
- \*amusement parks
- \*golf courses

Health	1
Flammability	1
Reactivity	0
Protection	B

Appearance and odor.....	Blue/white putty, characteristic odor
Specific Gravity.....	Concentrate - 1.9
VOC.....	<1%
NFPA Fire Rating.....	Flammable

**ONLY OMEGA™**

Fairfield, CA 94534

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134