

Steelman

Steel Reinforced Putty



STEELMAN is a hand kneadable, steel reinforced, epoxy putty that mixes in just one minute to provide fast repairs to items made of ferrous and aluminum metals. **STEELMAN** comes in a handy "tootsie-roll" form with the curing agent encapsulated in the contrasting color base material. The putty-like consistency eliminates drips and runs, providing "no mess" applications with no tools required for use. **STEELMAN** is resistant to water, chemicals, and extreme temperatures. Hardens like steel in one hour, then it can be drilled, tapped, machined, filed, etc. Use **STEELMAN** to make repairs to metal, wood, concrete, copper, aluminum, fiberglass, plaster and many plastics. Repairs cracks and seals leaks, use on dethreaded bolts and screws, sink traps and more. May cause mild skin irritation, use Omega's **SHIELD** skin protector to reduce potential for irritation while maintaining dexterity. For other surface specific repairs, also try Omega's **WOODMAN**, **CONCRETEMAN**, and **PLASTIKMAN** repair putty.

Directions: Before applying, roughen and clean the area to be repaired. Then follow these easy steps: 1) **CUT** or twist off required amount. 2) **MIX** by kneading with fingers to a uniform color. If mixing is difficult, warm **STEELMAN** to room temperature or slightly above. 3) **APPLY** to surface to be repaired within 2 minutes of mixing. For best adhesion, force into any cracks or holes and strike off excess material, preferably with a tool moistened with clean water. *When applying to a damp, wet or slowly leaking area, work the mixed epoxy putty forcefully into the surface and apply pressure until adhesion begins to take effect.* **For best results:** Use damp fingers for easier mixing, application and a smooth appearance of the cured compound. Remove excess material before hardening begins. **CURING: STEELMAN** has a 3 to 5 minutes work life. Functional cure occurs in one hour. **NOT INTENDED FOR STRUCTURAL APPLICATIONS.** Wash hands and tools to remove residue. If no water source is available, use Omega's **ROUGHMAN** hand towels to clean hands and tools.

Areas of Use:

- *vehicle maintenance
- *building maintenance
- *HVAC
- *sign shop
- *plumbing shop
- *school districts

Health	1
Flammability	1
Reactivity	0
Protection	B

Appearance and odor.....	Metallic/white putty, Slight odor
Specific Gravity.....	Concentrate - 1.9
VOC.....	<1%
NFPA Fire Rating.....	Flammable class IIIB

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134