

Wet Alert

Slip Hazard Indicator



WET ALERT is designed to alert the public of unsafe conditions that may pose a safety hazard. When applied to unsealed concrete. **WET ALERT** is undetected until the surface becomes wet due to rain, water leaks, spills, etc. Once the treated area becomes wet, the words CAUTION WET are visible in 4-inch high letters. This quickly alerts personnel in the area that there is an unsafe condition that cause accidents due to slipping.

Directions:

WET ALERT works best when unsealed concrete surface is clean and dry. Place stencil over area to be treated. Spray cut out in stencil with **WET ALERT** lightly and with continuous side to side motion holding bottle 6-8 inches from stencil, wetting concrete surface completely. Do not over apply product. It should only take about a half ounce of product per application. leave stencil in place until application is dry, approximately 3 to 5 minutes. Drying time will vary depending on conditions at the time of application. Treated area should be ready for use 30 minutes after application. Keep from freezing.

Areas of Use:

- *schools
- *industrial plants
- *warehouses
- *public walkways

- *loading docks
- *driveways
- *exits and entrances to buildings

Health	3
Flammability	0
Reactivity	0
Protection	B

Appearance and odor.....	Colorless liquid with bland odor
Specific Gravity.....	Concentrate - 1.04
% Volatile by Volume.....	94%
NFPA Fire Rating.....	Non-flammable Spray

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134