

Plug It

Spill Control



Plug It seals off gasoline, diesel, solvents and other chemicals (hydrocarbons). **Plug It** seals immediately and sticks to dirty, crumpled surfaces even with the fluid flowing out. No surface preparation is required. **Plug It** will plug up to 3 feet of head (1.5 psi) even if the liquid is flowing out. Not recommended for some biofuels, and other chemicals such as strong acids, caustics and oxidizers. **Plug It** can be used to plug a 6-inch diameter hole and a slit 1 inch by 2 feet. **Plug It** is intended as an immediate temporary seal.

Directions: No surface preparation is necessary. Put on latex gloves. Take a handful of **Plug It** and apply it directly into and around the edges of the leak. The initial contact of **Plug It** may only partly adhere to the surface. Work it and press down to get good adhesion. Apply enough **Plug It** to get a good thick layer over the leak. Additional **Plug It** can be added over the top. Do not use **Plug It** on Urethane or Teflon surfaces. Non-Toxic and Non-Flammable. Store above freezing. Remove any contaminated materials from inside container before closing tightly after use.

Health	0
Flammability	0
Reactivity	0
Protection	N/A

Appearance and odor.....	Gray heavy paste-like consistency, odorless
Specific Gravity.....	Concentrate - 1.4
VOC.....	N/A
NFPA Fire Rating.....	Non-Flammable

ONLY OMEGA™

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com www.facebook.com/onlyomega Fax: 707-864-8134