

**Material Safety Data Sheet**

May be used to Comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be Consulted for specific requirements

HMIS

<b>HEALTH</b>	<b>1</b>	<b>REACTIVITY</b>	<b>0</b>
<b>FLAMMABILITY</b>	<b>0</b>	<b>PERSONAL PROTECTION</b>	<b>B</b>

**Identity (As Used On Label and List)****A1107 Enviro Clean**

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

**Section I****Manufactured for:**

OMEGA INDUSTRIAL SUPPLY, INC

**Emergency Telephone Number:**

1-800-424-9300

**Address (Number, Street, City, State, and Zip Code)**

101 Grobriic Ct #1

**Telephone Number for Information:**

1-800-571-7347

Fairfield, CA 94534

**Date Prepared**

11-07-2007

**Signature of Prepare (Optional)**

REGULATORY DEPT.

**Section II - Ingredients / Identity Information****Components**

(Specific Chemical Identity, Common Name(s))

**CAS No.****OSHA PEL****TLV-TWA****Other Limits****Recommended.****%(Wt.)**

Liquefied Petroleum Gas

68476-86-8

1000 ppm

1000 ppm

This product is not known to contain any compounds listed and in quantities requiring reporting under SARA Title III Section 313.

Any substance listed as hazardous by the State of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

**Section III - Physical Chemical Characteristics**

<b>Boiling Point</b>	212°F	<b>Specific Gravity (H<sub>2</sub>O = 1) @ 70°F Concentrate</b>	1.00
<b>Vapor Pressure (psig @ 72°F)</b>	55	<b>Total VOC %</b>	6.71%
<b>Vapor Density (Air=1)</b>	>1	<b>Evaporation Rate (Butyl Acetate = 1)</b>	—
<b>Solubility in Water</b>	Complete	<b>pH</b>	9.2

**Appearance and Odor**—White foam with fresh fragrance.

**Section IV – Fire and Explosion Hazard Data**

<b>USA Flame Projection Test (ASTM D-3065)</b> Non Flammable Spray	<b>Flammable Limits</b> None to boiling	<b>LEL</b> N/A	<b>UEL</b> N/A
---	--	-------------------	-------------------

**Extinguishing Media** – Foam, CO<sub>2</sub>, dry media.

**Special Fire Fighting Procedures** – Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

**Unusual Fire and Explosion Hazards** – Exposure to temperature above 120°F may cause bursting.

Page 2 of 2 for A1107 Enviro Clean

**Section V – Reactivity Data**

<b>Stability</b>	Unstable	X	<b>Conditions to Avoid</b> – None	<b>Hazardous Polymerization</b>	<b>May Occur</b>
	Stable				

Will Not Occur

X

**Incompatibility (Materials to Avoid)** – Strong oxidizing agents.

**Hazardous Decomposition or Byproducts** – Carbon monoxide, carbon dioxide.

## Section VI – Health Hazard Data

Route(s) of Entry:	Eyes?	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes	Yes

**Health Hazards (Acute and Chronic)** –

*See Below*

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

### Signs and Symptoms of Exposure:

*Eyes*—May cause moderate irritation.

*Skin*—Frequent or prolonged contact may cause irritation. May aggravate existing skin conditions.

*Inhalation*—Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

*Ingestion*—Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

**Medical Conditions Generally Aggravated** –May aggravate existing skin conditions.

### Emergency and First Aid Procedures.

*Eyes*— Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

*Skin*—Wash with soap and water. If irritation persists seek medical attention.

*Inhalation*—Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

*Ingestion*—Do not induce vomiting. Seek medical attention immediately.

## Section VII – Precautions For Safe Handling and Use

### Steps to be Taken in Case Material is Released or Spilled.

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal state and local law.

**Waste Disposal Method** – Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

### Precautions to be Taken in Handling and Storing –

Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F.

**Other Precautions** –KEEP OUT OF REACH OF CHILDREN

## Section VIII – Control Measures

### Respiratory Protection (Specify Type) –

None needed for proper use in accordance with label directions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

### Protective Gloves –

Use chemical resistant gloves if hand contact will be made.

**Eye Protection** –Always wear safety glasses or chemical proof goggles when working with chemicals.

**Other protective Clothing or Equipment** – N/A

**Work/Hygienic Practices** – Observe good hygiene. Wash hands thoroughly after eating, drinking, and using restrooms, etc.

While the information and recommendations set forth herein are believed to be accurate as of the date hereon Omega Industrial Supply Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon.