

# Material Safety Data Sheet

May be used to Comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be Consulted for specific requirements

## HMIS

<b>HEALTH</b>	<b>1</b>	<b>REACTIVITY</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>2</b>	<b>PERSONAL PROTECTION</b>	<b>A</b>

### Identity (As Used On Label and List)

**A1140 X-42**

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

### Section I

#### Manufactured for:

OMEGA INDUSTRIAL SUPPLY, INC

#### Emergency Telephone Number:

1-800-424-9300

#### Address (Number, Street, City, State, and Zip Code)

4950-B Fulton Drive

#### Telephone Number for Information:

1-800-571-7347

Fairfield, CA 94534

#### Date prepared

03-01-2006

#### Signature of Prepare (Optional)

REGULATORY DEPT.

### Section II - Hazardous Ingredients / Identity Information

#### Hazardous Components

(Specific Chemical Identity, Common Name(s))

CAS No.

OSHA PEL

ACGIH-TLV

Other Limits Recommended.

%(Opt.)

Hydrotreated Naph. Dist

64742-52-5

5mg/m<sup>3</sup>

5mg/m<sup>3</sup>

N/A

Naphthenic Petroleum Dist

64742-53-6

5mg/m<sup>3</sup>

5mg/m<sup>3</sup>

Propane/N-Butane

68476-86-8

1000 ppm

600 ppm

N/A

This product is not known to contain any compounds listed and in quantities requiring reporting under SARA Title III Section 313.

Any substance listed as hazardous by the State of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

### Section III - Physical Chemical Characteristics

#### Boiling Point

600+

#### Specific Gravity (H<sub>2</sub>O = 1) Concentrate

0.92

#### Vapor Pressure (mm/Hg)

<0.01

#### Melting Point

N/A

#### Vapor Density (Air=1)

N/A

#### Evaporation Rate (Butyl Acetate=1)

<0.1

#### Solubility in Water

0%

#### pH

—

#### Appearance and Odor—

Straw colored liquid, mild petroleum odor.

#### VOC%

20%

### Section IV – Fire and Explosion Hazard Data

#### USA Flame Projection Test (ASTM D-3065)

+200°F TCC

#### Flammable Limits

Flammable

#### LEL

N/A

#### UEL

N/A

**Extinguishing Media** –Standard dry chemical fire extinguisher.

**Special Fire Fighting Procedures** – Self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards** – Contents under pressure. Exposure to temperatures above 120°F may cause bursting.

**Section V – Reactivity Data**

Stability	Unstable	<input type="checkbox"/>	Conditions to Avoid – Temperatures above 120°F	Hazardous Polymerization	May Occur	<input type="checkbox"/>
	Stable	X			Will Not Occur	X

Incompatibility (Materials to Avoid) – None

Hazardous Decomposition or Byproducts – None

**Section VI – Health Hazard Data**

Route(s) of Entry:	Eyes? Yes	Inhalation? Yes	Skin? Yes	Ingestion? Yes
--------------------	--------------	--------------------	--------------	-------------------

Health Hazards (Acute and Chronic) –  
See Below

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? No
------------------	------------	------------------------	-----------------------

**Signs and Symptoms of Exposure:**

- Eyes—May cause irritation.
- Skin— May cause localized dryness and/or irritation.
- Inhalation— May cause dizziness.
- Ingestion—.Nausea, sickness.

Medical Conditions Generally Aggravated –None Known

**Emergency and First Aid Procedures:**

- Eyes—Flush thoroughly with water for 15 minutes.
- Skin—Flush with water. Consult physician if needed.
- Inhalation—Remove to fresh air. Consult physician if difficulty in breathing persists.
- Ingestion—Do not induce vomiting. Contact physician immediately.

**Section VII – Precautions For Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled–  
Wipe up with rag or use some absorbent clay material.

Waste Disposal Method – Dispose of residue in accordance with federal, state and local regulations.

Precautions to be Taken in Handling and Storing –  
Do not use or store near heat or open flames. Exposure to temperatures above 120°F may cause bursting.

Other Precautions – None

**Section VIII – Control Measures**

Respiratory Protection (Specify Type) –  
Use only in well ventilated area.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)	Adequate	Other

Protective Gloves – N/A	Eye Protection –. Safety goggles are recommended whenever chemical are used.
----------------------------	---

Other protective Clothing or Equipment – N/A

Work/Hygienic Practices – Observe good hygiene. Wash hands thoroughly after eating, drinking, and using restrooms, etc.

While the information and recommendations set forth herein are believed to be accurate as of the date hereon Omega Industrial Supply Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon.