

Material Safety Data Sheet

May be used to Comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be Consulted for specific requirements

HMIS

HEALTH

1

REACTIVITY

0

FLAMMABILITY

4

PERSONAL PROTECTION

B

Identity (As Used On Label and List)

A1096 EZ Kleen Xtra

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufactured for:

OMEGA INDUSTRIAL SUPPLY, INC

Emergency Telephone Number:

1-800-424-9300

Address (Number, Street, City, State, and Zip Code)

101 Grobric Ct #1

Telephone Number for Information:

1-800-571-7347

Fairfield, CA 94534

Date prepared

09-17-2013

Signature of Prepare (Optional)

REGULATORY DEPT.

Section II - Hazardous Ingredients / Identity Information

Components

(Specific Chemical Identity, Common Name(s))

CAS No.

OSHA PEL

ACGIH-TLV

Other Limits

Recommended.

%(Wt.)

Sodium Metasilicate

6834-92-0

15mg/m³

10mg/m³

< 3.0%

Diethylene Glycol Monoethyl Ether *

111-90-0

N/E

N/E

< 12.0 %

Propellant Mixture

Propane

74-98-6

1000 ppm

N/A

< 5 %

N-Butane

106-97-8

600 ppm

N/A

< 5 %

*This product contains the toxic chemicals marked with an * subject to the reporting requirements of Section 313 of the emergency planning and community right-to know act of 1986 and of 40CFR372.

Section III - Physical Chemical Characteristics

Boiling Point

200°F

Specific Gravity (H₂O = 1)

Concentrate

1.04

Vapor Pressure (mm/hg)

N/E

Melting Point

Vapor Density (Air=1)

N/E

Evaporation Rate (Butyl Acetate = 1)

N/E

Solubility in Water

Complete

pH

12.5

Appearance and Odor—

Slightly cloudy, colorless spray with mild odor.

VOC % Content

17.5%

Section IV – Fire and Explosion Hazard Data

Flash Point

No flash by standard methods

Flammable Limits

LEL

N/A

UEL

N/A

Extinguishing Media – Dry chemical, CO₂, or foam is recommended.

Special Fire Fighting Procedures –CAUTION. Contents under pressure. Cool exposed containers with water spray to prevent bursting. SCBA should be used whenever chemical fires are present.

Unusual Fire and Explosion Hazards – N/A