

Material Safety Data Sheet

May be used to Comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be Consulted for specific requirements

NFPA

HEALTH	1	REACTIVITY	0
FLAMMABILITY	1	PERSONAL PROTECTION	-

Identity (As Used On Label and List) B4112P Sweeping Compound	Date Prepared 11-25-2008
---	-----------------------------

Section I

Manufactured for: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobriic Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section II - Ingredients / Identity Information

Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH-TLV	%(Wt.)
Distillates, hydrotreated heavy paraffinic	64741-96-4	-	5 mg/m3 (mist)	< 7%

Section III - Physical Chemical Characteristics

Boiling Point	N/D	Specific Gravity (H ₂ O = 1) Concentrate	0.78
Vapor Pressure (mm/hg)	N/D	Melting Point	N/D
Vapor Density (Air=1)	N/D	Evaporation Rate (Butyl Acetate = 1)	-
Solubility in Water	Complete	pH	-
Appearance and Odor— Reddish-brown granular powder with mild pine odor.		VOC Content by weight	-

Section IV - Fire and Explosion Hazard Data

Flash Point (Method)	> 350°F (PMCC)	Flammable Limits	LEL	-	UEL	-
----------------------	----------------	------------------	-----	---	-----	---

Extinguishing Media – Standard fire fighting media, including water fog, foam, dry chemical and carbon dioxide.

Special Fire Fighting Procedures - When this product is involved in a fire, firefighters should wear protective clothing and self-contained breathing apparatus to avoid exposure to vapors or products of combustion.

Unusual Fire and Explosion Hazards – Sealed drums can develop explosive pressure under fire conditions. Use a water spray to cool.

Section V - Reactivity Data

Stability:	Unstable <input type="checkbox"/>	Stable <input checked="" type="checkbox"/>	Conditions to Avoid – High temperatures, flames, incompatibles.	Hazardous Polymerization:	May Occur <input type="checkbox"/>	Will Not Occur <input checked="" type="checkbox"/>
Incompatibility (Materials to Avoid) – Strong oxidizing agents.			Hazardous Decomposition or Byproducts – High temperatures and flames may produce toxic oxides of carbon and other products of incomplete combustion.			

Section VI - Health Hazard Data

Carcinogenicity:	NTP?	No	IARC Monographs?	No	OSHA Regulated?	No
------------------	------	----	------------------	----	-----------------	----

Signs and Symptoms of Exposure:

Eyes— Irritating to the eyes resulting in reddening and tearing.

Skin— Mild irritant that can cause reddening of the skin.

Inhalation— Airborne concentrations of vapors may cause irritation to the upper respiratory tract and lungs.

Ingestion— Can cause irritation of the mucous membranes in the mouth, throat, esophagus, and stomach and upset stomach.

Emergency and First Aid Procedures.

Eyes— Immediately flush with flowing water, alternately lifting the upper and lower eyelids. If appropriate, after 5 minutes, remove contact lenses and continue flushing the eyes for an additional 15 minutes. Get medical attention if irritation develops or persists.

Skin— Flush the area with flowing water for at least 15 minutes, while removing contaminated clothing. Launder clothing before reuse. Launder clothing before reuse.

Inhalation— Move the victim to fresh air. Give artificial respiration if breathing has stopped. Get immediate medical attention.

Ingestion— Rinse mouth and drink 2 or 3 glasses of water. Do NOT induce vomiting or give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled. Eliminate all ignition sources. Wear chemically protective clothing. Contain spill using an inert diking material. Transfer material into an approved container for possible recovery and reuse or for disposal. Keep product out of sewers, watersheds, and water systems.

Waste Disposal Method – Material that cannot be recovered and reused should be disposed of in accordance with all Federal, State, and local regulations.

Precautions to be Taken in Handling and Storing – Containers should be stored in a cool, dry, well-ventilated area. Exercise due caution to prevent damage to a leakage from the container. Avoid contact with ignition sources and strong oxidizing agents. Keep containers closed when not in use.

Use good industrial practices in the storage, handling, and distribution of this product. Containers, even those that have been emptied, will retain product residue. Always obey hazard warning and handle empty containers as if they are full.

Section VIII - Control Measures

Respiratory Protection (Specify Type) – Avoid prolonged breathing of vapors. Use a NIOSH/MSHA approved respirator, with a full-face piece or full-face respirator with organic vapor/mist cartridges when concentrations are unknown.	Ventilation – Provides adequate mechanical or local exhaust ventilation to minimize exposure levels.
Protective Gloves – When in contact with the product, the wearing of neoprene, silver shield or Viton gloves is recommended.	Eye Protection – Under normal use conditions, the wearing of chemical splash goggles should not be necessary. An eye wash fountain should be located in areas where the product is used.

Work/Hygienic Practices – Observe good hygiene. Wash hands thoroughly after product use, eating, drinking, and using restrooms, etc.

Information presented herein was compiled from sources considered dependable and is accurate and reliable to the best of our knowledge, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, express or implied, except those that are stated in corresponding labels and technical literature.