

Section 1 ~ Identification

Identity (As Used On Label and List) A1122 AIR TOOL REJUVENATOR	Date Prepared: 11-17-205
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards	Flammable aerosols	Category 1
Health Hazards	Reproductive Toxicity	Category 2
	Aspiration Hazard	Category 1
OSHA Defined Hazards	Not classified.	

Label Elements



Signal Word: Danger.

Hazard Statement

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child.

Precautionary Statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. If exposed or concerned: Get medical advice/attention. Do NOT induce vomiting.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not Otherwise Classified (HNOC)

None known.

Supplemental Information

None.

Section 3 ~ Composition/Information on Ingredients

Chemical Name	Common Name & Synonyms	CAS No.	%(Wt.)
Solvent Naphtha (Petroleum), Light Aliphatic		64742-89-8	20 – 40
Butane		106-97-8	10 – 20
Naphtha, Petroleum, Light Alkylate		64741-66-8	10 – 20
White Mineral Oil (petroleum)		8042-47-5	10 – 20
Ethyl Alcohol		64-17-5	2.5 – 10
Heptane, branched, cyclic and linear		426260-76-6	2.5 – 10
Propane		74-98-6	2.5 – 10
n-Heptane		142-82-5	1 – 2.5
Cyclohexane		110-82-7	0.1 – 1
Octane		111-65-9	0.1 – 1
Toluene		108-88-3	0.1 – 1
Other components below reportable levels			2.5 – 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye Contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Most Important Symptoms/Effects, Acute and Delayed: Aspiration may cause pulmonary edema and pneumonitis.

Indication of Immediate Medical Attention and Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire -Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol. Combustible.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface

is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Level 3 Aerosol.

Conditions for Safe Storage, Including Any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Cyclohexane (110-82-7)	PEL	1050 mg/m3 300 ppm
Ethyl Alcohol (64-17-5)	PEL	1900 mg/m3 1000 ppm
n-Heptane (14-82-5)	PEL	2000mg/m3 500 ppm
Octane (111-65-9)	PEL	2350 mg/m3 500 ppm
Propane (74-98-6)	PEL	1800 mg/m3 1000 ppm

US OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (106-97-8)	STEL	1000 ppm
Cyclohexane (110-82-7)	TWA	100 ppm
Ethyl Alcohol (64-17-5)	STEL	1000 ppm
n-Heptane (142-82-5)	STEL	500 ppm
	TWA	400 ppm
Octane (111-65-9)	TWA	300 ppm
Toluene (108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (106-97-8)	TWA	1900 mg/m3 800 ppm
Cyclohexane (110-82-7)	TWA	1050 mg/m3 300 ppm
Ethyl Alcohol (64-17-5)	TWA	1900 mg/m3 1000 ppm
n-Heptane (142-82-5)	Ceiling	1800 mg/m3 440 ppm
	TWA	350 mg/m3 85 ppm
Octane (111-65-9)	Ceiling	1800 mg/m3 385 ppm
	TWA	350 mg/m3 75 ppm
Propane (74-98-6)	TWA	1800 mg/m3 1000 ppm
Toluene (108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure Guidelines

US - California OELs: Skin designation Toluene (108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies: Toluene (108-88-3) Skin designation applies.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Chemical goggles are recommended.

Skin Protection

Hand Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical and Chemical Properties

Appearance

Physical State: Gas.

Form: Aerosol.

Color: Not available.

Odor: Not available.

Odor Threshold: Not available.

pH: Not available.

Melting Point/Freezing Point: Not available.

Initial Boiling Point and Boiling Range: 655°F (346.11°C) estimated

Flash Point: -156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation Rate: Not available.

Flammability (solid, gas): Not available.

Upper/Lower Flammability or Explosive Limits

Flammability Limit - Lower (%): 1.3 % estimated

Flammability Limit - Upper (%): 7 % estimated

Explosive Limit - Lower (%): Not available.

Explosive Limit - Upper (%): Not available.

Vapor Pressure: Not available.

Vapor Density: Not available.

Relative Density: Not available.

Solubility(ies)

Solubility (water): Not available.

Partition Coefficient (n-octanol/water): Not available.

Auto-Ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: Not available.

Other Information

Explosive Properties: Not explosive.

Oxidizing Properties: Not oxidizing.

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.

Section 11 ~ Toxicological Information

Information on Likely Routes of Exposure

Inhalation: No adverse effects due to inhalation are expected.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Direct contact with eyes may cause temporary irritation.

Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Aspiration may cause pulmonary edema and pneumonitis.

Information on Toxicological Effects

Acute Toxicity: May be fatal if swallowed and enters airways.

<i>Components</i>	<i>Species</i>	<i>Test Results</i>
Butane (106-97-8) Acute Inhalation LC50	Mouse Rat	1237 mg/l, 120 Minutes 52%, 120 Minutes 1355 mg/l
Cyclohexane (110-82-7) Acute Dermal LD50 Inhalation LC50	Rabbit Rat	> 2000 mg/kg >32880 mg/m ³ , 4 Hours >5540 ppm, 4 Hours
Oral LD50	Rabbit Rat	>5000 mg/kg >5000 mg/kg
Ethyl Alcohol (64-17-5) Acute Inhalation LC50	Cat Mouse Rat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours >60000 ppm 79.43 mg/l, 134 Minutes >115.9 mg/l, 4 Hours 51.3 mg/l, 6 Hours
Oral LD50	Pig Rat	>5000 mg/kg 10470 mg/kg
Naphtha, Petroleum, Light Alkylate (64741-66-8) Acute Dermal LD50 Inhalation LC50	Rabbit Rat	>1900 mg/kg, 24 Hours > 5000 mg/m ³ , 4 Hours > 4980 mg/m ³ > 4980 mg/m ³ , 4 Hours > 4.96 mg/l, 4 Hours
Oral LD50	Rat	>5000mg/kg
n-Heptane (142-82-5) Acute Dermal LD50 Inhalation LC50 Oral LD50	Rabbit Rat Rat	>2000 mg/kg, 24 Hours >29.29 mg/l, 4 Hours >5000 mg/kg
Octane (111-65-9) Dermal LD50 Inhalation LC50 Oral LD50	Rabbit Rat Rat	>2000 mg/kg, 24 Hours >24.88 mg/l, 4 Hours >5000 mg/kg
Propane (74-98-6) Acute Inhalation LC50	Mouse Rat	1237 mg/l, 120 Minutes 52%, 120 Minutes 1355 mg/l 658 mg/l/4h
Solvent Naphtha (Petroleum), Light Aliphatic (64742-89-8) Acute Dermal LD50 Inhalation LC50	Rabbit Rat	>1900 mg/kg, 24 Hours > 5000 mg/m ³ , 4 Hours > 4980 mg/m ³ > 4980 mg/m ³ , 4 Hours > 4.96 mg/l, 4 Hours
Oral LD50	Rat	4820 mg/kg
Toluene (108-88-3) Acute Dermal LD50 Inhalation LC50	Rabbit Mouse	>5000 mg/kg, 24 Hours 6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
Oral LD50	Rat	5879 - 6281 ppm, 6 Hours 25.7 mg/l, 4 Hours >5000 mg/kg
White Mineral Oil (petroleum) (8042-47-5) Acute Dermal LD50 Inhalation LC50 Oral LD50	Rabbit Rat Rat	>2000 mg/kg, 24 Hours 2.18 mg/l, 4 Hours >5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Prolonged skin contact may cause temporary irritation.

Serious Eye Damage/Eye Irritation: Direct contact with eyes may cause temporary irritation.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity: Toluene (108-88-3) 3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.
US. National Toxicology Program (NTP) Report on Carcinogens: Not available.
Reproductive Toxicity: Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure: Not classified.
Specific Target Organ Toxicity - Repeated Exposure: Not classified.
Aspiration Hazard: May be fatal if swallowed and enters airways.

Section 12 ~ Ecological Information

Ecotoxicity: Toxic to aquatic life with long lasting effects.

<u>Components</u>		<u>Species</u>	<u>Test Results</u>
Cyclohexane (110-82-7)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
Ethyl Alcohol (64-17-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100.1 mg/l, 96 hours
Naphtha, Petroleum, Light Alkylate (64741-66-8)			
Aquatic			
Algae	IC50	Algae	30000 mg/L, 72 Hours
n-Heptane (142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Toluene (108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential

Partition coefficient n-octanol / water (log Kow)

Butane 2.89	Cyclohexane 3.44
Ethyl Alcohol -0.31	n-Heptane 4.66
Octane 5.18	Propane 2.36
Toluene 2.73	

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section 14 ~ Transportation Information

<u>DOT</u>	<u>IATA</u>	<u>IMDG</u>
UN Number: UN1950	UN Number: UN1950	UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)	UN Proper Shipping Name: Aerosols, flammable	UN Proper Shipping Name: AEROSOLS
Transport Hazard Class(es)	Transport Hazard Class(es)	Transport Hazard Class(es)
Class 2.1	Class 2.1	Class 2.1
Subsidiary Risk -	Subsidiary Risk -	Subsidiary Risk -
Label(s) 2.1	Label(s) 2.1	Label(s) None
Packing Group: Not applicable.	Packing Group Not applicable.	Packing Group: Not applicable.
Special Provisions: N82	Environmental Hazards: Yes	Environmental Hazards
Packaging Exceptions: 306	ERG Code 10L	Marine Pollutant: Yes
Packaging Non Bulk: None	Other Information	EmS F-D, S-U
Packaging Bulk: None	Passenger and Cargo Aircraft: Allowed with restrictions.	Packaging Exceptions: LTD QTY
	Cargo Aircraft Only Allowed with restrictions.	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.
	Packaging Exceptions LTD QTY	

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

General Information: DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

DOT



IATA;IMDG



Marine Pollutant



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Cyclohexane (110-82-7) Listed.

Toluene (108-88-3) Listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard – Yes
Pressure Hazard – Yes

Delayed Hazard – Yes
Reactivity Hazard – No

Fire Hazard – Yes

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Cyclohexane	110-82-7	0.1 – 1
Toluene	108-88-3	0.1 – 1

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Toluene (108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane (106-97-8) Propane (74-98-6)

Safe Drinking Water Act Not regulated. (SDWA): Not regulated.

Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number: Toluene (108-88-3) 6594

Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)): Toluene (108-88-3) 35 % WV

DEA Exempt Chemical Mixtures Code Number: Toluene (108-88-3) 594

US State Regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (106-97-8)

Naphtha, Petroleum, Light Alkylate (64741-66-8)

Solvent Naphtha (Petroleum), Light Aliphatic (64742-89-8)

Toluene (108-88-3)

US. Massachusetts RTK - Substance List

Butane (106-97-8)

Cyclohexane (110-82-7)

Ethyl Alcohol (64-17-5)

n-Heptane (142-82-5)

Octane (111-65-9)

Propane (74-98-6)

Toluene (108-88-3)

US. New Jersey Worker and Community

Right-to-Know Act

Butane (106-97-8)

Cyclohexane (110-82-7)

Ethyl Alcohol (64-17-5)

n-Heptane (142-82-5)

Octane (111-65-9)

Propane (74-98-6)

Toluene (108-88-3)

US. Pennsylvania Worker and Community

Right-to-Know Law

Butane (106-97-8)

Cyclohexane (110-82-7)

Ethyl Alcohol (64-17-5)

n-Heptane (142-82-5)

Octane (111-65-9)

Propane (74-98-6)

Toluene (108-88-3)

US. Rhode Island RTK

Butane (106-97-8)

Cyclohexane (110-82-7)

Propane (74-98-6)

Toluene (108-88-3)

US. California Proposition 65 WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (71-43-2) Listed: February 27, 1987

Ethyl Benzene (100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (71-43-2) Listed: December 26, 1997

Toluene (108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (71-43-2) Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	X	1= Slight 0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.