

# Aluminumman



## Aluminum-Reinforced Epoxy Repair Putty



**ALUMINUMMAN** is a hand-mixable, fast-setting, aluminum-reinforced, non-rusting epoxy putty that quickly repairs or rebuilds anything made of aluminum. After mixing, it forms a polymer compound that can be molded into shapes or used to build up, repair and patch items made of aluminum. **ALUMINUMMAN** is a industrial-strength product that cures tough and hard and bonds tenaciously to metals. Each handy stick contains pre-measured portions of activator and base throughout — no measuring or mixing tools are necessary. The consistency (like modeling clay) eliminates drips and runs, molds easily, and facilitates adhesion to the substrate. After 60 minutes the application can be drilled, tapped, machined, ground, filed and painted. It cures to a light-gray metallic color. Suitable for interior or exterior use, it is resistant to water, chemicals, and temperature extremes. It contains no solvents or VOCs. **ALUMINUMMAN** is non-flammable and releases no noxious fumes. It won't shrink or pull away. The unused portion stays fresh for future use when saved in its original package. May cause mild skin irritation, use Omega's **SHIELD** skin protector to reduce potential for irritation while maintaining dexterity. For other surface specific repairs, also try Omega's **COPPERMAN**, **WOODMAN**, **CONCRETEMAN**, **AQUAMAN**, **PLASTIKMAN** and **STEELMAN** repair putty.

**DIRECTIONS:** Before applying, roughen and clean the area to be repaired. Wear impervious gloves when mixing or handling uncured **ALUMINUMMAN**. Then follow these easy steps: 1) **CUT** or twist o required amount. 2) **MIX** by kneading with gloved fingers to a uniform color. If mixing is difficult, warm **ALUMINUMMAN** to room temperature or slightly above. 3) **APPLY** to surface to be repaired within 2 minutes of mixing. Force into any cracks or holes, and extend the patch at least one half inch beyond the area being repaired. When applying to a damp, wet or slowly leaking area, work the mixed epoxy putty forcefully into the surface and apply pressure until adhesion begins to take effect. **For best results:** Use damp fingers for easier mixing, application and a smooth appearance of the cured compound. Remove excess material before hardening begins. **CURING:** **ALUMINUMMAN** has a 5 to 7 minutes work life. Functional cure occurs in 60 Minutes.

Health	2
Flammability	1
Physical Hazard	0
Protection	-

### Areas of Use:

- \*Hotels
- \*Schools
- \*Cities
- \*Counties
- \*Amusement Parks
- \*Stadiums
- \*Apartments
- \*Retirement Homes
- \*Public Buildings

Appearance & Odor..... Gray (Dark) solid with pungent Sulfurous (strong) odor.  
 Net Contents..... 4 oz

## Omega Industrial Supply, Inc.

Fairfield, CA 94534  
 1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134