

This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification

Identity (As Used On Label and List) A1319 ALWAYS SHINE FOOD SAFE CLEANER	Date Prepared: 09/10/25	Date Revised: 05/19/26
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300	
Address (Number, Street, Suite/Apt#) 1133 WEST 27 TH STREET	Telephone Number for Information: 1-800-571-7347	
(City, State, and Zip Code) CHEYENNE, WY 82001	Signature of Prepare (Optional) REGULATORY DEPT.	

Section 2 ~ Hazard(s) Identification

Classifications	Aerosols Category 3	
Label Elements	N/A	Signal Word: WARNING
Hazard Statement	Pressurized container: may burst if heated.	
Precautionary Statement	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/ 122°F.	
Other Hazards	N/A	
Unknown acute toxicity (GHS US)	N/A	

Section 3 ~ Composition/Information on Ingredients

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Butane	106-97-8	1-5%
Propane	74-98-6	1-5%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation develops: Get medical advice or attention.

INGESTION: Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

SKIN: Wash thoroughly with soap and water for 15 minutes. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: None known.

CHRONIC HEALTH HAZARDS: None known.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

Section 5 ~ Firefighting Measures

EXTINGUISHING MEDIA: Dry chemical, foam or carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid contact with skin and breathing smoke, fumes and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 120 °F may cause bursting.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and unidentified organic compounds may be formed during combustion.

Section 6 ~ Accidental Release Measures

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not reuse, puncture or incinerate container. Wrap container and place in trash collection.

RCRA STATUS: Waste likely considered non-hazardous under RCRA, however, product should be fully characterized prior to disposal (40 CFR 261).

Section 7 ~ Handling and Storage

HANDLING AND STORAGE: Wear proper personal protective equipment when using this product. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Do not pierce or burn, even after use. Do not use or store with strong oxidizers.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong inorganic and organic bases. Strong oxidizing agents.

Section 8 ~ Exposure Controls/Personal Protection

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Butane	Not Established	1000 ppm
Propane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: General ventilation and local exhaust should be adequate.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection if used in confined, poorly ventilated areas.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles.

ADDITIONAL MEASURES: Wash hands and clothing in contact with product after use.

Section 9 ~ Physical and Chemical Properties

APPEARANCE: White Foam	ODOR: Bland.
ODOR THRESHOLD: N/D	pH: 9.75 – 10.8
MELTING POINT/FREEZING POINT: 32 °F (0 °C)	INITIAL BOILING POINT AND BOILING RANGE: N/D
FLASH POINT: N/D	EVAPORATION RATE: Slow
FLAMMABILITY (solid/gas): Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200)	UPPER FLAMMABILITY LIMIT: N/D
LOWER FLAMMABILITY LIMIT: N/D	EXPLOSIVE LIMIT UPPER (%): N/D
EXPLOSIVE LIMIT LOWER (%): N/D	VAPOR DENSITY (AIR=1): > 1 @ 77 °F (25 °C)
VAPOR PRESSURE (mm Hg): 17.5 @ 77 °F (25 °C)	SOLUBILITY (IES): 100% water.
RELATIVE DENSITY (H₂O=1): 1.00 – 1.03 @ 77° F (25° C)	AUTOIGNITION TEMPERATURE: N/D
PARTITION COEFFICIENT: n-OCTANOL/WATER (KOW): N/D	VISCOSITY: N/D
DECOMPOSITION TEMPERATURE: N/D	

Section 10 ~ Stability and Reactivity

REACTIVITY: None known.

CHEMICAL STABILITY: Stable under recommended storage conditions.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Extremes of hot and cold. Avoid incompatibles. Do not mix with strong acids.

INCOMPATIBLE MATERIALS: Strong inorganic and organic bases. Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Stable under recommended storage conditions.

Section 11 ~ Toxicological Information

TOXICOLOGICAL INFORMATION: **Propane** (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L. **Butane** (106-97-8): LC₅₀ (Inhalation, Rat, 4h) 30957 mg/m³.

ROUTES OF ENTRY: Eyes, Inhalation, Skin

EYES: May cause irritation, redness.

INGESTION: Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation.

INHALATION: Acute exposure may cause nausea, vomiting, coughing and pulmonary irritation.

SKIN: May cause mild irritation with prolonged or repeated contact.

MEDICAL CONDITION AGGRAVATED: May aggravate. Pre-existing disorders of the skin, respiratory system, and eyes will be aggravated by over exposure.

ACUTE HEALTH HAZARDS: None known.

CHRONIC HEALTH HAZARDS: None known.

CARCINOGENICITY: OSHA: No ACGIH: No N TP: No IARC: No OTHER: N/A

Section 12 ~ Ecological Information

ECOTOXICITY: Not established.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are expected to biodegrade over time.

BIOACCUMULATIVE POTENTIAL: Component or components in this product are not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None known

Section 13 ~ Disposal Considerations

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not reuse, puncture or incinerate container. Wrap container and place in trash collection.

RCRA STATUS: Waste likely considered non-hazardous under RCRA, however, product should be fully characterized prior to disposal (40 CFR 261).

Section 14 ~ Transportation Information

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, non-flammable.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:
VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols.
HAZARD CLASS/DIVISION: 2.2
UN/NA NUMBER: UN1950
PACKING GROUP: N/A
ENVIRONMENTAL HAZARDS WATER: N/A

Section 15 ~ Regulatory Information

TSCA STATUS: All Chemicals are listed or exempt.
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Potassium hydroxide (1310-58-3) Reportable Quantity = 1,000 pounds.
SARA 311/312 HAZARD CATEGORIES: Health Hazards.
SARA 313 REPORTABLE INGREDIENTS: This product does not contain any chemical components with known CAS numbers that exceed the threshold (*de minimis*) reporting levels established by SARA Title III, Section 313.
CLEAN WATER ACT: None.

STATE REGULATIONS: California Proposition 65: This product contains no known chemicals regulated by California Proposition 65.
INTERNATIONAL REGULATIONS: Listed or exempt from listing/notification on the following chemical inventories: Domestic Substances List (DSL, Canada).
VOLATILE ORGANIC COMPOUNDS (VOC): 6.9%

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	1	1	3= Serious
REACTIVITY	1	1	2= Moderate
OTHER	None		1= Slight
PERSONAL PROTECTION		A	0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and -may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet