

C Patch

Concrete Filler and Sealer



C Patch is a durable sealant specifically formulated to repair cracks and holes in concrete, mortar and masonry. **C Patch** contains silicone additives for improved adhesion and water resistance. **C Patch** forms a durable, flexible and water-tight seal. **C Patch** resists gas, oil, grease and salt. Interior/exterior use. Paintable. **ADHERES TO:** Concrete, mortar, cinder block, stucco, brick, wood, and stone.

FOR BEST RESULTS: Clean area with Omega's **Mega Power** degreaser to remove any grease or oily residue for best adhesion. Do not apply when temperatures are below 40°F, or when rain or freezing temperatures are eminent. Store away from extreme hot and cold temperatures. Not recommended for under water applications. Joint size should not exceed 1/2" wide by 1/2" deep. Allow to cure 24 hours before direct exposure to water. Serviceable for pedestrian and vehicular traffic after 24 hours (minimum). **C Patch** fully cures in 7-14 days, depending on temperature, humidity and depth of fill.

DIRECTIONS: Remove loose dirt and debris. Apply **C Patch** to a clean, dry surface. Cut nozzle at a 45° angle to desired bead size. Load cartridge in caulking gun. Fill crack or gap with **C Patch**. Smooth bead if necessary. Clean up excess uncured **C Patch** with damp sponge or cloth. Paintable after 2 hours (longer in cool or humid conditions) with latex or oil-based paints. **COVERAGE:** 56 linear feet at 3/16" diameter bead.

WARNING! Phthalate Esters, Petroleum Disillates and Ethylene Glycol.

Health	1
Flammability	1
Physical Hazard	0
Protection	X

Areas of Use:

- *Apartment Complexes
- *Utility Companies
- *Cities and Counties
- *Amusement parks
- *Industrial Facilities
- *Plumbing Departments
- *Grounds Maintenance
- *Warehouses

Appearance and odor.....	Gray paste, slight odor.
Specific Gravity.....	Concentrate - 1.5196
VOC%08%

Omega Industrial Supply, Inc.

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134