

This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

### Section 1 ~ Identification

<b>Identity (As Used On Label and List)</b> <b>A1075 Carb Clean</b>	<b>Date Prepared:</b> 11-26-2014
<b>Company Information:</b> OMEGA INDUSTRIAL SUPPLY, INC	<b>Emergency Telephone Number:</b> 1-800-424-9300
<b>Address (Number, Street, Suite/Apt#)</b> 101 Grobric Ct #1	<b>Telephone Number for Information:</b> 1-800-571-7347
<b>(City, State, and Zip Code)</b> Fairfield, CA 94534	<b>Signature of Prepare (Optional)</b> REGULATORY DEPT.

### Section 2 ~ Hazard(s) Identification

<b>Classifications</b>	Flammable Aerosol: Skin Irritant: Eye Irritant: Specific Target Organ Toxicity (Repeated Exposure): Aspiration Hazard:	Category 1 Dissolved Gas Category 2 Category 2A Category 1 Category 1
<b>Hazard Statement</b>	Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. Causes damage to Eyes and Central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. This product contains the following percentage of chemicals of unknown toxicity: 0%	
<b>Precautionary Statements</b>	Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. <b>If on skin:</b> Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. <b>If in eyes:</b> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. <b>If swallowed:</b> Immediately call a poison center or doctor. Do NOT induce vomiting. Do not breathe fumes, vapors, and spray. Do not eat, drink, or smoke when using this product. Get medical advice or attention if you feel unwell. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.	

Symbol



Hazards Not Otherwise Classified

N/A

### Section 3 ~ Composition/Information on Ingredients

Hazardous Ingredient	CAS No.	%(Wt.)
Acetone	67-64-1	60 – 100 %
Carbon Dioxide	124-38-9	5 – 10 %
Isoparaffinic Hydrocarbon	64742-47-8	10 – 30 %
Methyl Alcohol	67-56-1	5 – 10 %
Xylene	1330-20-7	1 – 5 %

### Section 4 ~ First Aid Measures

**Eyes:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.  
**Ingestion:** If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting.  
**Inhalation:** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.  
**Skin:** If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.  
**Acute Health Hazards**  
**Eyes:** redness, tearing, blurred vision  
**Skin:** defatting and dermatitis  
**Inhalation:** Irritation  
**Oral:** abdominal irritation, nausea, vomiting, diarrhea, aspiration risk  
**Chronic Health Hazards:** Repeated or prolonged exposure may be toxic to kidneys, liver, Central nervous system (CNS).  
**Note To Physician:** There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

### Section 5 ~ Fire Fighting Measures

**Extinguishing Media:** Dry chemical, carbon dioxide, and alcohol foam.  
**Unsuitable Extinguishing Media:** Water spray/stream.  
**Special Fire Fighting Procedures:** Wear SCBA in fire situations.  
**Unusual Fire And Explosion Hazards:** Contents under pressure. Exposure to temperatures above 120°F may cause bursting.  
**Hazardous Combustion Products:** Oxides of carbon

### Section 6 ~ Accidental Release Measures

**Personal Protective Equipment:** Refer to section VIII for proper Personal Protective Equipment.  
**Spill:** Remove sources of ignition such as pilot lights. Material is heavier than air and can settle in low lying areas in flammable concentrations. Use absorbent on spill sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.  
**Waste Disposal:** Dispose of in accordance with federal, state, and local regulations.  
**RCRA Status:** Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### Section 7 ~ Handling and Storage

**Handling And Storage:** Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.  
**Other Precautions:** None  
**Incompatibility:** Strong oxidizing agents. Most plastics.

### Section 8 ~ Exposure Controls/Personal Protection

Hazardous Ingredients	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	750 ppm
Carbon Dioxide	5000 ppm	5000 ppm
Isoparaffinic Hydrocarbon	400 ppm	400 ppm
Methyl Alcohol	200 ppm	250 ppm
Xylene	100 ppm	100 ppm

**Engineering Controls / Ventilation:** Use only outdoors or in a well-ventilated area.  
**Respiratory Protection:** If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.  
**Personal Protective Equipment:** Chemical resistant gloves recommended.  
**Additional Measures:** Follow normal hygiene practices

**Section 9 ~ Physical Chemical Properties**

<b>Appearance:</b> Clear Spray <b>Odor:</b> Acetone odor <b>Odor Threshold:</b> N/D <b>Boiling Point:</b> N/D <b>Freezing Point:</b> N/D <b>Flammability:</b> Extremely Flammable Aerosol <b>Flash Point:</b> N/D <b>Auto-Ignition Temperature:</b> N/D <b>Lower Flammability Limit:</b> N/A <b>Upper Flammability Limit:</b> N/A <b>Vapor Pressure (mm Hg):</b> Not Established <b>Vapor Density (AIR=1):</b> > 1 @ 77°F (25°C)	<b>Evaporation Rate:</b> 3.5 <b>Specific Gravity (H2O=1):</b> 0.81 @ 77°F (25°C) <b>pH:</b> N/A <b>Solids (%):</b> N/D <b>Solubility In Water:</b> 45% <b>Partition Coefficient: n-OCTANOL/Water (KOW):</b> N/D <b>Volatility Including Water (%):</b> 100 % <b>Volatile Organic Compounds (VOC):</b> 10% <b>Dielectric Strength (Volts):</b> N/D <b>Decomposition Temperature:</b> N/D <b>Viscosity:</b> N/D
---	---

**Section 10 ~ Stability and Reactivity**

**Reactivity:** If exposed to strong oxidizers, presents explosion hazard.  
**Chemical Stability:** Stable  
**Conditions To Avoid:** Temperatures greater than 122°F may cause bursting.  
**Incompatibility:** Strong oxidizing agents. Most plastics.  
**Hazardous Decomposition Or By-Product:** Oxides of carbon  
**Possible Hazardous Reactions:** None Known

**Section 11 ~ Toxicological Information**

**Toxicological Information:** Not Established  
**Routes Of Entry:** Eyes, Ingestion, Inhalation, Skin  
**Eyes:** Causes irritation.  
**Ingestion:** Causes gastrointestinal irritation, nausea. Contains Methanol which can cause blindness and or death. Warning, contains methanol. Cannot be made non-poisonous.  
**Inhalation:** May cause dizziness. Excessive exposure can cause blindness, unconsciousness and or death.  
**Skin:** May cause mild irritation, localized defatting, dryness.  
**Medical Condition Aggravated:** None known

**Acute Health Hazards**

**Eyes:** redness, tearing, blurred vision  
**Skin:** defatting and dermatitis  
**Inhalation:** Irritation  
**Oral:** abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

**Chronic Health Hazards:** Repeated or prolonged exposure may be toxic to kidneys, liver, Central nervous system (CNS).

**Carcinogenicity:** OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

**Section 12 ~ Ecological Information**

**Ecological Information:** Not Established  
**Biodegradability:** Component or components of this product are not biodegradable.  
**Bioaccumulation:** This product is not expected to bioaccumulate.  
**Soil Mobility:** This product is mobile in soil.  
**Other Ecological Hazards:** This material is toxic to aquatic life.

**Section 13 ~ Disposal Considerations**

**Waste Disposal:** Dispose of in accordance with federal, state, and local regulations.  
**RCRA Status:** Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

**Section 14 ~ Transport Information**

<b>Proper Shipping Name:</b> Aerosols, Ltd. Qty. <b>Hazard Class/Division:</b> 2.1 <b>UN/NA Number:</b> UN 1950 <b>Packaging Group:</b> None	<b>Air Shipment</b> <b>Proper Shipping Name:</b> Aerosols, Ltd. Qty. <b>Hazard Class/Division:</b> 2.1 <b>UN/NA Number:</b> UN 1950 <b>Packaging Group:</b> None	<b>Shipping By Water: Vessel (IMO/IMDG)</b> <b>Proper Shipping Name:</b> Aerosols, Ltd. Qty. <b>Hazard Class/Division:</b> 2.1 <b>UN/NA Number:</b> UN 1950 <b>Packaging Group:</b> None <b>Environmental Hazards Water:</b> N/A
---	--	---

**Section 15 ~ Regulatory Information**

**TSCA Status:** All Chemicals are listed or exempt.  
**CERCLA (Comprehensive Response Compensation, And Liability Act):** None  
**SARA 311/312 Hazard Categories:** Flammable  
**SARA 313 Reportable Ingredients:** None  
**Clean Water Act:** None  
**State Regulations:** California Proposition 65: None  
**International Regulations:** Acetone (67-64-1) Australia, China, Europe (EINECS), Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSC (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.

**Section 16 ~ Other Information**

N/A = Not Applicable; N/D = Not Determined

	NFPA	HMIS	Key
HEALTH	2	2	4= Severe
FLAMMABILITY	3	3	3= Serious
REACTIVITY	1	1	2= Moderate
OTHER/PROTECTION	-	B	1= Slight 0= Minimal

Disclaimer: Omega Industrial Supply, Inc. To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.