




Section 1 ~ Identification

Identity (As Used On Label and List) A1126BL COAT IT BLUE	Date Prepared: 06-21-2016
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards	Flammable aerosols	Category 1
Health Hazards	Serious eye damage/eye irritation Carcinogenicity Specific target organ toxicity, single exposure	Category 2A Category 2 Category 3 narcotic effects
OSHA Defined Hazards	Not classified.	
Label Elements	  	Signal Word: Danger.
Hazard Statement	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.	
Precautionary Statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not Otherwise Classified (HNOC)	None known	Supplemental Information None.

Section 3 ~ Composition/Information on Ingredients

Mixtures	Chemical Name	Common Name & Synonyms	CAS No.	% (Wt.)
	Acetone		67-64-1	10 – 20
	Propane		74-98-6	10 – 20
	Barium Sulfate, Natural		7727-43-7	2.5 – 10
	Butane		106-97-8	2.5 – 10
	Ethylene Glycol Propyl Ether		2807-30-9	2.5 – 10
	Isobutyl Acetate		110-19-0	2.5 – 10
	Methyl Isobutyl Ketone		108-10-1	2.5 – 10
	Methyl Propyl Ketone		107-87-9	2.5 – 10
	Titanium Dioxide		13463-67-7	2.5 – 10
	Xylene		1330-20-7	2.5 – 10
	Solvent Naphtha (Petroleum), Light Aromatic		64742-95-6	0.1 – 1
	Other components below reportable levels			20 – 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most Important Symptoms/Effects, Acute and Delayed: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of Immediate Medical Attention and Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General Information: IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising from the Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific Methods: Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and Materials for Containment and Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for Safe Storage, Including Any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (67-64-1)	PEL	2400 mg/m ³	
Barium Sulfate, Natural (7727-43-7)	PEL	1000 ppm	Respirable fraction
Isobutyl Acetate (110-19-0)	PEL	5 mg/m ³	Total dust.
Methyl Isobutyl Ketone (108-10-1)	PEL	15 mg/m ³	
Methyl Propyl Ketone (107-87-9)	PEL	700 mg/m ³	
Propane (74-98-6)	PEL	150 ppm	
Titanium Dioxide (13463-67-7)	PEL	410 mg/m ³	
Xylene (1330-20-7)	PEL	100 ppm	
		700 mg/m ³	
		200 ppm	
		1800 mg/m ³	
		1000 ppm	Total Dust
		15 mg/m ³	
		435 mg/m ³	
		100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Barium Sulfate, Natural (7727-43-7)	TWA	5 mg/m ³	Inhalable fraction
Butane (106-97-8)	STEL	1000 ppm	
Isobutyl Acetate (110-19-0)	TWA	150 ppm	
Methyl Isobutyl Ketone (108-10-1)	STEL	75 ppm	
	TWA	20 ppm	
Methyl Propyl Ketone (107-87-9)	STEL	150 ppm	
Titanium Dioxide (13463-67-7)	TWA	10 mg/m ³	
Xylene (1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (67-64-1)	TWA	590 mg/m ³	
		250 ppm	
Barium Sulfate, Natural (7727-43-7)	TWA	5 mg/m ³	Respirable
		10 mg/m ³	Total
Butane (106-97-8)	TWA	1900 mg/m ³	
		800 ppm	
Isobutyl Acetate (110-19-0)	TWA	700 mg/m ³	
		150 ppm	
Methyl Isobutyl Ketone (108-10-1)	STEL	300 mg/m ³	
		75 ppm	
	TWA	205 mg/m ³	
		50 ppm	
Methyl Propyl Ketone (107-87-9)	TWA	530 mg/m ³	
		150 ppm	
Propane (74-98-6)	TWA	1800 mg/m ³	
		1000 ppm	

Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (67-64-1)	25 mg/l	Acetone	Urine	*
Methyl Isobutyl Ketone (108-10-1)	1 mg/l	Methyl Isobutyl Ketone	Urine	*
Xylene (1330-20-7)	1.5 g/g	Methylhippuric Acids	Creatinine in Urine	*

* - For sampling details, please see the source document.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, Such as Personal Protective Equipment

Eye/Face Protection: Chemical respirator with organic vapor cartridge and full facepiece.

Skin Protection

Hand Protection: Wear appropriate chemical resistant gloves.

Other: Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory Protection: Chemical respirator with organic vapor cartridge and full facepiece.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical and Chemical Properties

Appearance

Physical State: Liquid.

Form: Aerosol.

Color: Not available.

Odor: Not available.

Odor Threshold: Not available.

pH: Not available.

Upper/Lower Flammability or Explosive Limits

Flammability Limit – Lower (%): Not available.

Flammability Limit – Upper (%): Not available.

Explosive Limit - Lower (%): Not available.

Explosive Limit - Upper (%): Not available.

Vapor Pressure: 4065.24 psig @70F estimated

Vapor Density: Not available.

Auto-Ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: Not available.

Other Information

Density: 1.04 g/cm³ estimated

Flammability Class: Flammable IA estimated

Heat of Combustion: 26.31 kJ/g estimated

Melting Point/Freezing Point: Not available.	Relative Density: Not available.	Heat of Combustion (NFPA 30B): 27.07 kJ/g estimated
Initial Boiling Point and Boiling Range: 92.39°F (33.55°C) estimated	Solubility (ies)	Percent Volatile: 35.92 % estimated
Flash Point: -2.2°F (-19.0°C) SUPPLIER estimated	Solubility (water): Not available.	Specific Gravity: 1.037 estimated
Evaporation Rate: Not available.	Partition coefficient (n-octanol/water): Not available.	VOC (Weight %): 46.3 % SUPPLIER estimated
Flammability (solid, gas): Not available.		

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens. Phosphorus. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.:

Section 11 ~ Toxicological Information

Information on Likely Routes of Exposure

Inhalation: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Causes serious eye irritation.

Ingestion: Expected to be a low ingestion hazard.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on Toxicological Effects

Acute Toxicity: Narcotic effects.

<i>Components</i>	<i>Species</i>	<i>Test Results</i>
Acetone (67-64-1)		
Acute		
Dermal LD50	Guinea pig	>7426 mg/kg, 24 Hours
	Rabbit	>9.4 ml/kg, 24 Hours
		>7426 mg/kg, 24 Hours
		>9.4 ml/kg, 24 Hours
Inhalation LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral LD50	Rat	5800 mg/kg
		2.2 ml/kg
Barium Sulfate, Natural (7727-43-7)		
Acute		
Oral LD100	Rat	564 g/kg
LD50	Rat	307 g/kg
Butane (106-97-8)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
		52%, 120 Minutes
	Rat	1355 mg/l
Ethylene Glycol Propyl Ether (2807-30-9)		
Acute		
Dermal LD50	Guinea pig	5.6 g/kg, 4 Days
	Rabbit	> 1 g/kg, 24 Hours
		1337 ml/kg, 14 Days
Inhalation LC50	Rat	>2132 ppm, 6 Hours
		>1800 ppm
Oral LD50	Guinea pig	2.2 g/kg
	Mouse	1774 mg/kg
	Rat	0.5 – 1 g/kg
Isobutyl Acetate (110-19-0)		
Acute		
Dermal LD50	Rabbit	> 17400 mg/kg, 24 Hours
Inhalation LC50	Rat	> 30 mg/l, 6 Hours
		>23.4 mg/l, 4 Hours
Oral LD50	Rat	13413 mg/kg
Methyl Isobutyl Ketone (108-10-1)		
Acute		
Inhalation LC50	Rat	2000 – 4000 ppm, 4 Hours
Oral LD50	Rat	2.08 g/kg
Methyl Propyl Ketone (107-87-9)		
Acute		
Inhalation Vapor LC50	Rat	>25.5 mg/l, 4 Hours
Oral LD50	Mouse	1600 mg/kg
	Rat	1600 – 3200 mg/kg
Propane (74-98-6)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
		52%, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)		
Acute		
Dermal LD50	Rabbit	>1900 mg/kg, 24 Hours
Inhalation LC50	Rat	>5000 mg/m ³ , 4 Hours
		>4980 mg/m ³
		>4980 mg/m ³ , 4 Hours
		4.96 mg/L, 4 Hours
		4820 mg/kg
Oral LD50	Rat	
Titanium Dioxide (13463-67-7)		
Acute		
Inhalation LC50	Rat	>2.28 mg/l, 4 Hours
Oral LD50	Mouse	>5000 mg/kg
	Rat	>2000 mg/kg
Xylene (1330-20-7)		
Acute		
Dermal LD50	Rabbit	>5000 ml/kg, 4 Hours
		12126 mg/kg, 24 Hours

Inhalation LC50	Rat	5922 ppm, 4 Hours
Oral LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg
		10 ml/kl

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Prolonged skin contact may cause temporary irritation.

Serious Eye Damage/Eye Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not available.

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl Isobutyl Ketone (108-10-1) 2B Possibly carcinogenic to humans.

Titanium dioxide (13463-67-7) 2B Possibly carcinogenic to humans.

Xylene (1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

Reproductive Toxicity: Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific Target Organ Toxicity - Single Exposure: May cause drowsiness and dizziness.

Specific Target Organ Toxicity - Repeated Exposure: Not classified.

Aspiration Hazard: Not available.

Chronic Effects: Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12 ~ Ecological Information

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Acetone (67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
Barium Sulfate, Natural (7727-43-7)		21.6 – 23.9 mg/l, 48 hours
		4740 - 6330 mg/l, 96 hours
Aquatic		
Crustacea	EC50	Tubificid worm (Tubifex tubifex)
Methyl Isobutyl Ketone (108-10-1)		28.61 – 38.03 mg/l, 48 hours
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas)
Methyl Propyl Ketone (107-87-9)		492 – 593 mg/l, 96 hours
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas)
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)		1190 – 1290 mg/l, 96 hours
Aquatic		
Crustacea	EC50	Daphnia
Titanium Dioxide (13463-67-7)		6.14 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Mummichog (Fundulus heteroclitus)
Xylene (1330-20-7)		> 1000 mg/l, 48 hours
		> 1000 mg/l, 96 hours
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus)
		7.711 – 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential: No data available.

Partition coefficient n-octanol / water (log Kow): Acetone -0.24 Butane 2.89 Isobutyl Acetate 1.78 Methyl Isobutyl Ketone 1.31
Methyl Propyl Ketone 0.91 Propane 2.36 Xylene 3.12 - 3.2

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Section 14 ~ Transportation Information

<p>DOT UN Number: UN1950 UN Proper Shipping Name: Aerosols, flammable Transport Hazard Class(es) Class: 2.1 Subsidiary Risk: - Label(s) 2.1 Packing Group: Not applicable. Special Provisions: N82 Packaging Exceptions: 306 Packaging Non Bulk: None Packaging Bulk: None</p>	<p>IATA UN Number: UN1950 UN Proper Shipping Name: Aerosols, flammable Transport Hazard Class(es) Class: 2.1 Subsidiary Risk - Label(s): 2.1 Packing Group: Not applicable. Environmental Hazards: No. ERG Code: 10L Other Information Passenger and Cargo Aircraft: Allowed with restrictions. Cargo Aircraft Only: Allowed with restrictions. Packaging Exceptions: LTD QTY</p>	<p>IMDG UN Number: UN1950 UN Proper Shipping Name: AEROSOLS Transport Hazard Class(es) Class: 2.1 Subsidiary Risk - Label(s): 2.1 Packing Group: Not applicable. Environmental Hazards Marine Pollutant: No. EmS: F-D, S-U Packaging Exceptions: LTD QTY Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.</p>
---	--	---

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

DOT



IATA;IMDG



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (67-64-1)	Listed.	Isobutyl Acetate (110-19-0)	Listed.	Methyl Isobutyl Ketone (108-10-1)	Listed.
Xylene (1330-20-7)	Listed.				

SARA 304 Emergency Release Notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA): Hazard Categories Immediate Hazard – Yes Delayed Hazard – Yes

Fire Hazard – Yes Pressure Hazard – No Reactivity Hazard – No

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Methyl Isobutyl Ketone	108-10-1	2.5 – 10
Xylene	1330-20-7	2.5 – 10

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Methyl Isobutyl Ketone (108-10-1) Xylene (1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane (106-97-8) Propane (74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (67-64-1) 6532 Methyl Isobutyl Ketone (108-10-1) 6715

Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (67-64-1) 35 % WV Methyl Isobutyl Ketone (108-10-1) 35 % WV

DEA Exempt Chemical Mixtures Code Number

Acetone (67-64-1) 6532 Methyl Isobutyl Ketone (108-10-1) 6715

US State Regulations

US, California Controlled Substances, CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US, California, Candidate Chemicals List, Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (67-64-1)	Butane (106-97-8)
Methyl Isobutyl Ketone (108-10-1)	Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)
Titanium dioxide (13463-67-7)	Xylene (1330-20-7)

US, Massachusetts RTK - Substance List

Acetone (67-64-1)
Barium Sulfate, Natural (7727-43-7)
Butane (106-97-8)
Isobutyl Acetate (110-19-0)
Methyl Isobutyl Ketone (108-10-1)
Methyl Propyl Ketone (107-87-9)
Propane (74-98-6)
Titanium dioxide (13463-67-7)
Xylene (1330-20-7)

US, New Jersey Worker and Community

Right-to-Know Act
Acetone (67-64-1)
Barium Sulfate, Natural (7727-43-7)
Butane (106-97-8)
Isobutyl Acetate (110-19-0)
Methyl Isobutyl Ketone (108-10-1)
Methyl Propyl Ketone (107-87-9)
Propane (74-98-6)
Titanium dioxide (13463-67-7)
Xylene (1330-20-7)

US, Pennsylvania Worker and

Community Right-to-Know Law
Acetone (67-64-1)
Barium Sulfate, Natural (7727-43-7)
Butane (106-97-8)
Isobutyl Acetate (110-19-0)
Methyl Isobutyl Ketone (108-10-1)
Methyl Propyl Ketone (107-87-9)
Propane (74-98-6)
Titanium dioxide (13463-67-7)
Xylene (1330-20-7)

US, Rhode Island RTK

Acetone (67-64-1)
Butane (106-97-8)
Isobutyl Acetate (110-19-0)
Methyl Isobutyl Ketone (108-10-1)
Propane (74-98-6)
Xylene (1330-20-7)

US, California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic Substance: Methyl Isobutyl Ketone (108-10-1) Listed: November 4, 2011

Titanium dioxide (13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental Toxin: Methyl Isobutyl Ketone (108-10-1) Listed: March 28, 2014

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no) *
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	2	2	2= Moderate
OTHER/PROTECTION		X	1= Slight 0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.