Ex-Pand



Expanding Insulated Foam



Health	3*
Flammability	4
Physical Hazard	2
Protection	X

EX-PAND is a unique one part urethane foam which expands as it dries and solidifies. Fills cracks and holes that caulk can't! Sprays as a liquid then expands and cures to a durable semi-rigid closed cell foam insulation. Each can dispenses over 250 linear feet of product when sprayed in a 3/8 inch cured bead. Forms a water resistant, weather resistant and airtight bond on masonry, wood, metal, glass, tile and most plastics. EX-PAND dries tack free in 15-30 minutes. Fills cracks, and plugs holes eliminating energy escape, dampens sound, and inhibits the entrance of insects or rodents. Makes a great insulating sealant around doors, windows, skylights, and A/C ventilation and heating ducts. Deadens sound when applied to sheet metal and conforms to any shape as it expands. 1" thickness yields R-5 insulating factor. Contains flame retardant. For best results use remainder of can within 30 days of first use.

Directions: Clean grease and dirt from area with a degreasing cleaner such as Omega's **BIO POWER** or **MEGA POWER**. Shake well. Invert can and press trigger slowly. Do not fill cavity completely as product will expand 200-300%. Clean up unwanted uncured foam immediately with paint thinner or acetone. Cured foam can be cut or sanded as needed.

Areas of Use:

*Plumbing
*HVAC Trades

*Hotels
*Hospitals

*Auto/Truck Doors

*Factories

*refrigeration Units

Appearance and odor...... Aerosol gas, Odor not available. % Volatile (by Volume)...... Not Available

Net Wt. 12 oz.

Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134