

Section 1 ~ Identification

Identity (As Used On Label and List) A1263 G.T.S.	Date Prepared: 10-27-2016
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Classifications

Specific Target Organ Toxicity -Single Exposure (Respiratory Tract Irritation) - Category 3
Skin Irritation - Category 2
Eye Irritation - Category 2A
Aerosols Category 1
Acute toxicity Oral - Category 5

Pictograms



Signal Word: Danger.

Hazard Statements – Physical

H222 - Extremely flammable aerosol

H229 - Pressurized container: May burst if heated

Hazard Statements – Health

H335 - May cause respiratory irritation

H319 - Causes serious eye irritation

H315 - Causes skin irritation

H303 - May be harmful if swallowed

Precautionary Statement – General

P101 - If medical advice is needed, have product container or label at hand.

P103 - Read label before use.

Precautionary Statement – Prevention

P102 - Keep out of reach of children.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

P233 - Keep container tightly closed.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

Precautionary Statement – Response

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P321 - For specific treatment see section 4.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

Precautionary Statement – Storage

P403 + P405 - Store in a well-ventilated place. Store locked up.

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statement – Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Section 3 ~ Composition/Information on Ingredients

Chemical Name	CAS No.	%(Wt.)
Ethyl Alcohol	64-17-5	41 – 68%
Acetone	67-64-1	18 – 30%
Isopropyl Alcohol	67-63-0	5 – 11%
Petroleum gases, liquefied, sweetened	68476-86-8	3 – 6%
CO2	124-38-9	0.1 – 2%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

Section 4 ~ First Aid Measures

Inhalation: Remove source of exposure or move person to fresh air and keep comfortable for breathing. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor. Eliminate all ignition sources if safe to do so.

Skin Contact: Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use. IF exposed or concerned: Get medical advice/attention.

Eye Contact: Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Do not give anything.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Dry chemical, foam, carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only. Do not direct a solid stream of water or foam into hot, burning pools this may result in frothing and increase fire intensity.

Unsuitable Extinguishing Media: No data available.

Specific Hazards in Case of Fire: Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water. DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers. Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

Fire-Fighting Procedures: Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions: Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6 ~ Accidental Release Measures

Emergency Procedure: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment: Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions: Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions: Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning Up: Cover spills with inert absorbent and place in closed chemical waste containers.

Section 7 ~ Handling and Storage

General: Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements: Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements: Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them. Store at temperatures below 120°F.

Section 8 ~ Exposure Controls/Personal Protection

Eye Protection: Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection: Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m ³)	OSHA STEL (ppm)	OSHA STEL (mg/m ³)	OSHA Tables Z1, 2, 3	OSHA Carcinogen	OSHA Skin Designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m ³)	NIOSH STEL (ppm)	NIOSH STEL (mg/m ³)	NIOSH Carcinogen
Acetone	1000	2400			1			250	590			
CO ₂	5000	9000			1			5000	9000	30000	54000	
Ethyl Alcohol	1000	1900			1			1000	1900			
Isopropyl Alcohol	400	980			1			400	980	500	1225	
Petroleum gases, liquefied, sweetened	500	2000			1							

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m ³)	ACGIH STEL (ppm)	ACGIH STEL (mg/m ³)
Acetone	250		500	
CO ₂	5000	9000	30000	54000
Ethyl Alcohol			1000	
Isopropyl Alcohol	200		400	
Petroleum gases, liquefied, sweetened				

Section 9 ~ Physical and Chemical Properties

Physical and Chemical Properties	Density VOC: 4.70890 lb/gal	VOC Actual: 4.70890 lb/gal
Density: 6.50126 lb/gal	Density VOC: 4.70890 lb/gal	VOC Actual: 4.70890 lb/gal
	VOC Actual: 564.26737 g/l	% VOC: 72.43055%
Appearance: Clear Liquid	Water Solubility: N.A.	Upper Explosion Level: N.A.
Odor Threshold: N.A.	Flash Point Symbol: N.A.	Vapor Pressure: N.A.
Odor Description: Alcohol	Flash Point: N.A.	Vapor Density: N.A.
pH: N.A.	Viscosity: N.A.	Freezing Point: N.A.
Flammability: N/A	Lower Explosion Level: N.A.	Melting Point: N.A.
		Low Boiling Point: N.A.
		High Boiling Point: N.A.
		Auto Ignition Temp: N.A.
		Evaporation Rate: N.A.
		VOC Composite Partial Pressure: N.A.

Section 10 ~ Stability and Reactivity

Stability: Material is stable at standard temperature and pressure.

Hazardous Reactions/Polymerization: Will not occur.

Conditions to Avoid: Keep away from direct sunlight and other sources of ignition. Dropping containers may cause bursting.

Incompatible Materials: Avoid strong oxidizers, reducers, acids, and alkalis.

Hazardous Decomposition Products: No data available.

Section 11 ~ Toxicological Information

Skin Corrosion/Irritation: Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin. Causes skin irritation

Serious Eye Damage/Irritation: Eye contact may lead to permanent damage if not treated promptly. Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly. Causes serious eye irritation

Respiratory/Skin Sensitization: No Data Available

Germ Cell Mutagenicity: No Data Available

Carcinogenicity: No Data Available

Reproductive Toxicity: No Data Available

Specific Target Organ Toxicity - Single Exposure: May cause respiratory irritation

Specific Target Organ Toxicity - Repeated Exposure: Prolonged exposure may cause damage to her central nervous system, lungs, skin and eyes.

Aspiration Hazard: No Data Available

Acute Toxicity: If inhaled, may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heart beats.

67-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m³ (4-hour exposure) (29)

LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m³ (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32,unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

64-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m³ (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

67-63-0 ISOPROPYL ALCOHOL
LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)
LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)
LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)
LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

Potential Health Effects - Miscellaneous

64-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be harmful.

67-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

Section 12 ~ Ecological Information

Toxicity: No Data Available

Mobility in Soil: No data available.

Persistence and Degradability: No data available.

Other Adverse Effects: No data available.

Bio-accumulative Potential: No data available.

Bio-accumulative Potential

67-64-1 ACETONE

Does not bioaccumulate

Persistence and Degradability

67-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Section 13 ~ Disposal Considerations

Waste Disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 ~ Transportation Information

U.S. DOT Information: Ground Transportation: (Continental United States, Canada & Mexico): Limited Quantity

IMDG Information:

Shipping Name: Aerosols, flammable

UN/NA #: 1950

Hazard Class: 2.1

Required Placard: Limited Quantity

Marine Pollutant: No data available

IATA Information: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

Section 15 ~ Regulatory Information

CAS	Chemical Name	% by Wt.	Regulation List
64-17-5	Ethyl Alcohol	41 – 68%	Canada_NPRI, DSL, SARA312, VOC, TSCA
67-64-1	Acetone	18 – 30%	DSL, CERCLA, SARA312, VOC_exempt, TSCA, RCRA
67-63-0	Isopropyl Alcohol	5 – 11%	Canada_NPRI, DSL, SARA312, VOC, TSCA
68476-86-8	Petroleum gases, liquefied, sweetened	3 – 6%	DSL, SARA312, VOC, TSCA
124-38-9	CO2	0.1 – 2%	DSL, SARA312, TSCA

Section 16 ~ Other Information

Glossary: ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG/Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; N.A. - Not Available; NFPA-National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

	NFPA	HMIS	Key
HEALTH	2	2	4= Severe
FLAMMABILITY	3	3	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	-	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.