

Section 1 ~ Identification

Identity (As Used On Label and List) A1095 GRAPHITE LUBE	Date Prepared: 05-15-2015
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Classification (GHS-US)	Flam. Aerosol 1 H222 Skin Irrit. 2 H315 Muta. 1B H340 Carc. 1A H350	STOT SE 3 H336 STOT RE 2 H373 Asp. Tox. 1 H304 Full text of H-phrases: See section 16
--------------------------------	--	--

Label Elements

Hazardous Pictograms (GHS-US)



Signal Word (GHS-US): Danger

Hazard Statement (GHS-US)

GHS02 Extreme flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer (Inhalation). May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement (GHS-US)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. – No smoking. Do not breathe fume, gas, mist, spray, vapors. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. **If Swallowed:** Immediately call a doctor, a POISON CENTER. **If on Skin:** Wash with plenty of water. **If Inhaled:** Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention call a doctor/POISON CENTER if you feel unwell. Get medical advice/attention if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container to comply with local/regional/national/international regulations.

Other Hazards

No additional information available

Unknown Acute Toxicity (GHS-US)

Not applicable

Section 3 ~ Composition/Information on Ingredients

Substance: Not applicable

Full text of H-phrases: see section 16

Components (Specific Chemical Identity, Common Name(s))	CAS No.	Classification (GHS US)	%(Wt.)
Toluene	108-88-3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	40 – 70%
Petroleum gases, liquified	68476-86-8	Flam. Gas. 1, H220 Compressed gas. H280 Muta. 1B, H340 Carc. 1A, H350	10 – 30%
Crystalline Silica	14808-60-7	Carc. 1A, H350	0.1 – 5%

Section 4 ~ First Aid Measures

Description of First Aid Measures

First-Aid Measures General: If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

First-Aid Measures After Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or a doctor if you feel unwell.

First-Aid Measures After Skin Contact: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

First-Aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-Aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth with water. Immediately call a poison center or doctor/physician.

Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms/Injuries: May cause cancer. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Central nervous system depression. Prolonged exposure: danger of damage to health through inhalation.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: Direct contact with the eyes is likely irritating.

Symptoms/Injuries After Ingestion: Gastrointestinal complaints. May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Indication of Any Immediate Medical Attention and Special Treatment Needed: Treat symptomatically.

Section 5 ~ Fire Fighting Measures

Extinguishing Media

Suitable Extinguishing Media: Foam. Carbon dioxide. Dry chemical powder.

Special Hazards Arising from the Substance or Mixture

Fire Hazard: Extremely flammable aerosol.

Explosion Hazard: Pressurized container: may burst if heated. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

Reactivity: Upon combustion: CO and CO2 are formed.

Advice for Firefighters

Firefighting Instructions: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Isolate from fire, if possible, without unnecessary risk. Eliminate every possible source of ignition.

For Non-Emergency Personnel

Protective Equipment: Protective goggles. Gloves. Protective clothing.

Emergency Procedures: Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.
Emergency Procedures: Stop leak if safe to do so. Stop release. Ventilate area.
Environmental Precautions: Avoid release to the environment. Prevent entry to sewers and public waters.
Methods and Material for Containment and Cleaning Up
For Containment: Contain released substance, pump into suitable containers.
Methods for Cleaning Up: This material and its container must be disposed of in a safe way, and as per local legislation.
Reference to Other Sections: No additional information available

Section 7 ~ Handling and Storage

Precautions for Safe Handling
Additional Hazards when Processed: Do not puncture, incinerate or crush. Do not use if spray button is missing or defective.
Precautions for Safe Handling: Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Obtain special instructions before use. Do not breathe gas/vapor/aerosol. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Handle uncleaned empty containers as full ones.
Hygiene Measures: Wash thoroughly after handling. Wash contaminated clothing before reuse.
Conditions for Safe Storage, Including any Incompatibilities
Technical Measures: Comply with applicable regulations.
Storage Conditions: Keep cool. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Incompatible Materials: Sources of ignition. Direct sunlight. Heat sources.
Heat-Ignition: KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
Storage Area: Meet the legal requirements. Store in a cool area. Store in a dry area.
Special Rules on Packaging: meet the legal requirements.

Section 8 ~ Exposure Controls/Personal Protection

Control Parameters

Toluene (108-88-3)

ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Visual impair; female repro;

Exposure Controls

Personal Protective Equipment: Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective clothing. Insufficient ventilation: wear respiratory protection.



Section 9 ~ Physical Chemical Properties

Information on Basic Physical and Chemical Properties

Physical State: Liquid
Appearance: Aerosol. Grey.
Odor: Hydrocarbon odor
Odor Threshold: No data available
pH: No data available
Melting Point: No data available
Freezing Point: No data available
Boiling Point: No data available

Flash Point: No data available
Relative Evaporation Rate (butyl acetate=1): No data available
Flammability (solid, gas): No data available
Explosion Limits: No data available
Explosive Properties: No data available
Oxidizing Properties: No data available
Vapor Pressure: ≈ 4.4 atm @ 70°F
Relative Density: No data available
Relative Vapor Density at 20°C: No data available

Solubility: Negligible.
Log Pow: No data available
Log Kow: No data available
Auto-Ignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: No data available
Viscosity, Kinematic: < 20 cSt
Viscosity, Dynamic: No data available
VOC Content: > 90 %

Section 10 ~ Stability and Reactivity

Reactivity: Upon combustion: CO and CO2 are formed.
Chemical Stability: Stable under normal conditions.
Possibility of Hazardous Reactions: Refer to section 10.1 on Reactivity.
Conditions to Avoid: Heat. No flames, No sparks. Eliminate all sources of ignition.
Incompatible Materials: No additional information available
Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 ~ Toxicological Information

Information on Toxicological Effects

Acute Toxicity: Not classified
Skin Corrosion/Irritation: Causes skin irritation.
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: May cause genetic defects.
Carcinogenicity: May cause cancer (Inhalation).
Crystalline Silica (14808-60-7)
IARC group 1 - Carcinogenic to Humans
Toluene (108-88-3)
IARC group 3 - Not Classifiable
Reproductive Toxicity: Not classified
Specific Target Organ Toxicity (single exposure): May cause drowsiness or dizziness.
Specific Target Organ Toxicity (repeated exposure): May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard: May be fatal if swallowed and enters airways.
Symptoms/Injuries After Inhalation: May cause respiratory irritation. Central nervous system depression. Prolonged exposure: danger of damage to health through inhalation.
Symptoms/Injuries After Skin Contact: Causes skin irritation.
Symptoms/Injuries After Eye Contact: Direct contact with the eyes is likely irritating.
Symptoms/Injuries After Ingestion: Gastrointestinal complaints. May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Section 12 ~ Ecological Information

Toxicity: No additional information available
Persistence and Degradability: No additional information available
Bioaccumulative Potential: No additional information available

Section 13 ~ Disposal Considerations

Waste Treatment Methods

Water Disposal instructions: Dispose in a safe manner in accordance with local/national regulations.

Section 14 ~ Transport Information

Department of Transportation (DOT)

Additional Information

Other Information: This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

ADR: No additional information available

Transport by Sea: No additional information available

Air Transport: No additional information available

Section 15 ~ Regulatory Information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory. Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene CAS No 108-88-3 40-70

Toluene (108-88-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

RQ (Reportable quantity, section 304 of EPA's List of Lists) 1000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

Section 16 ~ Other Information

Training Advice: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full Text of H-phrases:

Asp. Tox. 1 Aspiration hazard Category 1

Carc. 1A Carcinogenicity Category 1A

Compressed gas Gases under pressure Compressed gas

Flam. Aerosol 1 Flammable aerosol Category 1

Flam. Gas 1 Flammable gases Category 1

Flam. Liq. 2 Flammable liquids Category 2

Muta. 1B Germ cell mutagenicity Category 1B

Skin Irrit. 2 Skin corrosion/irritation Category 2

STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2

STOT SE 3 Specific target organ toxicity (single exposure) Category 3

H220 Extremely flammable gas

H222 Extremely flammable aerosol

H225 Highly flammable liquid and vapor

H280 Contains gas under pressure; may explode if heated

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H340 May cause genetic defects

H350 May cause cancer

H373 May cause damage to organs through prolonged or repeated exposure

	NFPA	HMIS	Key
HEALTH	3	3	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	-	1= Slight 0= Minimal

Disclaimer: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendors or users assume all risks associated with the use of this material.