

Jelly D Plus

Organic Foaming Engine Degreaser



JELLY D PLUS works quickly to emulsify tar, asphalt, grease and oil. **JELLY D PLUS** is safe and easy to use. Spray on and wash off with water. Dense foam allows product to cling to vertical surface allowing for longer contact time. Cleans engines enabling them to run cooler, look better and last longer. Biodegradable and VOC compliant in all 50 states.

Directions: When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar. **FOR ENGINES:** Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow **JELLY D PLUS** to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying. **OTHER SURFACES:** To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow **JELLY D PLUS** to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

Health	1
Flammability	1
Physical Hazard	0
Protection	B

Areas of Use:

- *Vehicles
- *Machinery
- *Industrial Equipment
- *Mechanical Shops
- *Appliances
- *Ship Yards
- *Amusement Parks



Appearance and odor.....	White foam with Glycol Etherodor.
Specific Gravity.....	0.099
VOC %	6%
Net Wt.	16 oz.

Omega Industrial Supply, Inc.

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134