## Ladder Restorer



Clear Coat



**LADDER RESTORER** restores fiberglass ladders and protects against UV rays. **LADDER RESTORER** is a clear coat that is resistant to the effects of weather and many chemicals, resists abrasions and heat (250°F).

**DIRECTIONS: 1.** Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C.).

- **2.** Shake can at least one minute after rattle is heard and occasionally during use.
- **3.** Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
- **4.** If clogging develops, turn spray head 1/4 turn or remove and clean spray head slot. Do not stick pin or other objects into can opening. With can and spray head pointed away from you, reinsert spray head with a gentle twisting motion.
- **5.** To clear spray head for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Health	1
Flammability	4
Physical Hazard	3
Protection	В

## Areas of Use:

\*Automotive

\*Industrial

\*Parks/Recreations

\*Hotels

\*Marine

\*School Districts

\*Aeronautical

\*Construction

## Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134