

Machine Gray Spray Paint



Multi Surface Paint



MACHINE GRAY SPRAY PAINT is a high quality enamel coating that is designed to adhere well and resist rust on a variety of surfaces. **MACHINE GRAY SPRAY PAINT** has a spray-anywhere valve that allows it to be sprayed in any direction and is heat resistant to 300°F. (149°C)

DIRECTIONS

1. Remove all contaminants that prevent adhesion. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when temperature is between 50°F and 100°F (10°C and 38°C). Do not apply below 40°F (4°C). A primer is not usually needed for most surfaces; however, it is recommended over bare metal, crevices and seams. To achieve the best results use our **PRIMAL PRIMER LIGHT GRAY**.
2. Shake can for one minute after agitator ball is heard and occasionally during use.
3. Hold can 6 to 8" from surface. Apply in multiple thin coats to avoid runs or drips.

Health	1
Flammability	4
Physical Hazard	1
Protection	-

Areas of Use:

- *Hotels
- *Schools
- *Cities
- *Counties
- *Amusement Parks
- *Stadiums
- *Apartments
- *Retirement Homes
- *Public Buildings

Appearance & Odor.....	Machine gray.
Net Contents.....	12 Oz.

Omega Industrial Supply, Inc.

Fairfield, CA 94534
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134