Section 1 ~ Identification			
Identity (As Used On Label and List)	Date Prepared:		
A1055 METAL PROTECT	10-08-2015		
Company Information:	Emergency Telephone Number:		
OMEGA INDUSTRIAL SUPPLY, INC	1-800-424-9300		
Address (Number, Street, Suite/Apt#)	Telephone Number for Information:		
101 Grobric Ct #1	1-800-571-7347		
(City, State, and Zip Code)	Signature of Prepare (Optional)		
Fairfield, CA 94534	REGULATORY DEPT.		

Section 2 ~ Hazard(s) Identification

Physical Hazards Flammable aerosols Category 1

Health Hazards Specific target organ toxicity, repeated exposure Category 1

Aspiration hazard Category 1

OSHA Defined Hazards None known

Label Elements



Signal Word: Danger.

Hazard Statement
Precautionary Statement

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure.

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not Otherwise Classified (HNOC) None known Supplemental Information None

Section 3 ~ Composition/Information on Ingredients

Chemical Name & Synonyms	CAS No.	%(Wt.)
Butane	106-97-8	20 – 40
Mineral Spirits	8052-41-3	20 – 40
Naphtha (petroleum), Light Alkylate	64741-66-8	10 – 20
Propane	74-98-6	10 – 20
Other components below reportable levels		20 – 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye Contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Most Important Symptoms/Effects, Acute and Delayed: Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Prolonged exposure may cause chronic effects.

Indication of Immediate Medical Attention and Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information: If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Foam. Powder. Carbon dioxide (CO2).

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for Safe Storage, Including Any Incompatibilities: Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:				
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)				
Components	Type	Value		
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3		
		500 ppm		
Propane (CAS 74-98-6)	PEL	1800 mg/m3		
		1000 ppm		
US. ACGIH Threshold Limit Values				
	<i>m</i>	** 1		
Components	Type	Value		
Butane (CAS 106-97-8)	STEL	1000 ppm		
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm		
US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Type	Value		
Butane (CAS 106-97-8)	TWA	1900 mg/m3		
		800 ppm		
Mineral Spirits (CAS 8052-41-3)	Ceiling	1800 mg/m3		
• •	TWA	350 mg/m3		
Propane (CAS 74-98-6)	TWA	1800 mg/m3		

Biological Limit Values: No biological exposure limits noted for the ingredient(s).

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

1000 ppm

Individual Protection Measures, Such as Personal Protective Equipment

Eye/Face Protection: If contact is likely, safety glasses with side shields are recommended.

Skin Protection

Hand Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~	· Physical	and	Chemical	Properties
-------------	------------	-----	----------	-------------------

Appearance	Evaporation Rate: Not available.	Solubility(ies)
Physical State: Gas.	Flammability (solid, gas): Not available.	Solubility (water): Not available.
Form: Aerosol.	Upper/Lower Flammability or Explosive Limits	Partition coefficient (n-octanol/water): Not available.
Color: Dark brown.	Flammability Limit – Lower (%): 0.9 % estimated	Auto-Ignition Temperature: Not available.
Odor: solvent	Flammability Limit – Upper (%): Not available.	Decomposition Temperature: Not available.
Odor Threshold: Not available.	Explosive Limit - Lower (%): Not available.	Viscosity: Not available.
pH: Not available.	Explosive Limit - Upper (%): Not available.	Other Information
Melting Point/Freezing Point: Not available.	Vapor Pressure: Not available.	Explosive Properties: Not explosive.
Initial Boiling Point and Boiling Range: Not available.	Vapor Density: Not available.	Oxidizing Properties: Not oxidizing.
Flash Point: -156.0 °F (-104.4 °C) PROPELLANT estimated	Relative Density: Not available.	Specific Gravity: 0.426 estimated

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.

Section 11 ~ Toxicological Information

Information on Likely Routes of Exposure

Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Direct contact with eyes may cause temporary irritation.

Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Aspiration may cause pulmonary edema and pneumonitis. Dizziness.

Information on Toxicological Effects

Acute Toxicity: May be fatal if swallowed and enters airways

<u>Components</u>	<u>Species</u>	<u>Test Results</u>
Butane (CAS 106-97-8)		
Acute		
Inhalatation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Naphtha (petroleum), Light Alkylate (CAS	64741-66-8)	
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
Vapor		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
Oral		> 4.96 mg/l, 4 Hours
LD50	Rat	4820 mg/kg
Propane (CAS 74-98-6)		
Acute		

Acute

Inhalation LC50

Rat

Mouse

1237 mg/l, 120 Minutes 52%, 120 Minutes 1355 mg/l 658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Prolonged skin contact may cause temporary irritation.

Serious Eye Damage/Eye Irritation: Direct contact with eyes may cause temporary irritation.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity: Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects.

Specific Target Organ Toxicity - Single Exposure: Not classified.

Specific Target Organ Toxicity - Repeated Exposure: Causes damage to organs through prolonged or repeated exposure. Central nervous system. Respiratory system. Eyes. Skin.

Kidneys

Aspiration Hazard: May be fatal if swallowed and enters airways.

Chronic Effects: Causes damage to organs through prolonged or repeated exposure.

Section 12 ~ Ecological Information

Ecotoxicity: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential

Partition coefficient n-octanol / water (log Kow)

Butane 2.89

Mineral Spirits 3.16 - 7.15

Propane 2.36

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers

Section 14 ~ Transportation Information

DOT

UN Number: UN1950

UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -Label(s): 2.1

Packing Group: Not applicable.

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Special Provisions: N82 Packaging Exceptions: 306 Packaging Non Bulk: None Packaging Bulk: None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

UN Number: UN1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

Packing Group: Not applicable. Environmental Hazards: No.

ERG Code: 10L

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other Information Passenger and Cargo Aircraft: Allowed with restrictions.

Cargo Aircraft Only: Allowed with restrictions.

Packaging Exceptions: LTD QTY

IMDG

UN Number: UN1950

UN Proper Shipping Name: AEROSOLS

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -Label(s): 2.1

Packing Group: Not applicable.

Marine Pollutant: No.

Environmental Hazards

EmS: F-D, S-U

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions: LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

IATA;IMDG



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No SARA 313 (TRI reporting): Not regulated.

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA): Not regulated.

US State Regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8)

Mineral Spirits (CAS 8052-41-3)

Naphtha (petroleum), Light Alkylate (CAS 64741-66-8)

US. Massachusetts RTK - Substance List US. New Jersey Worker and Community Butane (CAS 106-97-8) Right-to-Know Act Mineral Spirits (CAS 8052-41-3) Butane (CAS 106-97-8) Propane (CAS 74-98-6) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law Butane (CAS 106-97-8) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

US. Rhode Island RTK Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
* A #37 - # 1	-fabrican death and be with the insentence of an insentence of the first and the first and the fabrican decay of the fabrican decay	

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of

the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	3	3*	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	X	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.