




### Section 1 ~ Identification

|  |  |
|--|--|
| <b>Identity (As Used On Label and List)</b><br><b>A1014 O.G.L.</b> | <b>Date Prepared:</b><br>11-16-2016                        |
| <b>Company Information:</b><br>OMEGA INDUSTRIAL SUPPLY, INC        | <b>Emergency Telephone Number:</b><br>1-800-424-9300       |
| <b>Address (Number, Street, Suite/Apt#)</b><br>101 Grobric Ct #1   | <b>Telephone Number for Information:</b><br>1-800-571-7347 |
| <b>(City, State, and Zip Code)</b><br>Fairfield, CA 94534          | <b>Signature of Prepare (Optional)</b><br>REGULATORY DEPT. |

### Section 2 ~ Hazard(s) Identification

|   |  |   |
|---|--|---|
| <b>Classifications</b>                      | Specific Target Organ Toxicity - Repeated Exposure - Category 2<br>Aspiration Hazard - Category 1<br>Skin Irritation - Category 3<br>Eye Irritation - Category 2A<br>Aerosol - Category 1<br>Reproductive Toxicity - Category 2<br>Chronic aquatic toxicity - Category 3   |   |
| <b>Pictograms</b>                           |     | <b>Signal Word:</b> Danger.   |
| <b>Hazard Statements – Physical</b>         | H222, H229 - Extremely flammable aerosol. Pressurized container may burst if heated  |   |
| <b>Hazard Statements – Health</b>           | H373 - May cause damage to organs through prolonged or repeated exposure.<br>H304 - May be fatal if swallowed and enters airways<br>H316 - Causes mild skin irritation<br>H319 - Causes serious eye irritation<br>H361 - Suspected of damaging fertility or the unborn child.  |   |
| <b>Hazard Statements – Environmental</b>    | H412 - Harmful to aquatic life with long lasting effects   |   |
| <b>Precautionary Statement – General</b>    | P101 - If medical advice is needed, have product container or label at hand.<br>P102 - Keep out of reach of children.<br>P103 - Read label before use.   |   |
| <b>Precautionary Statement – Prevention</b> | P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P273 - Avoid release to the environment.<br>P280 - Wear protective gloves/protective clothing/eye protection/face protection.<br>P211 - Do not spray on an open flame or other ignition source.<br>P251 - Do not pierce or burn, even after use.<br>P260 - Do not breathe dust/fume/gas/mist/vapors/spray.<br>P264 - Wash thoroughly after handling.  |   |
| <b>Precautionary Statement – Response</b>   | P202 - Do not handle until all safety precautions have been read and understood.<br>P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.<br>P370 + P378 - In case of fire: Use water fog, dry chemical or carbon dioxide to extinguish.<br>P314 - Get medical advice/attention if you feel unwell.<br>P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.<br>P331 - Do NOT induce vomiting.<br>P332 + P313 - If skin irritation occurs: Get medical advice/attention.<br>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P337 + P313 - If eye irritation persists: Get medical advice/attention.<br>P308 + P313 - IF exposed or concerned: Get medical advice/attention. |   |
| <b>Precautionary Statement – Storage</b>    | P235 - Keep cool.<br>P403 - Store in a well-ventilated place.<br>P405 - Store locked up.   | P410 - Protect from sunlight.<br>P412 - Do not expose to temperatures exceeding 50°C/122°F. |
| <b>Precautionary Statement – Disposal</b>   | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.   |   |

### Section 3 ~ Composition/Information on Ingredients

| Chemical Name  | CAS        | %(Wt.)  |
|--|------------|---------|
| Stoddard Solvent   | 8052-41-3  | 15 – 26 |
| Asphalt, Oxidized  | 64742-93-4 | 10 – 22 |
| Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Paraffinic | 64742-54-7 | 9 – 21  |
| Propane  | 74-98-6    | 7 – 15  |
| Butane   | 106-97-8   | 4 – 8   |
| Hexane   | 110-54-3   | 2 – 5   |
| Isobutane  | 75-28-5    | 2 – 4   |

### Section 4 ~ First Aid Measures

**Inhalation:** Remove source of exposure or move person to fresh air and keep comfortable for breathing. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor. Eliminate all ignition sources if safe to do so.

**Eye Contact:** Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

**Skin Contact:** Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Gently blot or brush away excess product. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Call a POISON CENTER/doctor if you feel unwell. Store contaminated clothing under water and wash before reuse or discard.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position. Never give anything by mouth to an unconscious or convulsing victim. Keep person warm and quiet.

### Section 5 ~ Fire Fighting Measures

**Suitable Extinguishing Media:** Use water, fog, dry chemical, or carbon dioxide. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

**Unsuitable Extinguishing Media:** Water may be ineffective but can be used to cool containers exposed to heat or flame.

**Specific Hazards in Case of Fire:** Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Aerosol cans may rupture when heated. Heated cans may burst. In fire, will decompose to carbon dioxide, carbon monoxide

**Fire-Fighting Procedures:** Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**Special Protective Actions:** Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear. Care should always be exercised in dust/mist areas.

### Section 6 ~ Accidental Release Measures

**Emergency Procedure:** Flammable/combustible material. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stay upwind; keep out of low areas. Immediately turn off or isolate any source of ignition. Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for proper disposal.

**Recommended Equipment:** Wear safety glasses and gloves.

**Personal Precautions:** ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). Use explosion proof equipment. Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

**Environmental Precautions:** Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Section 7 ~ Handling and Storage

**General:** For industrial and institutional use only. For use by trained personnel only. Keep away from children. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored.

**Ventilation Requirements:** Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

**Storage Room Requirements:** Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous. Do not cut, drill, grind, weld, or perform similar operations on or near containers. Do not pressurize containers to empty them. Ground all structures, transfer containers and equipment to conform to the national electrical code. Use procedures that prevent static electrical sparks. Static electricity may accumulate and create a fire hazard. Store at temperatures below 120°F.

### Section 8 ~ Exposure Controls/Personal Protection

**Eye Protection:** Chemical goggles, safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage.

**Skin Protection:** Wear gloves, long sleeved shirt, long pants and other protective clothing as required to minimize skin contact. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Chemical-resistant clothing is recommended to avoid prolonged contact. Avoid unnecessary skin contact.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapors. When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

| Chemical Name  | OSHA TWA (ppm) | OSHA TWA (mg/m3) | OSHA STEL (ppm) | OSHA STEL (mg/m3) | OSHA Tables Z1, 2, 3 | OSHA Carcinogen | OSHA Skin Designation | NIOSH TWA (ppm) | NIOSH TWA (mg/m3) | NIOSH STEL (ppm) | NIOSH STEL (mg/m3) | NIOSH Carcinogen |
|--|----------------|------------------|-----------------|-------------------|----------------------|-----------------|-----------------------|-----------------|-------------------|------------------|--------------------|------------------|
| Butane   |                |                  |                 |                   |                      |                 |                       | 800             | 1900              |                  |                    |                  |
| Hexane   | 500            | 1800             |                 |                   | 1                    |                 |                       | 50              | 180               |                  |                    |                  |
| Isobutane  |                |                  |                 |                   |                      |                 |                       | 800             | 1900              |                  |                    |                  |
| Mineral Oil, Petroleum Distillates, Hydrotreated (Mild) Heavy Paraffinic | 500            | 2000             |                 |                   | 1                    |                 |                       |                 |                   |                  |                    |                  |
| Propane  | 1000           | 1800             |                 |                   | 1                    |                 |                       | 1000            | 1800              |                  |                    |                  |
| Stoddard Solvent   | 500            | 2900             |                 |                   | 1                    |                 |                       |                 | 350               |                  |                    |                  |

| Chemical Name  | ACGIH TWA (ppm)                        | ACGIH TWA (mg/m3) | ACGIH STEL (ppm) | ACGIH STEL (mg/m3) |
|--|--|-------------------|------------------|--------------------|
| Butane   | 1000                                   |                   |                  |                    |
| Hexane   | 50                                     | 176               |                  |                    |
| Isobutane  | 1000                                   |                   |                  |                    |
| Mineral Oil, Petroleum Distillates, Hydrotreated (Mild) Heavy Paraffinic |  |                   |                  |                    |
| Propane  | See Appendix F: Minimal Oxygen Content |                   |                  |                    |
| Stoddard Solvent   | 100                                    | 572               |                  |                    |

### Section 9 ~ Physical and Chemical Properties

#### Physical and Chemical Properties

**Density:** 7.26056 lb/gal

**Density VOC:** 3.59384 lb/gal

**% VOC:** 49.49813%

**Appearance:** N.A.

**Odor Threshold:** N.A.

**Odor Description:** N.A.

**pH:** N.A.

**Water Solubility:** Nil

**Flammability:** Flashpoint below 73 °F

**Flash Point Symbol:** N.A.

**VOC Actual:** 3.59384 lb/gal

**VOC Actual:** 430.65000 g/l

**VOC Regulatory:** 3.59384 lb/gal

**VOC Regulatory:** 430.65000 g/l

**Flash Point:** N.A.

**Viscosity:** N.A.

**Lower Explosion Level:** N.A.

**Upper Explosion Level:** N.A.

**Melting Point:** N.A.

**Vapor Density:** Slower than ether

**Freezing Point:** N.A.

**Low Boiling Point:** 0 °F

**High Boiling Point:** 156 °F

**Decomposition Pt:** 0

**Auto Ignition Temp:** N.A.

**Evaporation Rate:** Slower than ether

### Section 10 ~ Stability and Reactivity

**Stability:** Stable.

**Conditions to Avoid:** High temperatures.

**Incompatible Materials:** None known.

**Hazardous Reactions/Polymerization:** Will not occur.

**Hazardous Decomposition Products:** In fire, will decompose to carbon dioxide, carbon monoxide.

### Section 11 ~ Toxicological Information

**Skin Corrosion/Irritation:** Overexposure will cause defatting of skin. Causes mild skin irritation

**Serious Eye Damage/Irritation:** Overexposure will cause redness and burning sensation.

**Carcinogenicity:** No data available

**Germ Cell Mutagenicity:** No data available

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Respiratory/Skin Sensitization:** No data available

**Specific Target Organ Toxicity - Single Exposure:** No data available

**Specific Target Organ Toxicity - Repeated Exposure:** May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** May be fatal if swallowed and enters airways

**Acute Toxicity:** Inhalation: effect of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.

#### 8052-41-3 STODDARD SOLVENT

LC50 (rat): greater than 5500 mg/m<sup>3</sup> (880 ppm) (whole body exposure for 4 hours) (1)

LC50 (rat): greater than 8200 mg/m<sup>3</sup> (1300 ppm) (2)

LD50 (oral, rat): greater than 5 g/kg (1)

LD50 (dermal, rabbit): greater than 3 g/kg (1)

#### 64742-54-7 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY PARAFFINIC

LD50 (Rodent - rat, Oral): >15 gm/kg, Toxic effects: Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent- rabbit, Administration onto the skin): >5 gm/kg, Toxic Effects: Details of toxic effects not reported other than lethal dose value.

#### 110-54-3 HEXANE

LC50 (male rat): 38500 ppm (4-hour exposure); cited as 77000 ppm (271040 mg/m<sup>3</sup>) (1-hour exposure) (15)

LC50 (rat): 48000 ppm (4-hour exposure) (16)

LC50 (rat): 73680 ppm (260480 mg/m<sup>3</sup>) (4-hour exposure) (n-hexane and isomers) (1,3)

LD50 (oral, 14-day old rat): 15840 mg/kg (3)

LD50 (oral, young rat): 32340 mg/kg (3)

LD50 (oral, adult rat): 28700 mg/kg (3,16)

#### 75-28-5 ISOBUTANE

LC50 (mouse, inhalation): 520,000 ppm (52%); 2-hour exposure. (4)

#### 106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m<sup>3</sup>) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9)

LC50 (rat): 276000 ppm (658000 mg/m<sup>3</sup>) (4-hour exposure); cited as 658 mg/L (4-hour exposure) (9)

### Section 12 ~ Ecological Information

**Toxicity:** Harmful to aquatic life with long lasting effects

**Persistence and Degradability:** No data available.

**Bio-Accumulative Potential:** No data available.

**Mobility in Soil:** No data available.

**Other Adverse Effects:** No data available.

#### Bio-accumulative Potential

64742-54-7 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY PARAFFINIC

Contains constituents with the potential to bioaccumulate.

#### Mobility in Soil

64742-54-7 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY PARAFFINIC

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

### Section 13 ~ Disposal Considerations

**Water Disposal:** Under RCRA, it is the responsibility of the user of the product, to determine a time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### Section 14 ~ Transportation Information

**U.S. DOT Information:** Consumer Commodity, ORM-D

**IMDG Information:** Consumer Commodity, ORM-D

**IATA Information:** Consumer Commodity, ORM-D

### Section 15 ~ Regulatory Information

| Chemical Name   | CAS number | % by wt. |   |
|---|------------|----------|---|
| Propane   | 74-98-6    | 7 – 15   | SARA312, VOC, TSCA, ACGIH, OSHA                       |
| Isobutane   | 75-28-5    | 2 – 4    | SARA312, VOC, TSCA, ACGIH                             |
| Butane  | 106-97-8   | 4 – 8    | SARA312, VOC, TSCA, ACGIH                             |
| Hexane  | 110-54-3   | 2 – 5    | CERLA, HAPS, SARA312, SARA313, VOC, TSCA, ACGIH, OSHA |
| Stoddard Solvent  | 8052-41-3  | 15 – 26  | SARA312, VOC, TSCA, ACGIH, OSHA                       |
| Mineral Oil, Petroleum Distillates, Hydrotreated (Mild) | 94742-54-7 | 9 – 21   | SARA312, VOC, TSCA, OSHA                              |
| Heavy Paraffinic  |            |          |   |
| Asphalt, oxidized                                       | 64742-93-4 | 10 – 22  | SARA312, TSCA   |

### Section 16 ~ Other Information

**Glossary:** \* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS. ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec - Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ - Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA - Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

|                  | NFPA | HMIS | Key                     |
|------------------|------|------|-------------------------|
| HEALTH           | 2    | 2    | 4= Severe               |
| FLAMMABILITY     | 3    | 3    | 3= Serious              |
| REACTIVITY       | 0    | 0    | 2= Moderate             |
| OTHER/PROTECTION | -    | B    | 1= Slight<br>0= Minimal |

Disclaimer: Omega Industrial Supply, Inc. To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.