

Omega Asphalt Patch



Driveway Patching Compound



OMEGA ASPHALT PATCH is a ready-mixed compound that can be applied to holes and depressions in any solid base, such as asphalt, concrete, brick, stone or wood. It is ready to use and does not need any heating or mixing preparation. It is made from a combination of hard aggregate, asphalt, resins and wetting agents to match original blacktop surfaces. Tamped into place, it is ready for traffic at once. **OMEGA ASPHALT PATCH** can be applied to either wet or dry surfaces in any temperature from hot to sub-freezing. The particles in **OMEGA ASPHALT PATCH** are smaller than other patching compounds, therefore it will not re-crush under pressure and recreate the hole you have just filled. Provides a much more permanent repair than bagged products.

Directions: Area to be patched must be free from dust, dirt, oil, grease and foreign matter. Spread the compound into areas to be patched. Tamp it in place or roll it in with a car. Areas exceeding one inch depth should be repaired in one inch increments. Use Omega's Natural Way for effortless clean up of tools, vehicles and other surface contacted by **OMEGA ASPHALT PATCH**. Five gallons covers 5 sq. ft. at 1" thick.

Health	1
Flammability	1
Reactivity	0
Protection	**

Areas of Use:

- *Cities and Counties
- *School Districts
- *Colleges
- *Apartment Complexes
- *Building Maintenance
- *Street Departments

Appearance and odor.....	Black coated stone, granular black material with petroleum odor.
Net Wt.....	5 Gallons

Omega Industrial Supply, Inc.

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134