




Section 1 ~ Identification

Identity (As Used On Label and List) A1229 PRIMAL PRIMER LIGHT GRAY	Date Prepared: 12-02-2015
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards	Flammable aerosols	Category 1
Health Hazards	Acute toxicity, inhalation	Category 4
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
OSHA Defined Hazards	Not Classified	
Label Elements	  	Signal Word: Danger.
Hazard Statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.	
Precautionary Statement	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If eye irritation persists: Get medical advice/attention.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not Otherwise Classified (HNOC)	None Known	Supplemental Information None

Section 3 ~ Composition/Information on Ingredients

Chemical Name	Common Name & Synonyms	CAS No.	%(Wt.)
Acetone		67-64-1	20 - 40
Propane		74-98-6	10 - 20
Butane		106-97-8	2.5 - 10
Ethyl Alcohol		64-17-5	2.5 - 10
Magnesium Silicate		14807-96-6	2.5 - 10
n-Butyl Acetate		123-86-4	2.5 - 10
Titanium Dioxide		13463-67-7	2.5 - 10
Toluene		108-88-3	2.5 - 10
Xylene		1330-20-7	2.5 - 10
Other components below reportable levels			20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most Important Symptoms/Effects, Acute and Delayed: Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

Indication of Immediate Medical Attention and Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles

(wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Level 3 Aerosol.

Conditions for Safe Storage, Including Any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US, OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (67-64-1)	PEL	2400 mg/m3 1000 ppm	
Ethyl Alcohol (64-17-5)	PEL	1900 mg/m3 1000 ppm	
n-Butyl Acetate (123-86-4)	PEL	710 mg/m3 150 ppm	
Propane (74-98-6)	PEL	1800 mg/m3 1000 ppm	
Titanium Dioxide (13463-67-7)	PEL	15 mg/m3	Total dust.
Xylene (1330-20-7)	PEL	435 mg/m3 100 ppm	

US, OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value	Form
Toluene (108-88-3)	Ceiling TWA	300 ppm 200 ppm	

US, OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Magnesium Silicate (14807-96-6)	TWA	0.3 mg/m3 0.1 mg/m3 20 mppcf 2.4 mppcf	Total dust. Respirable Respirable

US, ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (67-64-1)	STEL TWA	500 ppm 250 ppm	
Butane (106-97-8)	STEL	1000 ppm	
Ethyl Alcohol (64-17-5)	STEL	1000 ppm	
Magnesium Silicate (14807-96-6)	TWA	2 mg/m3	Respirable fraction.
n-Butyl Acetate (123-86-4)	STEL TWA	200 ppm 150 ppm	
Titanium Dioxide (13463-67-7)	TWA	10 mg/m3	
Toluene (108-88-3)	TWA	20 ppm	
Xylene (1330-20-7)	STEL TWA	150 ppm 100 ppm	

US, NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (67-64-1)	TWA	590 mg/m3 250 ppm	
Butane (106-97-8)	TWA	1900 mg/m3 800 ppm	
Ethyl Alcohol (64-17-5)	TWA	1900 mg/m3 1000 ppm	
Magnesium Silicate (14807-96-6)	TWA	2 mg/m3	Respirable
n-Butyl Acetate (123-86-4)	STEL TWA	950 mg/m3 200 ppm	
Propane (74-98-6)	TWA	710 mg/m3 150 ppm	
Toluene (108-88-3)	TWA	1800 mg/m3 1000 ppm	
	STEL	560 mg/m3 150 ppm	
	TWA	375 mg/m3 100 ppm	

Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (67-64-1)	25 mg/l	Acetone	Urine	*
Toluene (108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure Guidelines

US - California OELs: Skin designation

Toluene (108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (108-88-3) Skin designation applies.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, Such as Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical and Chemical Properties

Appearance	Flash Point: -2.2°F (-19.0°C) supplier estimated	Solubility(ies)
Physical State: Gas.	Evaporation Rate: > 1 BuAc	Solubility (water): Not available.
Form: Aerosol.	Flammability (solid, gas): Not available.	Auto-Ignition Temperature: Not available.
Color: Not available.	Upper/Lower Flammability or Explosive Limits	Decomposition Temperature: Not available.
Odor: Not available.	Explosive Limit - Lower (%): 1.7 % estimated	Viscosity: Not available.
Odor Threshold: Not available.	Explosive Limit - Upper (%): 10.9 % estimated	Other Information
pH: Not available.	Vapor Pressure: 40 psig @70F estimated	Explosive Properties: Not explosive.
Melting Point/Freezing Point: Not available.	Vapor Density: Not available.	Oxidizing Properties: Not oxidizing.
Initial Boiling Point and Boiling Range: -166°F (-110°C) estimated	Relative Density: Not available.	Specific Gravity: 0.81 estimated

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.

Section 11 ~ Toxicological Information

Information on Likely Routes of Exposure

Inhalation: Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Causes serious eye irritation.

Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on Toxicological Effects

Acute Toxicity: May be fatal if swallowed and enters airways. Harmful if inhaled. Narcotic effects.

<i>Components</i>	<i>Species</i>	<i>Test Results</i>
Acetone (67-64-1)		
Acute		
Dermal LD50	Guinea Pig	> 7426 mg/kg, 24 Hours
	Rabbit	> 9.4 ml/kg, 24 Hours
		> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
Oral LD50	Rat	50.1 mg/l
		5800 mg/kg
		2.2 ml/kg
Butane (106-97-8)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52%, 120 Minutes
		1355 mg/l
Ethyl Alcohol (64-17-5)		
Acute		
Inhalation LC50	Cat	85.41 mg/l, 4.5 Hours
	Mouse	43.68 mg/l, 6 Hours
		> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral LD50	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
n-Butyl Acetate (123-86-4)		
Acute		
Dermal LD50	Rabbit	> 16 ml/kg, 24 Hours
Inhalation LC50	Rat	1087 ppm, 4 Hours
		0.74 mg/l, 4 Hours
Oral LD50	Rat	14130 mg/kg
		12.2 ml/kg
Propane (74-98-6)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52 %, 120 Minutes
		1355 mg/l
		658 mg/l/4h
Titanium Dioxide (13463-67-7)		
Acute		
Inhalation LC50	Rat	> 2.28 mg/l, 4 Hours
Oral LD50	Mouse	> 5000 mg/kg
	Rat	> 2000 mg/kg
Toluene (108-88-3)		
Acute		
Dermal LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		25.7 mg/l, 4 Hours
Oral LD50	Rat	> 5000 mg/kg
Xylene (1330-20-7)		

Acute		
Dermal LD50	Rabbit	> 5000 ml/kg, 4 Hours 12126 mg/kg, 24 Hours
Inhalation LC50	Rat	5922 ppm, 4 Hours
Oral LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg 10 ml/kg

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Prolonged skin contact may cause temporary irritation.

Serious Eye Damage/Eye Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Magnesium Silicate (14807-96-6)	2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
Titanium dioxide (13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens: Not available.

Reproductive Toxicity: Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific Target Organ Toxicity - Single Exposure: May cause drowsiness and dizziness.

Specific Target Organ Toxicity - Repeated Exposure: Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Chronic Effects: May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12 ~ Ecological Information

Ecotoxicity: Harmful to aquatic life with long lasting effects.

<u>Components</u>	<u>Species</u>	<u>Test Results</u>
Acetone (67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
		21.6 - 23.9 mg/l, 48 hours 4740 - 6330 mg/l, 96 hours
Ethyl Alcohol (64-17-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Fathead minnow (Pimephales promelas)
		7700 - 11200 mg/l, 48 hours > 100.1 mg/l, 96 hours
n-Butyl Acetate (123-86-4)		
Aquatic		
Algae	IC50	Algae
Fish	LC50	Fathead minnow (Pimephales promelas)
		674.7 mg/L, 72 Hours 17 - 19 mg/l, 96 hours
Titanium Dioxide (13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Mummichog (Fundulus heteroclitus)
		> 1000 mg/l, 48 hours > 1000 mg/l, 96 hours
Toluene (108-88-3)		
Aquatic		
Algae	IC50	Algae
Crustacea	EC50	Daphnia
		Water Flea (Daphnia Magna)
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)
		433.0001 mg/L, 72 Hours 7.645 mg/L, 48 Hours 5.46 - 9.83 mg/l, 48 hours 8.11 mg/l, 96 hours
Xylene (1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus)
		7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24	Butane	2.89
Ethyl Alcohol	-0.31	n-Butyl Acetate	1.78
Propane	2.36	Toluene	2.73
Xylene	3.12 - 3.2		

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section 14 ~ Transportation Information

DOT	IATA	IMDG
UN Number UN1950	UN Number UN1950	UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)	UN Proper Shipping Name: Aerosols, flammable	UN Proper Shipping Name: AEROSOLS
Transport Hazard Class(es)	Transport Hazard Class(es)	Transport Hazard Class(es)
Class: 2.1	Class: 2.1	Class: 2.1
Subsidiary Risk -	Subsidiary Risk -	Subsidiary Risk -
	Label(s): 2.1	Label(s): 2.1

Label(s): 2.1
Packing Group: Not applicable.
Special Provisions: N82
Packaging Exceptions: 306
Packaging Non Bulk: None
Packaging Bulk: None

Packing Group: Not applicable.
Environmental Hazards: No.
ERG Code: 10L
Other Information
Passenger and Cargo Aircraft: Allowed with restrictions.
Cargo Aircraft Only: Allowed with restrictions.
Packaging Exceptions: LTD QTY

Packing Group: Not applicable.
Environmental Hazards
Marine Pollutant: No.
EmS: F-D, S-U
Packaging Exceptions: LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
 This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

DOT

IATA:IMDG



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (67-64-1)	Listed.	n-Butyl Acetate (123-86-4)	Listed.
Toluene (108-88-3)	Listed.	Xylene (1330-20-7)	Listed.

SARA 304 Emergency Release Notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA): Hazard Categories:

Immediate Hazard – Yes Delayed Hazard – Yes Fire Hazard – Yes Pressure Hazard – No Reactivity Hazard – No

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Toluene	108-88-3	2.5 – 10
Xylene	1330-20-7	2.5 – 10

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Toluene (108-88-3) Xylene (1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane (106-97-8) Propane (74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (67-64-1)	6532	Toluene (108-88-3)	6594
-------------------	------	--------------------	------

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (67-64-1)	35 % WV	Toluene (108-88-3)	35 % WV
-------------------	---------	--------------------	---------

DEA Exempt Chemical Mixtures Code Number

Acetone (67-64-1)	6532	Toluene (108-88-3)	594
-------------------	------	--------------------	-----

US State Regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (67-64-1)	Butane (106-97-8)	Magnesium Silicate (14807-96-6)	Titanium dioxide (13463-67-7)	Toluene (108-88-3)
-------------------	-------------------	---------------------------------	-------------------------------	--------------------

Xylene (1330-20-7)

US. Massachusetts RTK - Substance List

Acetone (67-64-1)
 Butane (106-97-8)
 Ethyl Alcohol (64-17-5)
 Magnesium Silicate (14807-96-6)
 n-Butyl Acetate (123-86-4)
 Propane (74-98-6)
 Titanium Dioxide (13463-67-7)
 Toluene (108-88-3)
 Xylene (1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (67-64-1)
 Butane (106-97-8)
 Ethyl Alcohol (64-17-5)
 Magnesium Silicate (14807-96-6)
 n-Butyl Acetate (123-86-4)
 Propane (74-98-6)
 Titanium Dioxide (13463-67-7)
 Toluene (108-88-3)
 Xylene (1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (67-64-1)
 Butane (106-97-8)
 Ethyl Alcohol (64-17-5)
 Magnesium Silicate (14807-96-6)
 n-Butyl Acetate (123-86-4)
 Propane (74-98-6)
 Titanium Dioxide (13463-67-7)
 Toluene (108-88-3)
 Xylene (1330-20-7)

US. Rhode Island RTK

Acetone (67-64-1)
 Butane (106-97-8)
 n-Butyl Acetate (123-86-4)
 Propane (74-98-6)
 Magnesium Silicate (14807-96-6)
 Toluene (108-88-3)
 Xylene (1330-20-7)

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (13463-67-7)	Listed: September 2, 2011
-------------------------------	---------------------------

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (108-88-3)	Listed: January 1, 1991
--------------------	-------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2*	4= Severe
FLAMMABILITY	4	4	3= Serious
REACTIVITY	0	2	2= Moderate
OTHER/PROTECTION	-	X	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.