

# Primal Primer

## Primer Coating



**Primal Primer** coating for use on bare metal and bare wood surfaces. Provides massive rust protection. Fast drying sag free spray helps prevent rust and all chemical corrosion. **Available in Gray and Red**

### Directions

1. Surface must be clean and dry before painting. For better adhesion, sand lightly with fine sandpaper or steel wool.
2. Shake can at least one minute after rattle is heard and occasionally during use. For best results, use when can is between 70°F and 90°F (21°C and 32°C).
3. Spray surface with steady even strokes at a distance of 8 to 10 inches. One light coat will provide the best finish.
4. If clogging develops, turn nozzle 1/4 turn or remove and clean button slot. Do not stick objects into can opening.
5. After painting, turn can upside down and spray for 2 seconds to clean nozzle.
6. Discard empty can in trash pick up. Do not incinerate or compact.

Health	2*
Flammability	4
Physical Hazard	2
Protection	X

### Areas of Use:

- \*Hotels
- \*Schools
- \*Cities
- \*Counties
- \*Amusement Parks
- \*Stadiums
- \*Apartments
- \*Public Buildings

Appearance & Odor.....	Aerosol, Odor not available.
Specific Gravity.....	0.81 Estimate
Net Contents.....	12 Oz

***Omega Industrial Supply, Inc.***

Fairfield, CA 94534  
 1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134