

Safe Step

Epoxy Based Non-Slip Paint



SAFE STEP is a super hard, textured one part epoxy coating that quickly cures to a slip resistant rough grit surface. Unique aerosol contains special synthetic grit that contains no sharp edges so it will not cut wet feet or hands, aids in the reduction of slip and fall accidents and makes slippery surfaces more safe to walk on. Helps decrease potential hazards due to slippery surfaces and reduces the potential for personal injury or liability claims. **SAFE STEP** eliminates the need for mixing, waste, added cleanup, and application of a separate grit. **SAFE-STEP** adheres to most hard surfaces. One application of **SAFE-STEP** lasts for up to six months depending on foot traffic. **Available in Clear, Yellow and Black.**

Directions: To ensure proper adhesion, clean area with Omega's **MEGA POWER** degreaser to ensure area is free of any grease or oily residue. Existing paint can be removed with **JELL STRIP**. Allow surfaces to dry before application of **SAFE STEP**. Before initial application to surface light etching or sanding is recommended. Shake can well before and during application. Spray in a sweeping motion 12 to 15 inches from surface to be treated. Dries to touch in one hour. Wait 24 hours before subjecting to heavy foot traffic. Recoat every 3 to 6 months depending on wear.

Black and Clear

Health	*2
Flammability	4
Physical Hazard	3
Protection	X

Yellow

Health	*2
Flammability	4
Physical Hazard	1
Protection	X

Areas of Use:

- *Steps, Walkways, Ramps
- *Municipalities
- *Parks/Recreations
- *Public Restrooms
- *Apartment Complexes
- *School Districts
- *Amusement Parks

Appearance	Various colored gas aerosol.
Specific Gravity.....	Blk- 0.551 est, Clear- 0.584 est, Ylw- 0.85 est.
Net Wt.	12 oz.

Omega Industrial Supply, Inc.

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134