

## Section 1 ~ Identification

<b>Identity (As Used On Label and List)</b> <b>A1036 SUPER SILICONE</b>	<b>Date Prepared:</b> 11-20-2014
<b>Company Information:</b> OMEGA INDUSTRIAL SUPPLY, INC	<b>Emergency Telephone Number:</b> 1-800-424-9300
<b>Address (Number, Street, Suite/Apt#)</b> 101 Grobric Ct #1	<b>Telephone Number for Information:</b> 1-800-571-7347
<b>(City, State, and Zip Code)</b> Fairfield, CA 94534	<b>Signature of Prepare (Optional)</b> REGULATORY DEPT.

## Section 2 ~ Hazard(s) Identification

<b>Classification</b>	Flammable Aerosol: Category 1 Liquefied Gas Skin Irritant: Category 2 Eye Irritant: Category 2A Specific Target Organ Toxicity (Single Exposure): Category 3 Aspiration Hazard: Category 1
<b>Hazard Statement(s)</b>	Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways. This product contains the following percentage of chemicals of unknown toxicity: 0%
<b>Precautionary Statements</b>	<b>DANGER:</b> Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

<b>Symbols</b>	   
----------------	---

**Hazards Not Otherwise Classified:** N/A

## Section 3 ~ Composition/Information on Ingredients

Hazardous Ingredient	CAS No.	%(WT.)
Acetone	67-64-1	30 – 60
Heptane	142-82-5	10 – 30
Propane/n-Butane	68476-86-8	30 – 60

## Section 4 ~ First Aid Measures

**Eyes:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.  
**Ingestion:** If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.  
**Inhalation:** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.  
**Skin:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.  
**Acute Health Hazards:** Eyes: redness, tearing, blurred vision  
Skin: defatting and dermatitis  
Inhalation: drowsiness and dizziness  
Oral: abdominal irritation, nausea, vomiting, and diarrhea  
**Chronic Health Hazards:** None known  
**Note to Physician:** If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

## Section 5 ~ Fire Fighting Measures

**Extinguishing Media:** CO<sub>2</sub>, Dry Chemical  
**Unsuitable Extinguishing Media:** Water spray/stream.  
**Special Fire Fighting Procedures:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.  
**Unusual Fire and Explosion Hazards:** Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.  
**Hazardous Combustion Products:** Oxides of carbon

## Section 6 ~ Accidental Release Measures

**Personal Protective Equipment:** Refer to section 8 for proper Personal Protective Equipment.  
**Spill:** Eliminate all sources of ignition. absorb liquid with non-combustible material like vermiculite, sand or earth and clean up with mop or rag.  
**Waste Disposal:** Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.  
**RCRA Status:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

## Section 7 ~ Handling and Storage

**Handling and Storage:** Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.  
**Other Precautions:** Keep out of the reach of children.  
**Incompatibility:** Strong oxidizing agents.

## Section 8 ~ Exposure Controls/Personal Protection

Hazardous Ingredient	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Heptane	500 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm

**Engineering Controls / Ventilation:** Use only outdoors or in a well-ventilated area.  
**Respiratory Protection:** Wear NIOSH/MSHA approved organic vapor respiratory protection if exposure limits are exceeded.  
**Personal Protective Equipment:** Safety glasses and chemical resistant gloves  
**Additional Measures:** Wash hands thoroughly after handling.

## Section 9 ~ Physical Chemical Properties

<b>Appearance:</b> Clear, Colorless Spray	<b>Lower Flammability Limit:</b> N/D	<b>Solubility In Water:</b> 0%
<b>Odor:</b> Solvent odor	<b>Upper Flammability Limit:</b> N/D	<b>Partition Coefficient: n-OCTANOL/WATER (KOW):</b> N/D
<b>Odor Threshold:</b> N/D	<b>Vapor Pressure (mm Hg):</b> >36 @ 77°F (25°C)	<b>Volatility Including Water (%):</b> 97%
<b>Boiling Point:</b> <200°F	<b>Vapor Density (AIR=1):</b> > 2	<b>Volatile Organic Compounds (VOC):</b> 55%

<b>Freezing Point:</b> N/D	<b>Evaporation Rate:</b> >3 Fast	<b>Dielectric Strength (Volts):</b> N/D
<b>Flammability:</b> Extremely Flammable Aerosol	<b>Specific Gravity (H2O=1):</b> 0.755	<b>Decomposition Temperature:</b> N/D
<b>Flash Point:</b> <5° F	<b>pH:</b> N/A	<b>Viscosity:</b> N/D
<b>Auto-Ignition Temperature:</b> N/D	<b>Solids (%):</b> N/D	

### Section 10 ~ Stability and Reactivity

**Reactivity:** Certain plastics, rubber, strong oxidizers  
**Chemical Stability:** Stable  
**Conditions to Avoid:** Temperatures greater than 122°F and sources of ignition.  
**Incompatibility:** Strong oxidizing agents.  
**Hazardous Decomposition or By-Product:** Silicone Dioxide, Carbon oxides, Formaldehyde  
**Possible Hazardous Reactions:** None Known

### Section 11 ~ Toxicological Information

**Toxicological Information:** Acetone (67-64-1) LD50 (Oral, Rat) 5800 mg/kg; LD50 (Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg; LC50 (Inhalation, Rat, 8hr) 50100 mg/m3; LC50 (Inhalation, Mouse, 4hr) 44,000 mg/m3 **Heptane** (142-82-5) LD50 (Oral, Rat) 15,000 mg/kg; LC50 (Inhalation, Rat, 4hr) 103 g/m3; LD50 (Dermal, Rabbit) 2,000 mg/kg  
**Routes of Entry:** Eyes, Ingestion, Inhalation, Skin  
**Eyes:** Causes irritation, redness, tearing, pain, blurred vision.  
**Ingestion:** Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting.  
**Inhalation:** Causes dizziness, excessive or prolonged exposure may cause unconsciousness.  
**Skin:** Causes localized defatting, irritation, dermatitis.  
**Medical Condition Aggravated:** Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.  
**Acute Health Hazards:** Eyes: redness, tearing, blurred vision  
 Skin: defatting and dermatitis  
 Inhalation: drowsiness and dizziness  
 Oral: abdominal irritation, nausea, vomiting, and diarrhea  
**Chronic Health Hazards:** None known  
**Carcinogenicity:** OSHA: No ACGIH: N/A NTP: No IARC: N/A OTHER: N/A

### Section 12 ~ Ecological Information

**Ecological Information:** Acetone (67-64-1) LC50 (Trout, 96hr) 5540 mg/L; LC50 (Bluegill, 96hr) 8300 mg/L; LC50 (Fathead Minnow, 96hr) 7500 mg/L  
**Biodegradability:** Component or components of this product are not biodegradable.  
**Bioaccumulation:** This product is not expected to bioaccumulate.  
**Soil Mobility:** This product is mobile in soil.  
**Other Ecological Hazards:** This material is toxic to aquatic life.

### Section 13 ~ Disposal Considerations

**Waste Disposal:** Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.  
**RCRA Status:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### Section 14 ~ Transportation Information

<b>Proper Shipping Name:</b> Aerosols, Ltd. Qty. <b>Hazard Class/Division:</b> 2.1 <b>UN/NA Number:</b> UN 1950 <b>Packaging Group:</b> N/A	<b>Air Shipment</b> <b>Proper Shipping Name:</b> Aerosols, Ltd. Qty. <b>Hazard Class/Division:</b> 2.1 <b>UN/NA Number:</b> UN 1950	<b>Shipping by Water: Vessel (IMO/IMDG)</b> <b>Proper Shipping Name:</b> Aerosols, Ltd. Qty. <b>Hazard Class/Division:</b> 2.1 <b>UN/NA Number:</b> UN 1950 <b>Environmental Hazards Water:</b> Marine Pollutant
--	--	--

### Section 15 ~ Regulatory Information

**TSCA Status:** All Chemicals are listed or exempt.  
**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Acetone (67-64-1) Reportable Quantity = 5,000 lbs  
**SARA 311/312 Hazard Categories:** Acute Health, Fire  
**SARA 313 Reportable Ingredients:** None  
**State Regulations:** Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, RTK - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339); Acetone TSCA 8(b) inventory; Acetone TSCA 4(a) final test rules; Acetone TSCA 8(a) IUR; Acetone  
**Heptane** (142-82-5) California Director's List of Hazardous Substances, Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, New Jersey RTK, Massachusetts RTK, Minnesota RTK, Pennsylvania RTK, Rhode Island RTK  
**International Regulations:** All components are listed or exempted.

### Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	3	3	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	B	1= Slight 0= Minimal

Disclaimer: Omega Industrial Supply, Inc. To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.