

# AIR TOOL REJUVENATOR

Cleaner/Lubricant  
& Corrosion Inhibitor



**AIR TOOL REJUVENATOR** will prevent rust and corrosion on all metal parts. Apply to machine parts, dies, pipe threads, casting, tools, jigs and stamped metal parts. Prevents corrosion due to salt spray on cables, hoists, pulleys, winches and riggings. Affords long term protection for indoor storage. **AIR TOOL REJUVENATOR** is excellent for protecting materials while in transit. A 2 or 3 mil coating will provide protection for indoor storage for up to 2 years. Film is transparent, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

#### DIRECTIONS:

**SHAKE WELL BEFORE USING.** For interior application, insert extension tube into spray nozzle prior to use.  
1. Spray into all openings including air inlet connection.  
2. Allow product to penetrate for several seconds.  
3. Run air tool at maximum RPM for 30 seconds.  
4. Repeat above for severe conditions.  
5. For long term tool storage, repeat directions 1 through 3.

Health	1
Flammability	2
Physical Hazard	0
Protection	B

#### Areas of Use:

- \*Construction
- \*Municipalities
- \*Transportation
- \*Parks/Recreation
- \*Automotive Garages
- \*Refineries
- \*Amusement Parks
- \*Factories/Warehouses

Appearance & Odor.....	Milky tan liquid with oily odor
Relative Density.....	0.83 - 0.86 g/ml @ 77°F (25°C)
Net Contents.....	11 OZ. (312 Grams)

## OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 307-514-0631