
CONCRETEMAN







CONCRETEMAN is a handy, ready to use concrete repair putty that is designed for sealing small holes and patching chips in concrete, including floors, stairs, wall tiles, lawn ornaments and statues. It is a very convenient way to fill holes in sidewalks drilled by utility work crews and repair minor damage on any concrete surface. When dry it has the color of concrete for less noticeable repairs. **CONCRETEMAN** hardens like concrete in on hour and can be drilled, tapped, filed, sawed, or painted once cured. This epoxy putty can also be used under water and has a cure time of only 60 minutes for quick fixes. May cause mild skin irritation, use Omega's **SHIELD** skin protector to reduce potential for irritation while maintaining dexterity.

DIRECTIONS:

Before applying, roughen and clean the area to be repaired. Then follow these easy steps: 1) CUT or twist off required amount. 2) MIX by kneading with fingers to a uniform color. If mixing is difficult, warm **CONCRETEMAN** to room temperature or slightly above. 3) APPLY to surface to be repaired within 2 minutes of mixing. For best adhesion, force into any cracks or holes and strike off excess material, preferably with a tool moistened with clean water. When applying to a damp, wet or slowly leaking area, work the mixed epoxy putty forcefully into the surface and apply pressure until adhesion begins to take effect. **For best results:** Use damp fingers for easier mixing, application and a smooth appearance of the cured compound. Remove excess material before hardening begins. **Curing: CONCRETEMAN** has a 3 to 5 minutes work life. Functional cure occurs in one hour.

Health	2
Flammability	0
Physical Hazard	0
Protection	-

Areas of Use:

*Utility Companies

*Apartment Complexes

*Grounds Departments

*Construction Companies

*Hotels

*Cities & Counties

*Building Maintenance

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Chevenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631