

FAST

Penetrating Lubricant



FAST will loosen dirt and scale from painted and plated surface. Remove loosened scale and spray again to cover surface. Liberal application will loosen threads, tightly fitted parts, sliding and rotating parts, bolts, hinges and pins which have been “frozen” by corrosion. The formula will protect against renewed corrosion. **FAST** is a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture and sealing all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Dielectric strength 30,000 volts. **CORRODED SURFACES:** Will loosen dirt and scale from painted and plated surfaces. Remove loosened scale and spray again to cover surface. **TO LOOSEN BOUND PARTS:** Liberal application will loosen threads, tightly fitted parts, sliding and rotating parts, bolts, hinges and pins which have been “frozen” by corrosion. The formula will protect against renewed corrosion. Also lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard. Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected by the formula. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for re-application.

DIRECTIONS

Spray liberally directly on area to be treated. Re-apply periodically as required.

Health	1
Flammability	1
Physical Hazard	0
Protection	A

Areas of Use:

- *Machine Shops
- *Factories
- *Assembly Plants
- *Auto Body Shops
- *Mechanic Shops
- *Oil Rigs
- *Locksmiths
- *Air Conditioning Repair

Appearance & Odor.....	Amber spray with bland odoe
VOC%.....	0%
Net Contents.....	15 OZ (426 Grams)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631