

REBAR EPOXY COATING GREEN

Protects Against Corrosion



REBAR EPOXY COATING GREEN is a high performance, single stage epoxy coating that protects cut rebar. Protects against corrosion and rust staining when applied to rebar before setting in concrete. Prevents oxidation on the cut ends and is ideal for spot repair of damaged coatings. ASTM A775/A775-07 and D3963/D3963M-01 performance requirements for corrosion resistance and flexibility when repairing defects in coatings for rebar.

DIRECTIONS

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. **DO NOT** stick pin or other objects into can opening. With the can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. **DO NOT** incinerate or compact.

Areas of Use:

- *Industrial Plants
- *Cities & Counties

- *Stadiums
- *Construction Companies

Appearance & Odor.....	Aerosol with aromatic odor
VOC%.....	0%
Net Contents.....	12 OZ (340 g)

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631