

RED I GREASE

Non-Melt Spray Grease



RED I GREASE is a cured lubricant that withstands heat to 350°F, moisture, acids, high pressure and is highly rust resistant. This VOC compliant formula provides superior lubrication while forming a thick, long-lasting film to prevent future corrosion. A high pressure additive reduces wear and prolongs operational life of all machinery. Temperatures above 350°F may require periodic re-application.

DIRECTIONS

Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.

Health	3
Flammability	4
Physical Hazard	0
Protection	B

Areas of Use:

*Wire Rope	*Fittings
*Open Gears	*Winches
*Linkages	*Cranes
*Draglines	*Cables

Appearance & Odor.....	Opaque red spray with solvent odor
Relative Density (H ₂ O=1).....	0.83 - 0.87 @ 77°F (25°C)
Net Contents.....	14 oz.

OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 www.onlyomega.com Fax: 307-514-0631