

# SUPER O.G.L.

Open Gear Lubricant



**SUPER O.G.L.** is a solid film, highly viscous lubricant for use on gears, chains, cables, wire ropes, sprockets, industrial machinery, heavy construction equipment. Protects against rust and corrosion by repelling water from surfaces. Excellent stretching characteristics allow surfaces to be completely covered with lubricant, extending life of machinery and reducing down time and maintenance. Reduces noise and protects gears in case of excessive loads. Effective temperature range of +20°F to +175°F.

## DIRECTIONS:

Shake can well before using. Remove protective cap. Hold can 6 to 8 inches from surfaces to be sprayed. Apply an even coat to surface. Turn on machinery and allow lubricant to spread over all working surfaces. Apply a second thinner coating to insure adequate lubrication. Reapply as needed to lubricate and protect equipment. After spraying, turn can upside down and spray until nozzle is clear.

Health	1
Flammability	3
Physical Hazard	0
Protection	B

## Areas of Use:

- \*Hotels
- \*Schools
- \*Cities & Counties
- \*Restaurants
- \*Stadiums
- \*Casinos
- \*Amusement Parks

Appearance & Odor.....	Dark brown viscous spray with a petroleum odor
Relative Density (H <sub>2</sub> O=1).....	0.84 - 0.88 @ 77 °F (25 °C)
VOC%.....	24.8%
Net Contents.....	12 OZ (340 Grams)

## OMEGA INDUSTRIAL SUPPLY, INC.

1133 W 27th Street, Cheyenne, WY 82001

1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 307-514-0631