

UV Super Patch

Industrial Strength Repair Patch



This unique patch material is ideal for repairing leaky pipes, tanks, corroded metal parts, cracked or rotted wood along with hundreds of other applications. **UV SUPER PATCH** will not rot or rust. The quick and easy solution for all your repair problems. **UV SUPER PATCH** is great for the tool box, job site, repair trucks, maintenance departments or at home!

USE ON: Plastic, metal, pipes, concrete, drywall, fiberglass, wood, rubber, gutters and much more! (Except Polypropylene)

Directions:

1. Use on a clean and dry surface.
2. Remove **UV SUPER PATCH's** protective cover (away from sun or UV light).
3. Use whole patch or cut-to-size if desired. (Place any unused portion back into protective cover for future use.)
4. Peel (color) backing to reveal adhesive side.
5. Apply adhesive side to repair area.
6. Once patch is in place, remove (color) film and apply pressure to ensure bond.
7. Expose to sun or UV lighting to cure according to the chart on label.

Maximum PSI: 500 PSI
Load: 1,461 Pound-Force
Water Absorbtion: 0.36%

Shelf Life on OPENED pouch: 3 Months (if not exposed to light)
Time to Cure in Sunlight: 8 to 10 minutes
Time to Cure under UV Light: 10 to 15 minutes

Areas of Use:

- *Hospitals
- *Plumbing
- *Municipalities
- *School Districts
- *Hotels
- *Amusement Parks

Health	1
Flammability	0
Physical Hazard	0
Protection	A

Appearance & Odor.....	Soft tacky material with low odor.
Net Wt.	9" x 12"

Omega Industrial Supply, Inc.

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134