




This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification

Identity (As Used On Label and List) A1048 Acousta Tile	Date Prepared: 08-12-2015
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobriic Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

<i>Physical Hazards</i>	Flammable aerosols	Category 1
<i>Health Hazards</i>	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, repeated exposure	Category 2
<i>Environmental Hazards</i>	Not classified	<i>Hazard(s) not otherwise classified (HNOC):</i> None known.
<i>OSHA Defined Hazards</i>	Not classified	<i>Supplemental information:</i> None.
<i>Label elements</i>	  	<i>Signal Word:</i> Danger <i>Disposal:</i> Not available.
<i>Hazard Statement</i>	Extremely flammable aerosol. Causes serious eye irritation. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.	
<i>Precautionary Statement Prevention</i>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.	
<i>Response</i>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.	
<i>Storage</i>	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	

Section 3 ~ Composition/Information on Ingredients

Components (Specific Chemical Identity, Common Name(s))	CAS No.	%(Wt.)
Butane	106-97-8	20 - 40
Ethyl Alcohol	64-17-5	20 - 40
Acetone	67-64-1	10 - 20
Magnesium Silicate	14807-96-6	10 - 20
Propane	74-98-6	2.5 - 10
Titanium dioxide	13463-67-7	2.5 - 10
Toluene	108-88-3	2.5 - 10
Other components below reportable levels	-	10 - 20

* Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Eyes: Rinse with water. Get medical attention if irritation develops and persists.
Skin: Wash off with soap and water. Get medical attention if irritation develops and persists.
Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.
Ingestion: Rinse mouth. Get medical attention if symptoms occur.
Most Important Symptoms/Effects, Acute And Delayed: Headache. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. Prolonged exposure may cause chronic effects.
Indication Of Immediate Medical Attention And Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Powder, alcohol resistant foam. Carbon dioxide (CO2).
Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising From The Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special Protective Equipment And Precautions For Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment And Emergency Procedures: Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods And Materials For Containment And Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions For Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions For Safe Storage, Including Any Incompatibilities: Level 2 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection**Occupational Exposure Limits:****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3 Form: Total dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Magnesium Silicate (CAS 14807-96-6)	TWA	0.3 mg/m3 Form: Total dust. 0.1 mg/m3 Form: Respirable. 20 mppcf 2.4 mppcf Form: Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m3 Form: Respirable fraction. 10 mg/m3
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m3 Form: Respirable.
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation — Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies — Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls – Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Respiratory Protection – If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Skin Protection Other– Wear suitable protective clothing. Use of an impervious apron is recommended.

Hand Protection – Wear appropriate chemical resistant gloves.

Eye/face protection – Wear safety glasses with side shields (or goggles).

Thermal hazards – Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations – When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical Chemical Properties

Boiling Point	179.76 °F (82.09 °C) estimated	Specific Gravity	0.994 estimated
Vapor Pressure	95.21 psig @70°F estimated	Melting/Freezing Point	Not available
Vapor Density	Not available	Evaporation Rate (Butyl Acetate = 1)	Not available
Solubility in Water	Not available	pH	Not available
Appearance and Odor	Gas, aerosol, odor not available.	VOC%	-
Flash Point: -156.0 °F (-104.4 °C) Propellant estimated	Auto - Ignition Temperature: 699.8 °F (371 °C) estimated	Lower Flammability Level: 3.4 % estimated	Upper Flammability Level: 10.7 % estimated

Section 10 ~ Stability and Reactivity

Stability: Material is stable under normal conditions.	Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.	Possibility of Hazardous Reactions: Hazardous polymerization does not occur.
---	--	---

Incompatibility (Materials to Avoid) – Strong oxidizing agents, nitrates, fluorine, chlorine

Hazardous Decomposition or Byproducts – No hazardous decomposition products are known.

Reactivity – The product is stable and non-reactive under normal conditions of use, storage and transport.

Section 11 ~ Toxicological Information**Information on likely routes of exposure****Ingestion:** Expected to be a low ingestion hazard.**Inhalation:** May cause damage to organs through prolonged or repeated exposure by inhalation. Prolonged inhalation may be harmful.**Skin contact:** No adverse effects due to skin contact are expected.**Eye contact:** Causes serious eye irritation.**Symptoms related to the physical, chemical and toxicological characteristics:** Headache. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation.**Information on toxicological effects****Acute toxicity:**

<u>Product</u>	<u>Species</u>	<u>Test Results</u>	<u>Product</u>	<u>Species</u>	<u>Test Results</u>
Acetone (CAS 67-64-1)			Oral LD50	Monkey	6000 mg/kg
Acute				Mouse	10500 ml/kg
Dermal LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours		Rat	1187 - 2769 mg/kg 7800 ml/kg
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours	Propane (CAS 74-98-6)		
Inhalation LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l	Acute	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
Oral LD50	Rat	5800 mg/kg 2.2 ml/kg	Inhalation LC50	Rat	1355 mg/l 658 mg/l/4h
Butane (CAS 106-97-8)			Titanium Dioxide (CAS 13463-67-7)		
Acute			Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes	Inhalation LC50	Rat	> 2.28 mg/l, 4 Hours
	Rat	1355 mg/l	Oral LD50	Rat	> 11000 mg/kg
Ethyl Alcohol (CAS 64-17-5)			Toluene (CAS 108-88-3)		
Acute			Acute		
Inhalation LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours	Dermal LD50	Rabbit	> 5000 mg/kg, 24 Hours 6405 - 7436 ppm, 6 Hours
	Mouse	> 60000 ppm 79.43 mg/l, 134 Minutes	Inhalation LC50	Mouse	5320 ppm, 8 Hours 5879 - 6281 ppm, 6 Hours
	Rat	> 115.9 mg/l, 4 Hours 51.3 mg/l, 6 Hours		Rat	12.5 - 28.8 mg/l, 4 Hours
			Oral LD50	Rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation: Not applicable. Prolonged skin contact may cause temporary irritation**Serious eye damage/eye irritation:** Causes serious eye irritation.**Respiratory sensitization:** Not available.**Skin sensitization:** This product is not expected to cause skin sensitization.**Germ cell mutagenicity:** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.**Carcinogenicity:** Risk of cancer cannot be excluded with prolonged exposure.**IARC Monographs. Overall Evaluation of Carcinogenicity***Magnesium Silicate (CAS 14807-96-6)* 2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.*Titanium dioxide (CAS 13463-67-7)* 2B Possibly carcinogenic to humans.*Toluene (CAS 108-88-3) 3* 3 Not classifiable as to carcinogenicity to humans.**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed.**Reproductive Toxicity:** Suspected of damaging the unborn child.**Specific Target Organ Toxicity -single exposure:** Not classified.**Specific Target Organ Toxicity - repeated exposure:** Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.**Aspiration Hazard:** Not likely, due to the form of the product.**Chronic Effects:** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.**Section 12 ~ Ecological Information****Ecotoxicity:** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

<u>Components</u>	<u>Species</u>	<u>Test Results</u>
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, Donaldson trout (Oncorhynchus mykiss)
		21.6 - 23.9 mg/l, 48 hours 4740 - 6330 mg/l, 96 hours
Ethyl Alcohol (CAS 64-17-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Fathead minnow (Pimephales promelas)
		7700 - 11200 mg/l, 48 hours > 100.1 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Mummichog (Fundulus heteroclitus)
		> 1000 mg/l, 48 hours > 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)		
Aquatic		
Algae		Algae
		433.0001 mg/L, 72 Hours
Daphnia	IC50	Daphnia
		7.645 mg/L, 48 Hours
Crustacea	EC50	Water flea (Daphnia magna)
		5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)
		8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability: No data is available on the degradability of this product.**Bioaccumulative potential:** No data available.**Partition coefficient n-octanol / water (log Kow)****Mobility in soil:** No data available.

Acetone	-0.24	Propane	2.36
Butane	2.89	Toluene	2.73
Ethyl Alcohol	-0.31		

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations: Dispose in accordance with all applicable regulations.

Hazardous waste code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA (Resource Conservation and Recovery Act) Hazardous Waste U List: Reference: Acetone (CAS 67-64-1) U002, Toluene (CAS 108-88-3) U220

Waste from residues / Unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). **Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Section 14 ~ Transport Information

US Depart. of Transportation (DOT)		Water Transportation (IMDG)		Air Transportation (IATA)	
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)	Proper Shipping Name:	Aerosols	Proper Shipping Name:	Aerosols, flammable
Hazard Class:	2.1	Hazard Class:	2.1	Hazard Class:	2.1
Special provisions	N82	Marine pollutant	No	ERG Code	10L
UN Number:	UN1950	UN Number:	UN1950	UN Number:	UN1950
Packing exceptions:	306	Packing exceptions:	Ltd. Qty.	Packing exceptions:	Ltd. Qty.
Labels:	2.1	Labels:	2.1	Labels:	2.1

Packaging bulk: This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

DOT



IATA;IMDG



Section 15 ~ Regulatory Information

US federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

CERCLA Hazardous CERCLA Hazardous

SARA 304 Emergency Release Notification:

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard categories:

Immediate Hazard – Yes; Delayed Hazard – Yes; Fire Hazard – Yes; Pressure Hazard – No, Reactivity Hazard – No.

SARA 302 Extremely Hazardous Substance:

Not regulated

Acetone (CAS 67-64-1) Listed; Toluene (CAS 108-88-3) Listed.

Not regulated.

Not listed.

Not listed.

SARA 311/312 Hazardous Chemical:

SARA 313 (TRI reporting) Chemical name

Toluene

108-88-3

2.5 – 10%

t-Butyl Alcohol

75-65-0

0.1 – 1%

Benzene

71-43-2

0.01 - 0.1%

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA):

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR

Acetone (CAS 67-64-1)

6532

1310.02(b) and 1310.04(f)(2) and Chemical Code Number:

Toluene (CAS 108-88-3)

6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical

Acetone (CAS 67-64-1)

35 % WV

Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3)

35 % WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

6532

Toluene (CAS 108-88-3)

594

US State Regulations

US. Massachusetts RTK - Substance List

US. New Jersey Worker and Community Right-to-Know Act

US. Pennsylvania Worker and Community Right-to-Know Law

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Acetone (CAS 67-64-1)

Acetone (CAS 67-64-1)

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Butane (CAS 106-97-8)

Butane (CAS 106-97-8)

Butane (CAS 106-97-8)

Ethyl Alcohol (CAS 64-17-5)

Ethyl Alcohol (CAS 64-17-5)

Ethyl Alcohol (CAS 64-17-5)

Propane (CAS 74-98-6)

Magnesium Silicate (CAS 14807-96-6)

Magnesium Silicate (CAS 14807-96-6)

Magnesium Silicate (CAS 14807-96-6)

Toluene (CAS 108-88-3)

Propane (CAS 74-98-6)

Propane (CAS 74-98-6)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Titanium dioxide (CAS 13463-67-7)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Toluene (CAS 108-88-3)

Toluene (CAS 108-88-3)

US. California Proposition 65 Warning: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substances

Benzene (CAS 71-43-2)

Listed: February 28, 1987

Toluene (CAS 108-88-3)

Listed: September 2, 2011

Benzene (CAS 71-43-2)

Listed: December 26, 1997

Toluene (CAS 108-88-3)

Listed: January 1, 1991

Toluene (CAS 108-88-3)

Listed: August 7, 2009

Benzene (CAS 71-43-2)

Listed: December 26, 1997

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	-	2	4= Severe
FLAMMABILITY	-	1	3= Serious
REACTIVITY	-	-	2= Moderate
OTHER/PROTECTION	-	-	1= Slight
			0= Minimal

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.