C PATCH SELF LEVELING



Concrete and Masonry Filler & Sealer



C PATCH SELF LEVELING is a moisture cure concrete and masonry sealant designed for application to dry or damp horizontal cracks and chips around driveways, sidewalks, plaza decks, balconies, stairwells, parking structures, roof decks and surrounding pools & fountains. This unique product fills and adheres to concrete, masonry, wood, stone asphalt and metallic surfaces. C PATCH SELF LEVELING self-levels to a smooth, beautiful finish that is durable, and paintable within 24 hours. C PATCH SELF LEVELING 100% solids and will not shrink. This product cures rapidly to a solid rubber seal that can accommodate 25% joint movement. Product will not bubble when applied to damp concrete. Meets USDA requirements for Non-food contact applications.

DIRECTIONS: Clean surface and remove any finishes, dirt, oil, wax, oxidation, loose paint or debris from working surfaces. Pre-clean surface with **MEGA POWER** or similar water based cleaner followed by a water rinse or Isopropyl Alcohol. Do not use petroleum solvents to clean prior to application. For best results apply at temperatures above 35°F (2°C). Product can be tooled for 15 minutes after application. **Note:** For application at temperatures below 35°F, surface must be dry and free of any frost or ice as this will prevent bonding to substrate. Allow substantial additional cure time and test product hardness before subjecting cured material to any type of traffic. APPLICATION TIP: **C PATCH SELF LEVELING** will flow into and through cracks and crevices. Use **C PATCH** standard to create barriers to stop the flow of the Self Leveling product if you need to fill only a section or specific area.

Health	1
Flammability	0
Physical Hazard	0
Protection	-

Areas of Use:

*Hotels

*Schools

*Cities & Counties

*Restaurants

*Stadiums

*Casinos

*Amusement Parks

 Specific Gravity
 1.08

 VOC%
 15.21 g/l

 Net Contents
 10 oz.

Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134