

Section 1 ~ Identification

Identity (As Used On Label and List)

A1074C **C&G CLEAR**

Date Prepared:

01/23/2019

Company Information:

OMEGA INDUSTRIAL SUPPLY, INC

Emergency Telephone Number:

1-800-424-9300

Address (Number, Street, Suite/Apt#)

101 Grobric Ct #1

Telephone Number for Information:

1-800-571-7347

(City, State, and Zip Code)

Fairfield, CA 94534

Signature of Prepare (Optional)

REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Classifications

Eye Irritation - Category 2A
Gases Under Pressure Liquefied Gas
Skin Irritation - Category 2

Pictograms



Signal Word: Warning

Hazard Statements - Physical

H280 - Contains gas under pressure; may explode if heated

Hazard Statements - Health

H319 - Causes serious eye irritation

H315 - Causes skin irritation

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

Precautionary Statements - Storage

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

Precautionary Statements - Disposal

No precautionary statement available.

Section 3 ~ Composition/Information on Ingredients

Components (Specific Chemical Identity, Common Name(s))	CAS No.	%(Wt.)
Methyl Siloxane Linear/Cyclic	70131-67-8	52% - 82%
Silica, Amorphous	7631-86-9	5% - 12%
Mineral Seal Oil	64742-46-7	1% - 4%
Methylthiacetoxysilane	4253-34-3	1% - 4%
Ethylthiacetoxysilane	17689-77-9	1% - 4%
Difluoroethane	75-37-6	1% - 2%

Section 4 ~ First Aid Measures

Inhalation: No ill effects expected. If exposed/feel unwell/concerned: Get medical attention.

Eye Contact: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

Skin Contact: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

Ingestion: Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Use extinguishing media suitable for surrounding fire.

Unsuitable Extinguishing Media: None known.

Specific Hazards in Case of Fire: Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce silicon oxides; carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

Fire-Fighting Procedures: Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

Special Protective Actions: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

Section 6 ~ Accidental Release Measures

Emergency Procedure: Ventilate the area. Wear appropriate protective clothing and equipment.

Recommended Equipment: Wear appropriate protective equipment (see Section 8). Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

Personal Precautions: Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

Section 7 ~ Handling and Storage

General: Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers. Do not puncture or incinerate (burn) cans. Do not spray in eyes. Do not take internally.

Ventilation Requirements: Use in a well-ventilated place.

Storage Room Requirements: Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F.

Section 8 ~ Exposure Controls/Personal Protection

Eye Protection: Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

Skin Protection: Use solvent-resistant protective gloves for prolonged or repeated contact.

Respiratory Protection: In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls: Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables Z1, 2, 3	OSHA Carcinogen	OSHA Skin Designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
Difluoroethane		2.5			1							
Mineral Sea Oil	500	2000			1							
Silica, Amorphous	20 (b)	80 mg/m3 Percent SiO2+2			1, 3				6			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
Difluoroethane		2.5		
Mineral Sea Oil				
Silica, Amorphous				

Section 9 ~ Physical Chemical Properties

Physical and Chemical Properties

Density: 1.81942 lb/gal

Density VOC: 0.25160 lb/gal

% VOC: 3.07800%

Appearance: Thick liquid under pressure (Viscous paste)

Odor Threshold: N.A.

Odor Description: Acetic Acid Odor

pH: N.A.

Water Solubility: N.A.

Flammability: Flash point at or above 200°F/93°C

Flash Point Symbol: >100 °C(>212°F) Closed Cup (Liquid component)

Flash Point: N.A.

Viscosity: N.A.

Lower Explosion Level: N.A.

Upper Explosion Level: N.A.

Vapor Density: N.A.

Melting Point: N.A.

Freezing Point: N.A.

Low Boiling Point: N.A.

High Boiling Point: N.A.

Decomposition Pt: N.A.

Auto Ignition Temp: N.A.

Evaporation Rate: N.A.

Section 10 ~ Stability and Reactivity

Stability: The product is stable under normal storage conditions.

Conditions to Avoid: Keep away from heat, sparks, extreme temperature, flame, other sources of ignition and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizing agents.

Hazardous Reactions/Polymerization: None known.

Hazardous Decomposition Products: Burning may produce silicon oxides; carbon oxides.

Section 11 ~ Toxicological Information

Skin Corrosion/Irritation: Causes skin irritation

Classification of the Substance or Mixture: There is no toxicological data available for this product.

Serious Eye Damage/Irritation: Causes serious eye irritation

Carcinogenicity: No data available

Germ Cell Mutagenicity: No data available

Reproductive Toxicity: No data available

Respiratory/Skin Sensitization: No data available

Specific Target Organ Toxicity - Single Exposure: No data available

Specific Target Organ Toxicity - Repeated Exposure: No data available

Aspiration Hazard: No data available

Acute Toxicity: No data available

Section 12 ~ Ecological Information

Toxicity: No data available.

Classification of the Substance or Mixture: There is no ecological data available for this product.

Persistence and Degradability: No data available.

Bio-Accumulative Potential: No data available.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

Section 13 ~ Disposal Considerations

Water Disposal instructions: Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 ~ Transport Information

U.S. DOT Information

UN Number: UN1950

Proper Shipping Name: Aerosols, non-flammable

Hazard Class: 2.2

Packaging Group: No Data Available

Hazardous Substance (RQ): No Data Available

Toxic-Inhalation Hazard: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)

IMDG Information

UN Number: UN1950

Proper Shipping Name: Aerosols, non-flammable

Hazard Class: 2.2

Packaging Group: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)

IATA Information

UN Number: UN1950

Hazard Class: 2.2

Packaging Group: No Data Available

Proper Shipping Name: Aerosols, non-flammable

Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)

Section 15 ~ Regulatory Information

CAS	Chemical Name	% By Weight	Regulation List
70131-67-8	Methyl Siloxane Linear/Cyclic	52% - 92%	SARA312, TSCA
7631-86-9	Silica, Amorphous	5% - 12%	SARA312, TSCA, OSHA
64742-46-7	Mineral Seal Oil	1% - 4%	SARA312, TSCA, OSHA
4253-34-3	Methyltriacetoxysilane	1% - 4%	SARA312, TSCA
17689-77-9	Ethyltriacetoxysilane	1% - 4%	SARA312, TSCA
75-37-6	Difluoroethane	1% - 2%	SARA312, VOC_exempt, TSCA, ACGIH, OSHA

Section 16 ~ Other Information

Glossary: * There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS. ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESLEffects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94- 469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	1	1	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	B	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.