

# Face Lift



## for Asphalt & Concrete



Permanent marking paints that remain on streets and sidewalks can be a nuisance **FACE LIFT FOR CONCRETE** and **FACE LIFT FOR ASPHALT** will cover those marks, helping you avoid the time and expense of using paint stripper. The **FACE LIFT FOR CONCRETE** coating has similar texture and color to most sidewalks. **FACE LIFT FOR ASPHALT** black coating is asphalt based - identical to standard driveway sealers. Both are quick dry, highly durable. Yields approximately 250 linear feet per can (4" wide stripe). The paint is traffic ready in 60 minutes. The universal spray head also works in competitive marking machines. For marking curbs or walls, it can be actuated by hand or with a marking machine.

**Directions:** 1.) For best results, use when can is between 50°F and 90°F 2.) Shake can at least one minute after rattle is heard and occasionally during use. 3.) Turn can upside down and place into holder of the Marking Machine. **MAKE SURE THAT SPRAY HEAD FITS PROPERLY INTO HOLE.** The long side of the spray head must be parallel to the axle. By adjusting the can platform up or down, stripes approximately 3 to 5 inches wide can be applied. 4.) Squeeze trigger to activate spray. To avoid any possible "build-up" of paint when starting, it is suggested that the machine be in motion when passing over the starting point. 5.) If clogging develops, take the can out of the marking

machine. Remove spray head from can and clean orifice in spray head. With can and spray head pointed away from you, reinsert spray head with a gentle twisting motion. 6.) To clear spray head for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. **DO NOT** incinerate or compact.

### Asphalt

Health	1
Flammability	3
Physical Hazard	3
Protection	B

### Areas of Use:

#### Concrete

Health	1
Flammability	3
Physical Hazard	3
Protection	B

\*Sidewalks      \*Driveways      \* Warehouse floors      \*Cinder block walls

Appearance and odor.....	Aerosol, aromatic odor.
Specific Gravity.....	N/D
VOC.....	Concrete: 53.6% Asphalt: 65.4%
Net Wt.....	17 oz.

## Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347    www.onlyomega.com    Fax: 707-864-8134