This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification		
Identity (As Used On Label and List) B4037 Grease It All Lube	Date Prepared: 04-06-2015	
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300	
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347	
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.	

Section 2 ~ Hazard(s) Identification

Classifications This product is not considered hazardous by OSHA Hazard Communication Standard 29 CFR 1910.1200

Label Elements Hazardous Pictogram



Signal Word: Warning

Hazard Statement May be harmful in contact with skin. May cause eye irritation.

Precautionary Statement

General Prevention and Personal

Keep out of reach of children. Read label before use.

Prevention and Personal
Protection Equipment

Always wear eye or face protection. Protect exposed skin from prolonged use

Hazardous Response Eyes: Rinse eyes continually for several minutes. Skin: Wash affected skin with soap and water.

Storage Not applicable.

Disposal Always return waste to appropriate collection center. Dispose of empty containers in accordance with all national, state and local regulations.

Section 3 ~ Composition/Information on Ingredients

Mixtures: This product contains no substances which at their given concentrations are to be considered hazardous to health and safety.

Additional Information: This product is a Lithium Complex Grease blended with a mixture of mineral oil with additives. The formulation is considered a trade secret and specific chemical names and/or percentages of the components have not been disclosed.

Section 4 ~ First Aid Measures

General Information: Not expected to contain or cause any specific health or safety hazards when used in accordance with label.

INGESTION: Seek medical attention if discomfort occurs. Do not induce vomiting.

SKIN: Remove with soap and water. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.

EYE: Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. Seek medical attention if symptoms persist or if unconscious.

NOTES TO PHYSICIAN: No Data

Section 5 ~ Fire Fighting Measures

Conditions Of Flammability: Heat, sparks, flame, red hot metal

Suitable Means Of Extinction: Water, CO2, dry chemical, or universal aqueous film forming foam.

Unsuitable Extinguishing Media: Not available

Flash Point And Method Of Determination: 455 F ASTM D92 (Cleveland Open cup)

Flammable Limits: Lower (LEL): No data Upper (UEL): No data

Auto Ignition Temperature: Not Available

Hazardous Combustion Products: Oxides of Carbon (CO, CO2), smoke, and vapors as products of incomplete combustion.

Explosion Data-Sensitivity To Mechanical Impact: Not available

Explosion Data-Sensitivity To Static Discharge: Not available

Special Fire Fighting Procedures: Use water spray to cool fire exposed containers as contents can rupture violently from heat developed pressure. Firemen should wear self-contained breathing apparatus.

Special Fire And Explosion Hazards: Not available

Section 6 ~ Accidental Release Measures

Notification Procedures: Report spills/releases as required to appropriate authorities. Some regulations require immediate reporting of spills/releases that could reach any waterway including intermittent dry creeks.

Procedures if Material is Released or Spilled: For Land Spills shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping or contain spilled material with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of absorbed residues as directed in Section 13. For Water Spills confine the spill immediately with booms. Notify port and/or other relevant authorities. Remove from the surface by skimming or with suitable absorbents.

Environmental Precautions: Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil or vegetation.

Section 7 ~ Handling and Storage

Handling: No special precautions are necessary beyond normal good hygiene practices. See Section 8 for additional personal protection.

Storage: Keep contains closed when not in use. Do not store in open or unlabeled containers. Store away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, or flame.

Empty Container Warning: Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. Empty drums should be completely drained, properly bunged, and promptly returned to drum re-conditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Section 8 ~ Exposure Controls/Personal Protection

Exposure Limit Values: When mists/aerosols can occur, the following are recommended: 5 mg/m3 (as oil mist) - ACGIH Treshold Limit Value (TLV), 10 mg/m3 (as oil mist) - OSHA

Permissible Exposure Limit (PEL).

Lithium Hydroxide Mono Hydrate AIHA WEEL Ceiling 1.8 mg/m3 Mineral Oil ACGIH TWA- Vacated and TWA 5.0 mg/m3 Zinc Alkyl Dithiphosphate ACGIH TWA 5.0 mg/m3

Engineering And Exposure Controls: General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation, or an enclosed handling system may be necessary to control air contamination below that of the lowest PEL rated ingredient from Section 2.



Personal Protective Equipment Pictograms:

Respiratory Protection: When mists are generated, and/or when ventilation is not adequate, wear a NIOSH approved respirator with an appropriate cartridge. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary within the United States.

Skin And Hand Protection: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

Eye Protection: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

Other Protective Equipment: Safety showers and eye-wash stations should be available in the workplace

Hygiene Measures: Avoid breathing vapors and contact with the skin and eyes. Keep out the reach of children. Wash hands after use.

Section 9 ~ Physical Chemical Properties

Flash Point (COC): >455F Melting/Freezing Point: Not available Specific Gravity (H²O=1): 0.870g/cc Weight: 7.8 lbs/gal Vapor Pressure: <1 mm Hg

pH: Not available Vapor Density: Not available

Evaporation Rate: Not available Physical State: Paste

Water Solubility: Insolubl

Percent Volatile: 0% Wt (0% Vol) max VOC Content: 0.0 lbs/gal (0.0 g/L) Percent VOC: 0% Wt (0% vol) Max HAP Content: 0.0 lbs/gal (0.0 g/L) Viscosity: >220 SSU

MIR Value: 0.0 Odor Threshold: Not available Coeff. Of Water/Oil Dist: Not available Appearance: Red or Blue Semi-solid Odor: Slight Petroleum

Section 10 ~ Stability and Reactivity

Stability: Stable

Conditions Of Instability: Not available Hazard Polymerization: Not expected to occur Material Incompatibility: Strong oxidizers

Conditions Of Reactivity: Extreme heat and high energy sources of ignition Decomposition Products: At elevated temperatures oxides of carbon can be produced.

Section 11 ~ Toxicological Information

Carcinogenicity: The petroleum base oil contained in this product has been highly refined by a variety processes including hydro treating and dewaxing to remove aromatics and improve performance characteristics. None of these oils used are listed as a carcinogen by NTP, IARC or OSHA.

Section 12 ~ Ecological Information

 Ecotoxicity

 INGREDIENT
 FISH LC50
 DAPHNIA EC50
 ALGEAL IC50
 BACTERIAL EC50

 Base Oil
 >10 g/l/96 hr
 Not available
 Not available
 Not available

 Mobility: When released into the environment, absorption to sediment and soil will be the predominant behavior.

Persistence: Not available

Degradability: This product is expected to be inherently biodegradable. **Bioaccumulation:** Unlikely due to the very low water solubility of the product. **Other Ecologic Data:** Do not allow to enter waters, waste water, or soil.

Effect On Ozone Layer: This product does not contain any ozone depleting ingredients.

Section 13 ~ Disposal Considerations

Waste Management Information: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and Regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Section 14 ~ Transport Information

NON-REGULATED MATERIAL: All Modes NMFC DESCRIPTION (United States) Item Description: Compounds, Lubricating Item Number: LC222, 221,220

Class: 55-65

Section 15 ~ Regulatory Information

UNITED STATES-FEDERAL Ingredient CAS# **RCRA** CERCLA SARA 313 SARA 311/312 **TSCA United States-States:** Ingredient CA DE FL. MA PA MN NI NY WA Canada: В D1B D2A D2B E DSL NDSL. **NPRI** CWC Ingredient WHMIS Classification: Not regulated

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

This product has been classified in ac **European Union:**

Ingredient EINECS SYMBOL RISK PHRASES SAFETY PHRASES

SARA (313) Toxic Release Inventory: This material may contain chemical(s) regulated under SARA. For specific question contact customer service.

RoHS Compliance: This product is RoHS compliant according to the definitions and restrictions given by The European Parliament (Directive 2002/95/EC) and The Council of January 27, 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	1	0	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	0	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. This SDS provides the information contained herein in good faith but makes no representation as though its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of this product by properly trained persons using this product. Individuals receiving this information must exercise their judgment in determining its appropriateness for a particular purpose. This SDS make no representation or warranties either expressed or implied including without limitations and warranties of merchantability, fitness for particular purpose without respect to the information set forth herein or the product to which the information refers accordingly. This SDS does n+ot remit responsibility for damages resulting from use of or reliance upon this information.