

Jell Strip

Paint & Varnish Remover



JELL STRIP is a gel formulation paint remover that quickly removes paint, epoxy paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. **JELL STRIP** has been authorized by the USDA for use in federally inspected meat and poultry plants.

Directions: SHAKE WELL BEFORE USING. Holding can 8 to 10 inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow **JELL STRIP** to complete blistering before removing.

Health	3
Flammability	2
Reactivity	0
Protection	B

Areas of Use:

- *Heavy duty graffiti removal
- *Decal removal
- *Adhesive removal
- *Wood and metal refinishing
- *Departments of transportation
- *Municipalities
- *Sign shops
- *Vehicle maintenance shops
- *Plumbing departments

Appearance and odor.....	Viscous, hazy spray with chlorinated solvent odor.
Specific Gravity.....	1.185
VOC.....	33%

Omega Industrial Supply, Inc.

Fairfield, CA 94534
1-800-571-7347 www.onlyomega.com Fax: 707-864-8134