Liquid Auger



Drain Opener with Bi-Phase Action



LIQUID AUGER is a fast working, industrial bi-phase drain opener that works without harming pipes or fixtures. It features an inhibited virgin acid that is safer to handle than conventional acidic drain openers, combined with a grease eliminator that also acts as an odor masking agent. LIQUID AUGER will unclog even the toughest blockages saving you the excessive cost of having a plumber come out to your property. If you are a plumber, this product will be your first choice to use! The handy single use pint containers are designed for added safety and convenience. LIQUID AUGER is safe on all types of plumbing including copper, PVC, galvanized, zinc, and brass.

DIRECTIONS EXACTLY. DO NOT use drain opener in or on aluminum, chrome, stainless steel, berglass, lead pipes or non-acid-resistant enamel. Clean spills or drips immediately. Always close connecting drains when using drain opener. Avoid backups. Do not use plunger. Place a bucket or other large, deep container under drain before use. This product is inhibited against attacking most metals. Old piping systems may be porous and have defects that are sealed with accumulated organic matter. This product may expose these defects by attacking organic matter, as intended, and cause leaks. REMOVE standing water and temper fixture with hot water before applying drain opener. Incorrect use may

crack toilet. After tempering, slowly pour small quantity directly into drain opening. Do not inhale fumes. If no "bubbling" occurs, add balance of dosage. **USAGE AMOUNTS:** • Small drains, traps, waste lines, toilets and urinals:... 1/2 pint. • 3 to 4 inch lines:... 1 quart. • 6 to 8 inch lines: ... 1/2 gallon (allow additional standing time). After 15 minutes standing time, slowly add 1 quart of cold water into drain opening and wait another 5 minutes. If line is clear, flush throughly with more cold water. Do not allow water to splash. Recommended dosage will open most lines, but if blockage persists, repeat dosage. Use as directed, drain opener will not harm drainage systems.

Health	3
Flammability	0
Reactivity	2
Protection	-

Areas of Use:

*Cities and Counties

*Apartment complexes

*Housing authorities

*Building maintenance

*Plumbers

Appearance and odor	Liquid, colorless, dark pink with acidic almost odorle	ess sulfur.
Specific Gravity	N/A	
VOC	N/A	
Net Wt	Pint	

Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134