

# Metal Protect



## Metal Parts Protector (Non-Chlorinated)



**METAL PROTECT** is a long-term, flexible, non-tacky, dust resistant coating that will not crack, peel, flake or chip over a wide temperature range (-40°F to +175°F). Adheres to most clean metal surfaces. **METAL PROTECT** is easily applied and removed, can be used as a corrosion preventative, it has a flexible dust retardant coating and has a thru film which allows parts to be identified.

**Directions:** Make sure surface is clean and dry. Spray a thin uniform film. Allow approximately 5 minutes to set up. For more severe storage conditions, a second coating can be applied within a few minutes. Complete setting of protective coating takes approximately two hours after spraying.

### Areas of Use:

- \*Milled parts
- \*Parts in transit
- \*Parts in storage
- \*Maintenance crews
- \*Universities
- \*Schools
- \*Large molds
- \*Seasonal equipment

|              |   |
|--------------|---|
| Health       | 1 |
| Flammability | 3 |
| Reactivity   | 0 |
| Protection   | B |

|                          |                                 |
|--------------------------|---------------------------------|
| Appearance and odor..... | Dark brown liquid, Solvent odor |
| Specific Gravity.....    | 0.848                           |
| VOC.....                 | 76.33%                          |
| NFPA Fire Rating.....    | Extremely Flammable Spray       |

***Omega Industrial Supply, Inc.***

Fairfield, CA 94534  
1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134