


Section 1 ~ Identification

Identity (As Used On Label and List) A1056 NO SWEAT	Date Prepared: 07-07-2015
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards	Flammable aerosols	Category 1	
Health Hazards	Acute toxicity, dermal	Category 4	Skin corrosion/irritation Category 2
	Serious eye damage/eye irritation	Category 2A	Germ cell mutagenicity Category 2
	Carcinogenicity	Category 1	Reproductive toxicity (the unborn child) Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	Specific target organ toxicity, repeated exposure Category 2
Environmental Hazards	Not classified		OSHA Defined Hazards Not classified
Label Elements			Signal Word: Danger
Hazard Statement	Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing genetic defects. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.		
Precautionary Statement Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) Not Otherwise Classified HNOC	None Known	Supplemental Information	None

Section 3 ~ Composition/Information on Ingredients

Components (Specific Chemical Identity, Common Name(s))	CAS No.	%(Wt.)
Trichloroethylene	79-01-6	40 – 60
Butane	106-97-8	20 – 40
Propane	74-98-6	10 – 20
Magnesium Silicate	14807-96-6	1 – 2.5
Palmitic Acid	57-10-3	1 – 2.5
Titanium dioxide	13463-67-7	1 – 2.5
Toluene	108-88-3	1 – 2.5
1,2-Butylene Oxide	106-88-7	0.1 – 1
Other components below reportable levels		2.5 – 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin: Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most Important Symptoms/Effects, Acute And Delayed: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication Of Immediate Medical Attention And Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising From The Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special Protective Equipment And Precautions For Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment And Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods And Materials For Containment And Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. **Small Spills:** Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions For Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions For Safe Storage, Including Any Incompatibilities: Level 1 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)				US. ACGIH Threshold Limit Values			
Components	Type	Value	Form	Components	Type	Value	Form
Propane (CAS 74-98-6)	PEL	1800 mg/m ³		Butane (CAS 106-97-8)	STEL	1000 ppm	
		1000 ppm		Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust	Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	
				Toluene (CAS 108-88-3)	TWA	20 ppm	
US. OSHA Table Z-2 (29 CFR 1910.1000) Components				US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Type	Value	Form	Components	Type	Value	Form
Toluene (CAS 108-88-3)	Ceiling	300 ppm		Butane (CAS 106-97-8)	TWA	1900 mg/m ³	
	TWA	200 ppm				800 ppm	
Trichloroethylene (CAS 79-01-6)	Ceiling	200 ppm		Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable
	TWA	100 ppm		Propane (CAS 74-98-6)	TWA	1800 mg/m ³	
US. OSHA Table Z-3 (29 CFR 1910.1000)							
Components	Type	Value	Form	Components	Type	Value	Form
Magnesium Silicate (CAS 14807-96-6)	TWA	0.3 mg/m ³	Total dust	Toluene (CAS 108-88-3)	STEL	560 mg/m ³	
		0.1 mg/m ³	Respirable			150 ppm	
		20 mppcf				375 mg/m ³	
		2.4 mppcf	Respirable			100 ppm	
US. Workplace Environmental Exposure Level (WEEL) Guides							
Components	Type	Value		Components	Type	Value	
1,2-Butylene Oxide (CAS 106-88-7)	TWA	5.9 mg/m ³		Trichloroethylene (CAS 79-01-6)	TWA	25 ppm	
		2 ppm					

Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Trichloroethylene (CAS 79-01-6)	15 mg/l	Trichloroacetic acid	Urine	*
	0.5 mg/l	Trichloroethanol, without hydrolysis	Blood	*

*- For sampling details, please see the source document

Exposure Guidelines

US - California OELs: Skin Designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin

US - Minnesota Haz Subs: Skin Designation Applies

Toluene (CAS 108-88-3)

Skin designation applies

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Respiratory Protection: Chemical respirator with organic vapor cartridge and full face piece.

Skin Protection Other: Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Hand Protection: Wear appropriate chemical resistant gloves.

Eye/Face Protection: Chemical respirator with organic vapor cartridge and full face piece.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical Chemical Properties

Appearance: Liquid.

Physical State: Liquid.

Form: Aerosol

Color: White

Odor: Solvent

Odor Threshold: Not Available

Ph: Not available

Melting Point/Freezing Point: Not available

Initial Boiling Point And Boiling Range: 194°F (90°C) estimated

Flash Point: -156.0°F (-104.4°C) Propellant estimated

Evaporation Rate: Not available

Flammability (solid, gas): Not Available

Upper/Lower Flammability Or Explosive Limits

Flammability Limit - Lower (%): 8% estimated

Flammability Limit - Upper (%): 52% estimated

Explosive Limit - Lower (%): Not available

Explosive Limit - Upper (%): Not available

Vapor Pressure: 55 psig @70F estimated

Vapor Density: Not available

Relative Density: 1.137 g/cm³ estimated

Solubility(ies)

Solubility (water): Not available

Partition Coefficient (n-octanol/water): Not available

Auto-Ignition Temperature: 788°F (420°C) estimated

Decomposition Temperature: Not available

Viscosity: Not available

Other Information

Density: 1.14 g/cm³ estimated

Flammability Class: Flammable 1B estimated

Heat Of Combustion: 18.76 kJ/g estimated

Heat Of Combustion (NFPA 30B): 17.78 kJ/g estimated

Percent Volatile: 88.1 % estimated

Specific Gravity: 1.136 estimated

VOC (Weight 0/0): 87.82 % estimated

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous Polymerization does not occur.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatibility Materials: Strong oxidizing agents, nitrates, fluorine, chlorine.

Hazardous Decomposition or Byproducts - No hazardous decomposition products are known.

Section 11 ~ Toxicological Information**Information On Likely Routes Of Exposure****Ingestion:** Expected to be a low ingestion hazard.**Inhalation:** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache, nausea, vomiting, narcotic effects,. Prolonged inhalation may be harmful.**Skin Contact:** Causes skin irritation.**Eye Contact:** Causes serious eye irritation.**Symptoms Related To The Physical, Chemical And Toxicological Characteristics:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.**Information On Toxicological Effects****Acute Toxicity:** Narcotic effects

<u>Product</u>	<u>Species</u>	<u>Test Results</u>	<u>Product</u>	<u>Species</u>	<u>Test Results</u>
Butane (CAS 106-97-8) Acute			Titanium dioxide (CAS 13463-67-7) Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes	Inhalation LC50	Rat	> 2.28 mg/l, 4 hours
	Rat	52%, 120 Minutes	Oral LD50	Rat	> 11000 mg/kg
		1355 mg/l			
Palmitic Acid (CAS 57-10-3) Acute			Toluene (CAS 108-88-3) Acute		
Dermal LD50	Rabbit	> 2000 mg/kg, 24 hours	Dermal LD50	Rabbit	> 5000 mg/kg, 24 hours
Inhalation LC50	Rat	> 0.1621 mg/l, 4 hours	Inhalation LC50	Mouse	6405 – 7436 ppm, 6 hours
				Rat	5320 ppm, 8 hours
					5879 – 6281 ppm, 6 hours
Propane (CAS 74-98-6) Acute			Oral LD50	Rat	12.5 – 28.8 mg/l, 4 hours
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes			5000 mg/kg
	Rat	52%, 120 Minutes	Trichloroethylene (CAS 79-01-6) Acute		
		1355 mg/l	Dermal LD50	Rat	19031 mg/kg
		658 mg/l/4h	Inhalation LC50	Rat	12500 ppm, 4 hours
					1044 mg/l/4 hours

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Causes skin irritation**Serious Eye Damage/Eye Irritation:** Causes serious eye irritation**Respiratory Sensitization:** Not available**IARC Monographs. Overall Evaluation of Carcinogenicity****1,2-Butylene Oxide (CAS 106-88-7)** 2B Possibly carcinogenic to humans.**Magnesium Silicate (CAS 14807-96-6)** 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Skin Sensitization: This product is not expected to cause skin sensitization**Germ Cell Mutagenicity:** Suspected of causing genetic defects**Carcinogenicity:** May cause cancer**Titanium dioxide (CAS 13463-67-7)** 2B Possibly carcinogenic to humans.**Toluene (CAS 108-88-3)** 3 Not classifiable as to carcinogenicity to humans.**Trichloroethylene (CAS 79-01-6)** If <1L: Consumer Commodity Carcinogenic to humans.**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed**US. National Toxicology Program (NTP) Report Carcinogens:** Trichloroethylene (79-01-6) Reasonably Anticipated to be a Human Carcinogen.**Reproductive Toxicity:** Suspected of damaging the unborn child**Specific Target Organ Toxicity - Single Exposure:** May cause drowsiness and dizziness.**Specific Target Organ Toxicity - Repeated Exposure:** May cause damage to organs through prolonged or repeated exposure.**Aspiration Hazard:** Not available**Chronic Effects:** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.**Section 12 ~ Ecological Information****Ecotoxicity:** Harmful to aquatic life with long lasting effects.

<u>Product</u>	<u>Species</u>	<u>Test Results</u>	<u>Product</u>	<u>Species</u>	<u>Test Results</u>
No Sweat (CAS Mixture) Aquatic			Toluene (CAS 108-88-3) Aquatic		
Algae IC50	Algae	27295.2051 mg/L, 72 Hours estimated	Algae IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea EC50	Daphnia	4,6954 mg/L, 48 Hours estimated	Crustacea EC50	Daphnia	7.645 mg/L, 48 Hours
Fish LC50	Fish	111.2775 ppm, 96 hours estimated		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
				Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
1,2-Butylene Oxide (CAS 106-88-7) Aquatic					
Algae IC50	Algae	500 mg/L, 72 Hours			
Crustacea EC50	Daphnia	69.8 mg/L, 48 Hours			
Fish LC50	Fish	160, 96 Hours			
			Trichloroethylene (CAS 79-01-6) Aquatic		
Titanium dioxide (CAS 13463-67-7) Aquatic			Crustacea EC50	Daphnia	2.2 mg/L, 48 Hours
Crustacea EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours	Fish LC50	Fish	40.8933, 96 Hours
	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours		Flagfish (Jordanella floridae)	3.1 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence And Degradability: No data is available on the degradability of this product.**Bioaccumulative Potential:** No data available**Partition Coefficient n-octanol / Water (log Kow)**

Butane	2.89	Toluene	2.73
Palmitic Acid	7.17	Trichloroethylene	2.61
Propane	2.36		

Mobility In Soil: No data available**Other Adverse Effects:** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.**Section 13 ~ Disposal Considerations****Disposal Instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.**Local Disposal Regulations:** Dispose in accordance with all applicable regulations.**Hazardous Waste Code:** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.**US RCRA (Resource Conservation and Recovery Act) Hazardous Waste U List: Reference:** Toluene (CAS 108-88-3) U220, Trichloroethylene (CAS 79-01-6) U228**Waste from Residues / Unused Products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Section 14 ~ Transport Information

DOT	IATA	IMDG
UN Number: UN1950	UN Number: UN1950	UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)	UN Proper Shipping Name: Aerosols, flammable	UN Proper Shipping Name: AEROSOLS
Transport Hazard Class(es)	Transport Hazard Class(es)	Transport Hazard Class(es)
Class: 2.1	Class: 2.1	Class: 2.1
Subsidiary Risk: -	Subsidiary Risk: -	Subsidiary Risk: -
Label(s): 2.1	Label(s): 2.1	Label(s): 2.1
Packing Group: Not applicable	Packing Group: Not applicable	Packing Group: Not applicable
Special Provisions: N82	Environmental Hazards: No.	Environmental Hazards
Packaging Exceptions: 306	ERG Code: 10L	Marine Pollutant: No.
Packaging Non Bulk: None	Other Information	EmS: F-D, S-U
Packaging Bulk: None	Passenger And Cargo Aircraft: Allowed	Packaging Exceptions: LTD QTY
	Cargo Aircraft Only: Allowed	Transport in bulk according to Annex 11 of MARPOL 73/78 and the IBC Code: Not applicable
	Packaging Exceptions: LTD QTY	

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

DOT

IATA;IMDG

**Section 15 ~ Regulatory Information**

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) — Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4) — 1,2-Butylene Oxide (CAS 106-88-7) Listed. Toluene (CAS 108-88-3) Listed. Trichloroethylene (CAS 79-01-6) Listed.

SARA 304 Emergency release notification — Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) — Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories: *Immediate Hazard:* Yes *Delayed Hazard:* Yes *Fire Hazard:* Yes *Pressure Hazard:* No *Reactivity Hazard:* No

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Trichloroethylene	79-01-6	40 – 60
Toluene	108-88-3	1 – 2.5
1,2-Butylene Oxide	106-88-7	0.1 - 1

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List — 1,2-Butylene Oxide (CAS 106-88-7), Toluene (CAS 108-88-3), Trichloroethylene (CAS 79-01-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) — Butane (CAS 106-97-8), Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) — Not regulated.

Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number — Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) — Toluene (CAS 108-88-3) 35 % WV

DEA Exempt Chemical Mixtures Code Number — Toluene (CAS 108-88-3) 594

US State Regulations

US. Massachusetts RTK - Substance List	US. New Jersey Worker and Community Right-to-Know Act	US. Pennsylvania Worker and Community Right-to-Know Law	US. Rhode Island RTK
1,2-Butylene Oxide (106-88-7)	1,2-Butylene Oxide (106-88-7)	1,2-Butylene Oxide (106-88-7)	1,2-Butylene Oxide (106-88-7)
Butane (106-97-8)	Butane (106-97-8)	Butane (106-97-8)	Butane (106-97-8)
Magnesium Silicate (14807-96-6)	Magnesium Silicate (14807-96-6)	Magnesium Silicate (14807-96-6)	Propane (74-98-6)
Propane (74-98-6)	Propane (74-98-6)	Propane (74-98-6)	Toluene (108-88-3)
Titanium dioxide (13463-67-7)	Titanium dioxide (13463-67-7)	Titanium dioxide (13463-67-7)	Trichloroethylene (79-01-6)
Toluene (108-88-3)	Toluene (108-88-3)	Toluene (108-88-3)	
Trichloroethylene (79-01-6)	Trichloroethylene (79-01-6)	Trichloroethylene (79-01-6)	

US. California Proposition 65 WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance:

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011 Trichloroethylene (CAS 79-01-6) Listed: April 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin: Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin: Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	3	3*	4= Severe
FLAMMABILITY	2	2	3= Serious
REACTIVITY	1	0	2= Moderate
OTHER/PROTECTION	-	X	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.