

Omega P.D.S.



Pourable Driveway Sealer



OMEGA P.D.S. is a fast drying, rubberized compound for use on the repair of asphalt roads, driveways, pavements, expansion joints and walkways. Speeds up seal coating jobs with quick drying. Provides a long term flexible repair on cracks and joints up to 3/4" wide. Also seals foundation walls and other pavement surfaces. Dries to dark black finish.

DIRECTIONS: PREPARATION: Surfaces should be cleaned with **MEGA POWER** a cleaner and degreaser and free of any loose materials, grease, oil and dirt, before filling cracks. Rinse area thoroughly with a high pressure hose and allow to dry. **APPLICATION:** Make sure top is secured and shake thoroughly. Unscrew top and flip over spout. Cut tip on a 45° angle to desired opening (for smaller amounts cut closer to top). Pour into crack filling slightly higher to allow for settling, but do not overfill. Allow 1 hour at good drying conditions (ie: above 65°F and under 50% relative humidity) prior to coating with a premium driveway sealer.

Note: Humidity and cool air/surface temperatures may lengthen cure time. Make sure filler has cured before sealing. Do not apply if rain is expected within 24 hours. **DO NOT HEAT.**

Areas of Use:

- *Apartment complexes
- *School districts
- *Cities and Counties
- *Grounds maintenance
- *Amusement parks
- *Facilities maintenance departments
- *Dock areas/shipyards

Health	1
Flammability	0
Physical Hazard	0
Protection	B

Appearance and odor.....	Paste
Specific Gravity.....	N/A
% Volatile.....	26 - 28%

Omega Industrial Supply, Inc.

Fairfield, CA 94534
 1-800-571-7347 www.onlyomega.com Fax: 707-864-8134