P.P.P.



Pan Plug Patch Epoxy Pan Sealant



Health	2
Flammability	1
Physical Hazard	_
Protection	_

P.P.P. is a unique two-part epoxy that creates a permanent bond, it stops leaks or holes in drain pans, has a fast acting formula with long lasting results. It pours through standing water to create a permanent bond. The permanent bond stops leaks to prevent damage adheres to almost any surface, including metal, wood and concrete. P.P.P repairs pan leaks to save replacement cost, takes only minutes to apply. P.P.P. also includes an anti-microbial additive to eliminate future mold growth. P.P.P. has a self-leveling formula that will provide a smooth, even coat.

Directions: 1. Remove large loose particles from pan. 2. Neutralize oils and acids prior to an application. 3. Remove the black clip by holding each end of bag and pulling firmly. 4. Mix thoroughly in bag until color is uniform. Do not use excessive pressure or puncture bag during mixing. 5. Slightly elevate one end of drain pan using a screw driver or knife. 6. Cut corner and empty P.P.P. into drain pan at one end. P.P.P. is self-leveling, sets up in standing water and seals leaks caused by rust and corrosion. Unit can be returned to service immediately.

Note: Failure to mix thoroughly could result in poor adhesion to surface.

Areas of Use:

*Apartments

*Hospitals

*Municipalities

*High Rise Buildings

*Hotels

*School Districts

Appearance and odor..... Amber liquid, amine odor. Specific Gravity...... 1.01

Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134