Patch It



Aerosol Rubberized Coating and Roof Patch



OMEGA INDUSTRIAL SUPPLY, INC	OMEGA INDUSTRIAL SUPPLY, IX	OMEGA INDUSTRIAL SUPPLY
PATCH IT WHITE	PATCH IT	PATCH IT
UTRA DURABLE RUBBERIZED LEMERROOF, AND WATERPROOF CONTINUOUS COATING LEMERT OF COATING LEMER OF COATING LEME	ULTRA DURABLE RUBBERIZED MEATHERPROOF, AND WATERPROOF CONTINUOUS COATING MISTANTEY/REPAIRS/GRACKS, TELES, SZULT/SEAMS, THIN SPOUS ROOF GULTERS/AND RUSSHING DOWNSPOUSS AGEN COVERS/UPTO/2050/FI	ULTRA DURABLE RUBBERIZE MATHERPROOF AND WATERPRO CONTINUOUS COATING INSTANTLY/REPAIRS CRACKS TELES, SPUIT SEAMS, THINSFOR ROOF/GUITTERS/AND FUSHINDOWNS/ROUS GAINGOVERS/UPTO/2009-75
NT REIGHT 16 0.2: (454 Gramm) The Second State of Second Sec	INTEREST TO DZ (454 Grams) IN	Parmatine, Liquid & Vigoro may Casin Fasilians. Vigor Harmful, Humble of Polit Elements Vigoro Harmful

PATCH-IT is multi-purpose continuous coating				
instant leak sealer. PATCH IT can be applied to				
any surface to provide a waterproof flexible				
continuous rubber coating that will stop leaks				
and act as a barrier against moisture, rust, and				
corrosion. Once applied, area becomes imper-				
vious to humidity, mold, and fungus. PATCH IT				
is fast drying and will not crack or peel.				
Available in Aluminum, Black and White.				

Directions: Shake can well until ball rattles & then for a further 30 seconds. For best results use & store at room temperature. Remove dust from area before application. Apply to surface from a distance of 10-12 inches. Spray evenly over desired area. Multiple coats can be applied, but allow approximately 20-30 minutes of drying time between coats. Leaks, breaks & large cracks may be repaired by coating around defect and applying a mesh such as a heavy cloth, wire mesh or fiberglass before final coating is applied. Clean actuator tip after use by inverting can and spraying until only gas comes out.

Health	-
Flammability	-
Reactivity	-
Protection	_

Areas of Use:

- *Gutters and downspouts
- *Metal siding
- *Roofs
- *Flashings
- *Municipalities

- *Building maintenance
- *Roofing departments
- *Schools
- *Vehicle undercoating
- *Pipes

Appearance and odor	.Rubberized	coating spray,	various colors.
Specific Gravity	.Liquid: .85 -	.91	
VOC	MIR: <14		

Omega Industrial Supply, Inc.

Fairfield, CA 94534 1-800-571-7347 www.onlyomega.com

Fax: 707-864-8134