## Protect All



Weather Protection for Electrical Connections



Health	N/A
<u> Health</u>	
Flammability	N/A
Reactivity	N/A
Protection	N/A

**PROTECT ALL** can be applied to any surface to provide a waterproof flexible permanent rubber film that will act as a barrier against moisture causing rust & corrosion on electrical connections. Once applied area becomes impervious to humidity, salt and fungus. Dries crystal clear and will not discolor or harm any surface.

Directions: Shake container well before and during use. Due to the amount of rubber, the nozzle may on occasion sputter or momentarily clog, continue to spray, clogging will clear after a few seconds. Peel away any accumulation from nozzle tip. Wires and terminals to be sealed must be clean and dry. Spray PROTECT ALL on electrical connection area. Allow to dry for 15 minutes. Apply second coat if greater thickness is required or needed. NOTE: Not to be sprayed on running Electrical motrs or Live Wires. Disconnect all electrical equipment before using. Allow sufficient time to dry before reconnecting electrical equipment.

## Areas of Use:

- \*Shipyards
- \*Electrical shops
- \*Around electrical boxes
- \*Municipalities
- \*Utilities
- \*Schools

Appearance and odor	Clear coating
Specific Gravity	Liquid: 0.770
Specific GravityVOC	N/A
Net Wt	11 oz.

## Omega Industrial Supply, Inc.

Fairfield, CA 94534

1-800-571-7347 www.onlyomega.com Fax: 707-864-8134