This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification			
Identity (As Used On Label and List)	Date Prepared:		
A1024 Protect It	08-15-2014		
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300		
Address (Number, Street, Suite/Apt#)	Telephone Number for Information:		
101 Grobric Ct #1	1-800-571-7347		
(City, State, and Zip Code)	Signature of Prepare (Optional)		
Fairfield, CA 94534	REGULATORY DEPT.		

Section 2 ~ Hazard(s) Identification

Classification Flammable Aerosol:

Liquefied Gas

Skin Irritant: Category 2 Eye Irritant: Category 2b

Category 1

Reproductive Toxicity: 2

Specific Target Organ Toxicity (Single Exposure): Category 3

Specific Target Organ Toxicity (Repeated Exposure): Category 2

Aspiration Hazard: Category 1

Lahel elements









SYMBOL: **HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

Hazard Statement

DANGER: Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to Central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. This product contains the following percentage of chemicals of unknown toxicity: 18%

Precautionary Statement

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

Section 3 ~ Composition/Information on Ingredients

Hazardous Ingredients (Specific Chemical Identity, Common Name(s))	CAS No.	%(Wt.)
Propane/n-Butane	68476-86-8	10-30%
Hexane	110-54-3	30-60%
Heptane	142-82-5	10-30%
Light Aliphatic Solvent Naphtha	64742-89-8	7-13%

Section 4 ~ First Aid Measures

Eyes — Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Skin-Wash with plenty of water. If skin irritation occurs: get medical attention.

Inhalation — Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

Ingestion — Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

Acute Health Hazards— Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: Anesthetic, irritation, Central Nervous System depression. Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

Chronic Health Hazards - Excessive exposure may result in peripheral neuropathies due to n-hexane. Symptoms would be sensory numbness and possible motor weakness in extremeties.

NOTE TO PHYSICIAN— If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media – Dry chemical, foam, or Carbon Dioxide (CO2).

Unsuitable Extinguishing Media – Water spray/stream

Special Fire Fighting Procedures – Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

Unusual Fire And Explosion Hazards - Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source

Hazardous Combustion Products - Oxides of carbon, various hydrocarbons

Section 6 ~ Accidental Release Measures

Personal Protective Equipment — Refer to section VIII for proper Personal Protective Equipment.

Spill — Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, State and Federal regulations.

Waste Disposal — Dispose of in accordance with local, State and Federal regulations. Do not dump in sewers. Use sand or other non-combustible absorbent material to clean up spill and place in container for later disposal. Do not puncture, incinerate, or reuse container.

RCRA Status — Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Section 7 ~ Handling and Storage

Handling And Storage — Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

Other Precautions — Keep out of the reach of children.

Incompatibility — Strong acids, strong oxidizing agents (chlorine and other halogens, chromates, perchlorates and oxygen.).

Section 8 ~ Exposure Controls/Personal Protection

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Propane/n-Butane	1000 ppm	1000 ppm
Hexane	500 ppm	500 ppm
Heptane	500 ppm	400 ppm
Light Aliphatic Solvent Naphtha	300 ppm	300 ppm

Engineering Controls / Ventilation – Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

Respiratory Protection - If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

Hand Protection - Chemical resistant gloves Eye/face protection - Safety glasses

Additional Measures - Wash hands thoroughly after handling.

Section 9 ~ Physical Chemical Properties

Section > 1 hjstem chemical 1 repetition				
Boiling Point	N/D	Specific Gravity	0.690	
Vapor Pressure (mm Hg)	N/D	Freezing Point	N/D	
Vapor Density	> 2	Evaporation Rate (Butyl Acetate = 1)	N/D	
Solubility in Water	0%	рН	N/A	
Appearance and Odor— Opaque red spray, petroleum odor		VOC%	79%	
Flash Point (Method Used): -132°F	Flammability: Extremely Flammable Aerosol	Lower Flammability Level: N/D	Upper Flammability Level: N/D	

Section 10 ~ Stability and Reactivity

Stability:	Unstable	Stable 🔀	1		Hazardous Polymerization:	May Occur	Will Not Occur
Incompatibility (Materials to Avoid) – Strong acids, strong oxidizing agents (chlorine and other halogens, chromates, perchlorates and oxygen.)		Hazardous Decomposit products.	tion or Byproducts –	Oxides of Carbon, and	other Decomposition		

Reactivity -- None Known

Section 11 ~ Toxicological Information

Toxicological Information — Hexane (110-54-3) LD50 (Oral, Rat) > 5000 mg/kg; LD50 (Dermal, Rabbit) > 2000 mg/kg; LC50 (Inhalation, Rat, 4hrs) > 3367 ppm

Routes Of Entry: Eyes, Ingestion, Inhalation, Skin

Eyes — May cause burning, irritation, redness, tearing.

Ingestion — No toxicity expected with normal use.

Inhalation-No hazards with normal use. May causes dizziness.

Skin — Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

Medical Condition Aggravated — Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

Acute Health Hazards — Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: Anesthetic, irritation, Central Nervous System depression. Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

Chronic Health Hazards — Excessive exposure may result in peripheral neuropathies due to n-hexane. Symptoms would be sensory numbness and possible motor weakness in extremeties.

Carcinogenicity: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

Section 12 ~ Ecological Information

Ecological Information — Not Established

Biodegradability — This product is biodegradable.

Bioaccumulation — This product is not expected to bioaccumulate.

Soil Mobility — This product is mobile in soil.

Other Ecological Hazards — This material is toxic to aquatic life.

Section 13 ~ Disposal Considerations

Waste Disposal — Dispose of in accordance with local, State and Federal regulations. Do not dump in sewers. Use sand or other non-combustible absorbent material to clean up spill and place in container for later disposal. Do not puncture, incinerate, or reuse container.

RCRA Status — Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal(40 CFR 261).

Section 14 ~ Transport Information

US Depart. of Transportation (DOT)		Water Transportation (IMDG)		Air Transportation (IATA)	
Proper Shipping Name:	Aerosols, Ltd. Qty.	Proper Shipping Name:	Aerosols, Ltd. Qty.	Proper Shipping Name:	Aerosols, Ltd. Qty.
Hazard Class/Division:	2.1	Hazard Class/Division:	2.1	Hazard Class/Division:	2.1
UN Number:	UN 1950	UN Number:	UN 1950	UN Number:	UN 1950
Packing Group:	N/A	Environmental Hazard:	Marine Pollutant	Packing Group:	-

Section 15 ~ Regulatory Information

TSCA Status — All Chemicals are listed or exempt.

CERCLA (Comprehensive Response Compensation, And Liability Act) — None

SARA 311/312 Hazard Categories — Acute Health, Chronic Health - Fire

SARA 313 Reportable Ingredients — n-Hexane CAS # 110-54-3

State Regulations — California Proposition 65: None

International Regulations: All components of this product are on the Canadian DSL list.

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	1	1	4= Severe
FLAMMABILITY	3	3	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	None	В	1= Slight
			0= Minimal

Disclaimer: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for so, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.