

# Red I Grease

Non-Melt Spray Grease



**RED I GREASE** is a cured lubricant that withstands heat to 350°F, moisture, acids, high pressure and is highly rust resistant. This VOC compliant formula provides superior lubrication while forming a thick, long-lasting film to prevent future corrosion. A high pressure additive reduces wear and prolongs operational life of all machinery. Temperatures above 350°F may require periodic reapplication. Use on chains, winches, conveyors, gears, cables, tools, hinges, bushings, pins, levers and rollers.

**Directions:** Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.

Health	1
Flammability	3
Reactivity	0
Protection	B

**Areas of Use:**

- \*Wire rope
- \*Open gears
- \*Linkages
- \*Draglines
- \*Fittings
- \*Winches
- \*Cranes
- \*Cables
- \*Rollers

Appearance and odor.....	Opaque red spray with petroleum odor.
Specific Gravity.....	0.850
VOC.....	79%
Net Wt.....	14 oz.

***Omega Industrial Supply, Inc.***

Fairfield, CA 94534  
 1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134