

# Protect-All



Weather protection  
for electrical connections



This product was engineered to keep electrical connectors and terminals free from contaminants. **PROTECT-ALL** protects parts and components from wind, dirt, airborne particles and water (even when submerged). May be used on terminals and connectors. **PROTECT-ALL** absorbs vibrations, is extremely durable, flexible, and has a high di-electric strength. This product is not suitable for use on running electrical motors or live wires. Electrical equipment should be disconnected before use.

**Directions:** Clean wires and terminals to be sealed with Omega's **ENVIRO TAC** contact cleaner or **MEGA SAFE** safety solvent and allow to dry. Shake container well before and during use. Due to the amount of rubber in this product, the nozzle may occasionally clog momentarily and sputter. Continue spraying, clog will clear after a few moments. Cover the entire connection area. Allow to dry for about 45 minutes. Apply a second coat if greater thickness is desired.

**Areas of Use:**

- \*shipyards
- \*electrical shops
- \*around electrical boxes
- \*municipalities
- \*utilities
- \*schools

Health	3
Flammability	4
Reactivity	0
Protection	B

Appearance and odor.....	Clear coating, mild odor
Specific Gravity.....	Concentrate - 0.77
Propellant.....	Mixture
VOC.....	1.40 MIR
NFPA Fire Rating.....	Extremely Flammable Spray

**ONLY OMEGA™**

Fairfield, CA 94534  
1-800-571-7347 [www.onlyomega.com](http://www.onlyomega.com) Fax: 707-864-8134